

CRANE REMOTES

WD CONTROLLER



NON-PROPORTIONAL



PROPORTIONAL



LW CONTROLLER



FEATURES

- WIRED
- 6' LANYARD
- 2 FUNCTION CONTROLLER
- ROPE, LUFFING

- WIRED
- 15' LEAD
- 4 FUNCTION CONTROLLER
- ROPE, ROTATION, LUFFING, EXTENSION

- WIRED
- 15' LEAD OR 20' LEAD
- 4 FUNCTION CONTROLLER
- ROPE, ROTATION, LUFFING, EXTENSION

- WIRELESS
- 2 CONTROLLERS
- DUAL ACTING SOLENOID
- RANGE UP TO 50'

APPLICATION

WD600, WD800, WD1000

E1000, E1100, ES1000, ES1100

ES1500, ES1750, CT2000, CT2500, CT3500, CT4000, CT5000, CT6000

LW250

SM-1



HEIGHT 2.75"

WIDTH 5.12"

PORPORTIONAL GUIDER



HEIGHT 8.60"

WIDTH 4.90"

MACRO CONTROLLER



HEIGHT 4.70"

WIDTH 2.59"

MICRO CONTROLLER



HEIGHT 2.80"

WIDTH 1.75"

FEATURES

- WIRELESS
- 4 FUNCTION CONTROLLER
- ROPE, ROTATION, LUFFING, EXTENSION
- IP67 RATED
- AAA BATTERIES
- RANGE UP TO 100'

- WIRELESS
- 4 FUNCTION CONTROLLER
- ROPE, ROTATION, LUFFING, EXTENSION
- PROPORTIONAL TRIGGER CONTROLLED
- TWIST TO RELEASE E-STOP SAFE SHUTDOWN
- RANGE UP TO 1000'
- RECHARGEABLE BATTERY

- WIRELESS
 - 4 FUNCTION CONTROLLER
 - ROPE, ROTATION, LUFFING, EXTENSION
 - BATTERY LIFE 40 HOURS
 - MICRO USB CHARGER
 - RANGE UP TO 600'
 - CLONEABLE TRANSMITTER
- (CAN HAVE MORE THAN ONE CONTROLLER PER RECEIVER)

- WIRELESS
 - 4 FUNCTION CONTROLLER
 - ROPE, ROTATION, LUFFING, EXTENSION
 - BATTERY LIFE 40 HOURS
 - MICRO USB CHARGER
 - RANGE UP TO 600'
 - CLONEABLE TRANSMITTER
- (CAN HAVE MORE THAN ONE CONTROLLER PER RECEIVER)

APPLICATION

ALL E, ES & CT CRANES

ES1500, ES1750, ES2200, ES2500, ALL CT CRANES

ES1000 & ES1100

ES1000 & ES1100