



AUT-O-LOC Safety Strap

Engineered to be the strongest safety strap for folding basketball standards!

The **AUT-O-LOC** Safety Strap is the only safety strap designed specifically for folding basketball standards. Not only is the design proven, it is patented. It employs a unique, multi-pawl design with a fall-sensing inertia plate to detect backstop falls and immediately stop them. The housing is machined from high strength heat treated aluminum alloy for maximum strength and failsafe operation. After twenty years of protecting gyms, it's still the number one choice of leading gymnasium equipment manufactures.

The **AUT-O-LOC** is uniquely engineered to provide two-fold protection in the event of a backstop fall. First, the patented inertia plate senses the centrifugal force of a fall. Then it engages three unique steels pawls that each lock into the teeth of a cast housing. It instantly stops the load before it gains momentum, damages the gymnasium structures, or, worse, injures players and spectators.

Universal mounting clamps allow for installations parallel or 90 degrees to the backboard. Each pipe clamp is tested prior to shipment. The unique design is patented and proven with over twenty years of installation and worry-free safety for players, spectators, and the structural integrity of you gymnasium. The patented inertia plate triggers three unique steel pawls simultaneously engaging the locking teeth within the all-aluminum cast housing.

Product Specifications:

Lightweight unit weighing just 14 pounds/6.34 kilograms. The unit is rated for a maximum of 1,000 pounds/453.51 kilograms. Silent Continuous Sensing of inertial and centrifugal forces provides security in the case of an immediate fall or an unexpected increase in speed. Fully automatic system, so there's no need to reset to reset handles, ropes, levers, or buttons. Constant protection that is fully functional during the storage, raising and lowering of equipment. Spring loaded to retract up to 35 feet/10.66 meters of standard belt stored in the housing unit. Sets by inertial force for immediate and positive setting, or centrifugal force. Easy installation with standard pipe clamps for 3 1/2 inch/8.88 centimeter outside diameter.



PRODUCT SPECIFICATION

BA950LR: AUT-O-LOC SAFETY STRAP

REVISED 3/9/23