

Bench legs shall be constructed of 2" x 2" square aluminum tubing with a 12 ga. wall thickness and polyester powder coated finish. Leg length shall allow 12" bury into a 30" deep concrete footing. All exposed tube ends shall be enclosed by means of molded plastic end caps. Bench shall be 7 1/2' in length to accommodate up to 5 players. Seat shall be extruded aluminum with clear anodized finish designed to provide a 10" wide plank with a 1 3/4" overall thickness and have molded end caps. For powder coated aluminum seat planks, order optional BL07SEAT1-XX. Choose any combination of colors: Royal, Scarlet, Navy, Forest Green, Black and White. The planks shall have a minimum cross section thickness of .090". Planks shall be attached to two tubular leg assemblies. All assembly hardware shall be zinc plated. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. Bench shall carry a 5-year limited warranty on legs and 2-year limited warranty on aluminum planks and shall weigh 30#.



PRODUCT SPECIFICATION

BNF0701 7 1/2' FIXED PLAYER BENCH

REVISED 11/8/23 L.M.

603 L Street, Lincoln, NE 68508 - Phone: (800) 247-7668 - Fax: (800) 638-0698 - www.bisoninc.com - info@bisoninc.com