



Bench legs shall be constructed of 2" x 2" square aluminum tubing with a 12 ga. wall thickness and a polyester powder coated finish. 3" diameter rubber molded feet shall attach to the bottom of legs at 6 places to prevent scratching of floors. All exposed tube ends shall be enclosed by means of molded plastic end caps. Bench shall be 15' in length to accommodate up to 10 players. Seat and seat back shall be extruded aluminum with clear anodized finish designed to provide a 10" wide plank with an overall thickness of 1 3/4" and have molded end caps. Seat and foot planks in excess of 7 1/2 shall be shipped in 2 or 3 piece sections. Each section shall be connected to the adjoining section at assembly by means of two aluminum extrusion connector tubes, and 8 self drilling, self-threading hex screws. The aluminum planks shall have a minimum cross section thickness of .090". For Powder Coated Aluminum Seat Planks order optional BL15SEAT1-XX for each plank. Choose any combination of colors: Royal, Scarlet, Navy, Forest Green, Black and White. Plank and setback shall be attached to three tubular leg assemblies. All assembly hardware shall be zinc plated. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. Bench shall carry a 5-year limited warranty on legs and a 2-year limited warranty on aluminum planks and shall weigh 75# on BNP1501BAA.



PRODUCT SPECIFICATION

BNP1501B 15' PORTABLE PLAYER BENCHES WITH BACKREST

REVISED 11/8/23 L.M.