

Bench legs shall be constructed of 2" x 2" square aluminum tubing with a 12 ga. wall thickness with a polyester powder coated finish. 3" diameter rubber molded feet shall attach to the bottom of the legs at eight places to prevent scratching of floors. All exposed tube ends shall be enclosed by means of molded plastic end caps. Bench shall be 21' in length to accommodate up to 14 players. Seat shall be extruded aluminum with clear anodized finish designed to provide a 10" wide plank with an overall thickness of 1 3/4" and have molded end caps. Seat and foot planks in excess of 7 1/2' Shall be shipped in 2 or 3 piece sections. Each section shall be connected to the adjoining section at assembly by means of two aluminum extrusion connector tubes, and 8 self drilling, self-threading hex screws. For powder coated aluminum seat planks, order optional BL21SEAT1-XX for each plank. Choose any combination of colors: Royal, Scarlet, Navy, Forest Green, Black and White. The aluminum planks shall have a minimum cross section thickness of .090". Plank shall be attached to four tubular leg assemblies. All assembly hardware shall be zinc plated. Installation to be completed in accordance to manufacturer's instructions. Do not scale drawings. Bench shall carry a 5-year limited warranty on legs and 2-year limited warranty on aluminum planks and shall weigh 60#.



PRODUCT SPECIFICATION

BNP2101 21' PORTABLE PLAYER BENCH

REVISED 11/8/23 L.M.

603 L Street, Lincoln, NE 68508 - Phone: (800) 247-7668 - Fax: (800) 638-0698 - www.bisoninc.com - info@bisoninc.com