


























### ACMER 1064nm Infrared Laser Module-P1

| Materials               | Line Interval | Speed (mm/m) | Max-Power | Image Mode | Engraving Effect  | Note |
|-------------------------|---------------|--------------|-----------|------------|---|------|
| Yellow Copper           | 0.03          | 10000        | 80%       | Threshold  |    |      |
| Purple Copper           | 0.03          | 10000        | 80%       | Threshold  |    |      |
| Iron                    | 0.03          | 10000        | 100%      | Threshold  |    |      |
| Galvanized Sheet        | 0.03          | 10000        | 80%       | Threshold  |    |      |
| Natural Color Alumina   | 0.03          | 10000        | 80%       | Threshold  |   |      |
| Coated Alumina          | 0.03          | 10000        | 80%       | Threshold  |  |      |
| Brushed Stainless Steel | 0.03          | 10000        | 80%       | Threshold  |  |      |
| Mirror Stainless Steel  | 0.03          | 10000        | 80%       | Threshold  |  |      |
| Acrylic                 | 0.03          | 5000         | 100%      | Threshold  |  |      |
| ABS                     | 0.03          | 5000         | 100%      | Threshold  |  |      |
| Artificial Leather      | 0.03          | 10000        | 60%       | Threshold  |  |      |
| Black Tile              | 0.03          | 200          | 100%      | Threshold  |  |      |

|                            |      |       |      |           |  |  |
|----------------------------|------|-------|------|-----------|--|--|
| Rubber                     | 0.03 | 10000 | 60%  | Threshold |   | The engraving effect must be viewed in a well-lit place.   |
| Bakelite                   | 0.03 | 3000  | 100% | Threshold |   | Avoid direct light shining on the engraving surface. You can place the light source on the back of the engraving surface to view the engraving effect. |
| PCB                        | 0.03 | 10000 | 100% | Threshold |   |  |
| Rock                       | 0.03 | 200   | 100% | Threshold |   | The stone has many curved surfaces and cannot guarantee a uniform focal length. There may be different shades of engraving effects.                    |
| Spray-painted Wooden Board | 0.03 | 10000 | 80%  | Threshold |   |  |
| Wood Glue Board            | 0.03 | 8000  | 100% | Threshold |  |  |

### ACMER 1064nm Infrared Laser Module-P2

| Materials               | Line Interval | Speed (mm/m) | Max-Power | Image Mode | Engraving Effect  | Note |
|-------------------------|---------------|--------------|-----------|------------|---|------|
| Yellow Copper           | 0.03          | 30000        | 100%      | Threshold  |    |      |
| Purple Copper           | 0.03          | 30000        | 100%      | Threshold  |    |      |
| Iron                    | 0.03          | 30000        | 100%      | Threshold  |    |      |
| Galvanized Sheet        | 0.03          | 10000        | 100%      | Threshold  |    |      |
| Natural Color Alumina   | 0.03          | 30000        | 100%      | Threshold  |    |      |
| Coated Alumina          | 0.03          | 30000        | 65%       | Threshold  |   |      |
| Brushed Stainless Steel | 0.03          | 30000        | 100%      | Threshold  |  |      |
| Mirror Stainless Steel  | 0.03          | 30000        | 80%       | Threshold  |  |      |
| Acrylic                 | 0.03          | 20000        | 100%      | Threshold  |  |      |
| ABS                     | 0.03          | 20000        | 100%      | Threshold  |  |      |
| Artificial Leather      | 0.03          | 30000        | 65%       | Threshold  |  |      |
| Black Tile              | 0.03          | 300          | 100%      | Threshold  |  |      |

|                            |      |       |      |           |   |   |
|----------------------------|------|-------|------|-----------|---|---|
| Rubber                     | 0.03 | 30000 | 65%  | Threshold |  | The engraving effect must be viewed in a well-lit place.                |
| Bakelite                   | 0.03 | 5000  | 100% | Threshold |  | Avoid direct light shining on the engraving surface. You can place the  |
| PCB                        | 0.03 | 30000 | 100% | Threshold |  |   |
| Rock                       | 0.03 | 500   | 100% | Threshold |  | The stone has many curved surfaces and cannot guarantee a uniform focal |
| Spray-painted Wooden Board | 0.03 | 30000 | 80%  | Threshold |  |   |
| Wood Glue Board            | 0.03 | 30000 | 100% | Threshold |  |   |