

# THE DUTCH

## Installation



## Front Rack Jordaan - The Dutch

### In the box:

Front Rack	1x	
Bungees	1x	
Allan Key (tool)	1x	
Stays	2x	
Bolt large	1x	
Bolt small	4x	
Nut	2x	
Ring large	1x	
Ring small	6x	

### Installation Instructions:

Video instructions are available on:  
[www.lekkerbikes.com/lekker-bikes-assembly/](http://www.lekkerbikes.com/lekker-bikes-assembly/)  
 and via the QR code on the bottom.

#### 1. Install the stays

Using the four small bolts, marry the carrier with the stays. **3** Put a small ring around the bolts and slot them trough the top holes of the stay. (Orientation - see picture) Place over the holes on the rack and push trough. Place a small ring over the bolts at the rear, followed by a small nut. Loosely fasten using the allan key and a wrench. Repeat for both sides.

#### 2. Connect to the frame

Remove the front light if fitted on bike. Locate the bolt at the top of the fender. **2** Unscrew fully using the allan key. Place the new front rack in front of the hole and use the large delivered bolt to fasten. Put the large ring over the bolt before screwing in. Use the allan key and screw in loosely.

#### 3. Connect to the fork

At the lower end of the front wheel placeholder (the 'fork') there are two bolts holding the fender in place **1**, one on either side of the bike. Unscrew these bolts from the fork. Place the bottom end of the stav in place over the

hole, and reuse the bolt with small ring to loosely hold it into place. Screw in using the allan key. Repeat on both sides.

#### 4. Tightening

Tighten the large bolt **2** with the allan key. Tighten the bolts on the fork. **1 + 3** Check if tight by shaking carrier up and down. When rattling is heard or too much movement is felt, tighten all bolts and nuts one more time.

#### 5. Front Light

Install the front light in the bracket **4** reusing the bolt and nut that it was fastened with or with a delivered bolt. Tighten using the allan key and a wrench.

#### 6. Finishing touches

Grab the bungees and strap them from left to right over the rack. The hooks slot into the slots on the stays, or on the front and rear slots on the rack itself.



Enjoy the ride!

