


- Make sure the waterproof lid is mounted when connecting



Touch the image on the screen to start live video

# **COMPUTER SET UP**



www.luda.farm/farmcam2.0 View all of your cameras on your computer

### **LEARN MORE**

Learn more about extra features for FarmCam 2.0 application. Scan below QR code with your mobile phone to access our guidelines



# **INCLUDED IN THE BOX**



Push notifications

Flex Hub (Art.no 1122)

Flex 5MP camera

(Art.no 1121)

Motion alarm

Bridge 300 (Art.no 1123)

EPOWER adapter (Art.no 1124)

10 m combined network and power cable (Art.no 5055)

> Network extender female to female RJ45 (Art.no 5029)

> > Screw kit

# ICON SUMMARY



# **TECHNICAL SPECIFICATION**

Operating temperature:

IP classification:

Angle of view:

Power source:

PoE standard:

LED indicator:

Power supply:

Bridge 300 art. no 1123

Working temperature:

Storage temperature:

Working humidity:

Storage humidity:

Wireless standard:

IP classification:

Frequency:

Wireless standard:

Consumption:

IP classification:

Ports:

Night vision range:

Image resolution:

Storage (Micro-SD):

Flex Hub art. no 1122

Port power voltage:

Max. port power:

Recording frame rate:


Flex 5MP Camera art. no 1121 80° horizontal, 42° vertical 64 GB included (max 256 GB) IEEE 802.3af, 48 V Active (PoE)

1×100 Mbps for WAN 4×100 Mbps PoE ports for LAN IEEE 802.3AT/ IEEE 802.3AF 48 V 30 W 5 green link/active LEDs IP44 -20 °C to 55 °C (-4 °F to 131 °F) -40 °C to 85 °C (-40 °F to 185 °F) 100 to 240 V, 50/60 Hz, max 6.5 A 5.5 W


Operating temperature: Storage temperature: Power consumption in idle:

IEEE802.11b/g/n <8 W -40\*C~55\*C -50 C~75 C 10%~90%RH non-condensing 5%~90%RH non-condensing IP65 2.3Ghz-2.7Ghz IEEE802.11b/g/n


**INSTALL WATERPROOF LID** When mounting your camera outdoors, make sure to install the wareproof lid on the end of the cables for camera and Flex Hub \*



Remove the rubber seal ring and insert the Ethernet cable through the waterproof lid




2 Apply the rubber seal ring on the Ethernet cable between the top cover and waterproof connector




**3** Apply rubber O-ring to the Ethernet port, then plug in the Ethernet cable to the Ethernet port

\*It is necessary for the waterproof lid to be installed in order for the system to be covered by the warranty



4 Align waterproof connector with the Ethernet port and twist it clockwise to tighten the two parts



5 Push the rubber seal ring into the waterproof connector and screw the top cover and lock it into position firmly to finish installation

0



















### TROUBLESHOOTING

1. The camera will not connect
Pull out the powerplug of the Flex Hub and put it back in,
wait for 2 minutes and try to connect again
2. I have forgotten my camera password
Reset the camera by holding the button on the camera cable
for at least 5 seconds
3. The camera is disconnected
Try connect the camera to another port on the Flex Hub,
if still not connecting try to reset the camera
4. My connection is bad
Make sure there is no obstacle or units that interrup
the signal between the antennas
5. Camera has no power
Make sure there is power connected to the Flex Hub. If the led
indicator on the pigtail from Flex Hub is blinking green it
provides power to the camera
6. I cannot use the camera wirelessly
The cameras must be connected to Flex Hub with cable
7. The image is black and white
Use more lights in the camera area as the IR light of the
camera is activated in dark conditions, which makes the
image black and white
8. Further questions?
You are always welcome to visit our website www.luda.farm
or contact your local sales representative

-10°C +55°C IP66 Up to 30 meters 2560 x 1920p Up to 30 fps FAO

- 1. Can anyone see my camera? No, they would have to access your Device ID and password of your camera
- 2. How can I customize my farm according to the features of the device? To optimize the device best way for your use, please visit
- www.support.luda.farm and read our FarmCam 2.0 guides 3. The image is frozen when I'm in the main window
- Yes, the image is only updated when you select the camera. Click on the picture and you will get live video
- 4. Can I connect several cameras to my phone? Yes, just add another camera by pressing the "+" sign on top right in main window
- 5. Is the signal from the camera encrypted? Yes
- 6. Is the camera water resistant? Yes, the camera is IP66 rated which means it is well protected and can be placed outside and even washed off with a hose.
- 7. Can I hear sound from the camera? Yes, just press the speaker symbol (second from the left) when in live video mode
- 8. Can I save pictures from the camera to my phone? Yes, press the picture camera icon (third from left) when in live video mode
- 9. Can I record a video from the camera to my phone? Yes, by pressing the film camera icon (fourth from the left)
- 10. Can i add another Flex Hub to expand my network?
- Yes, each Flex Hub has a cable "Link option", connect a network cable between both to expand your network

