

# TECHNICAL SPECIFICATION

Luda.Farm – SmartPlug – Art. No. 1071

## GSM / Mobilnätverk

2G Dual-band 900/1800 MHz

## Power Input / Puissance d'utilisation / Netzstrom / Ineffekt

AC110-250V/50Hz

## Maximum Load / Puissance maximum / Maxim. Stromaufnahme

Maximal belastning

250V / 16A

## Operating Temperature / Température de fonctionnement du capteur

Betriebstemperatur / Drifttemperatur

-20°C to +60°C

## Storage Temperature / Température de stockage du capteur

Lagertemperatur / Förvaringstemperatur

-20°C to +70°C

## Protection Class / Classe IP / Schutzklasse / Skyddsklass

IP20 only internal operation / IP20 utiliser à l'intérieur uniquement

IP20 nur Inneneinsatz / IP20 endast för inomhusbruk

## Temperature Sensor Cable Length / Longueur du câble thermomètre

Temperatur Sensor Kabellänge / Längd kabel temperatursensor

3m

## Temperature Sensor Range / Détection de la température

Temperatur Sensor Bandbreite / Räckvidd temperatursensor

-20°C to +70°C

## Temperature sensor accuracy / Précision du thermomètre

Schwankungsbereich Temperatursensor / Noggrannhet temperatursensor

±2°C



# SmartPlug

## QUICK GUIDE



# LUDA FARM

Luda.Farm, Krokslätts fabriker 30, 43137 Mölndal, Sweden



→ [support.luda.farm](https://support.luda.farm)

## INCLUDED IN THE BOX



### Luda.SmartPlug

Art. No. 1071



### Temperature Sensor

Thermomètre  
Temperatursensor

Art. No. 6052

## INSTALLATION



Download on the  
App Store

ANDROID APP ON  
Google play

My.Luda.Farm



PC/Mac



[www.my.luda.farm](http://www.my.luda.farm)



## FUNCTIONS



### Manual ON/OFF

Activation manuelle ON/OFF  
Manuell Ein/Aus  
Manuell Av/På-knapp

### Reset

Réinitialiser  
Zurücksetzen  
Återställa

### GSM

### USB port - No function today

Port USB / Pas de fonctions aujourd'hui  
USB Anschluss/ohne Funktion  
USB-port - Ingen funktion i dagsläget



[support.luda.farm](http://support.luda.farm)