



Technical Specification for Article: BD9788

Color	Black /Yellow
Size Range	Euro : 37 - 48 UK : 4 - 13 US : 5 - 14
Type of construction	Vulcanized Rubber Upper and Sole. European Standard, CE Approved – EN 345-2:1996.
Compliance	CSA –Canadian Standards Association. ANSI – American National Standard
Air pressure applied for water leakage testing	50 kPa
Lining Material	Leg Lining : Woven Cotton Canvas Weight (min.) 250g/m ² Thickness (min.) 0.60mm. Insole Lining : Woven Sheeting Weight (min.) 140g/m ² Thickness (min.) 0.30mm.
Rubber Components	Upper : Black in Colour, 65% Natural Rubber 30% Styrene Butadiene Rubber and 5% Chloroprene Rubber. Foxing : Yellow in Colour, 65% Natural Rubber 30% Styrene Butadiene Rubber and 5% Chloroprene Rubber.
Thickness of Upper and Fabric Combined	1.80mm (Minimum)
Sole / Heel	Black in Colour, 80% Chloroprene Rubber & 20% Nitrile Rubber Oil Resistant – Immersion in iso-octane (22 hours at 22 °C) 12% max change in volume. Abrasion Resistant – DIN 53516 : 250mm ³ max. Hardness Shore A : 65 ± 5.
Sole Protection	Electric Shock Resistant, meets CSA – Z195-M92,
Steel Midsole	One piece Stainless Steel, meets CSA-Z195-M92 Sole Penetration and EN 345 Flexing test.
Steel Toe	Meets EN 345 Impact and Compression.
Chemical Resistant	Upper -Resistant towards mild acids and alkali. Sole – Resistant towards mild acids.
Finishing	Hypalon Lacquer.
Packing	Polybag 6 pairs / carton.