

BEST BOY / M-8027

BEST BOY S3 SRC Steel Toe/Steel Plate PU/PU High Ankle Shoe



CE EN ISO 20345:2011 S3 SRC



FEATURES:

- Upper: High quality embossed cow leather
- Lining: Breathable & Abrasion resistant sandwich
- Insock: Anti-static breathable EVA insock
- Outsole: PU/PU injection, dual density
- Tested : By UK Intertek lab (Appoved body:0362)
- Toe: Steel toe cap to resist 200 joules impact
- Penetration: Steel plate to resist 1100 newtons puncture

ERP Code: S5020128
Size: 38 – 46

G.Weight: 13kgs/carton
Carton dimension: 62x48x33cm
Cubic meter/Carton: 0.098208
Packing: 10PCS/Carton



200 JOULE
TOECAP



SLIP-
RESISTANT



SHOCK
ABSORPTION



ANTI-STATIC



PETROL AND
CHEMICAL
RESISTANT



ANTI-NAIL
MIDSOLE



WATER
RESISTANT



OIL
RESISTANT



ELECTROSTATIC
DISCHARGE

BEST BOY / M-8027

BEST BOY S3 SRC Steel Toe/Steel Plate PU/PU High Ankle Shoe



Outsole material:

The outsole is made in PU/PU dual density. The midsole is 45 degree hardness PU, which is soft and shock absorption. The outsole is 60-65 degree hardness PU, which is tough and abrasion resistant. The outsole can pass SRC slip-resistant test.



Insock material:

J-001 insock design, the ventilation fabric can absorb 90% sweat and dry feet efficiently. U-design support heel can disperse human weight pressure, and reduce friction between feet and shoes. EVA material is soft and flexible, to increase comfortability during walk.



Toe protection:

Stainless steel toe cap can reach 200 joules. It is more strong than iron toe cap.



Penetration protection:

Steel plate, is zero-penetration resistant, which can resist 1100 newtons nail puncture. It is more strong and flexible than normal iron plate.



SRC		
SRC (SRA+SRB)		
SRA CERAMIQUE + EAU ET	PLAT ≥ 0.32 TALON (RELIEVE ?) ≥ 0.28	0.52 0.48
SRB ACIER + GLYCÉRINE	PLAT ≥ 0.18 TALON (RELIEVE ?) ≥ 0.13	0.23 0.18

EN ISO 20345: 2011

Usage & Storage:

1. Recommended places: Basic workplace, construction, logistics, mechanics, chemical factory, electronic factory, mining, food & Health etc

2. It is very important that shoes selected must be suitable for the right workplace and environment. The protection against risks or hazards which are not mentioned in this document is not warranted. The levels of performance mentioned are not valid for fire, water, electric etc.

3. Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum upto 14/12/2010 for intermediate design category products. This has been shown through satisfactory testing to EN ISO 20345:2011 and examination of the Technical File Documentation.

BEST BOY / M-8027

BEST BOY S3 SRC Steel Toe/Steel Plate PU/PU High Ankle Shoe



Intertek

EC Type Examination Certificate



Approved Body 0362

The safety footwear detailed herein meets the criteria of an EC Type Examination in accordance with Article 10 of the PPE Directive (89/686/EEC) including amendments and corrigendum up to 14/12/2010 for intermediate design category products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EC Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 13 of the PPE Directive (89/686/EEC).

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311



www.intertek.com

Issued to	: Shanghai Lanfeng Industrial Co.,Ltd Room 908 Building 1, Luxiang Road, 111, Shanghai, China
Manufacturer	: Shanghai Lanfeng Industrial Co.,Ltd Room 908 Building 1, Luxiang Road, 111, Shanghai, China
Date of Issue	: 18 July 2017
Expiry Date	: 18 July 2022
Certificate No.	: LEC F100368246
Product Reference(s)	: M-8402, L-7315, M-8025, L-7001, L-7002, L-7003, L-7015, L-7141, M-8138, L-7252, M-8001, M-8027, M-8070, M-8316
Description	: Construction : Injection Toecap : Steel toecap Insert : Steel plate Last : 604# Sole : PU/PU Mould : 05 Test Report(s) : See technical file Size Range : 36#-48# Category : S3 SRC

P. Wilkense
Assessor

18/07/2017

Date

M. Carter
Certification Manager

18/07/2017

Date

For and on behalf of ITS Testing Services (UK) Limited

Registered in England No. 1408284 Registered Office: Academy Place, 1-8 Brook Street, Brentwood, Essex, CM14 5NQ

This certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Certificate. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.