## Gorilla Flex Cut C3

Nitrile foam finish palm coated cut resistant glove



Standards: CE Cat. II EN 388:2016 4X43B EN ISO 21420:2020, EN 407:2004

## Features:

Unique NBR micro foam finish provides excellent dry, wet & oil grip performance. 360 degree breathable coating keeps hand cool & comfortable.

Ergonomically design for superior fit, feel & comfort. Special blend of engineered covered yarn for high cut performance & protection. Excellent abrasion resistance allows long term use and better durability.

> Product is in compliance with reach directives, Oeko Tex certified & azo free dyestuff. Coating: Black nitrile rubber coating.

30% coating content.

Liner: 18GG machine knitted.

Melange green & melange

orange. HPPE, polyester, glass, nylon & spandex.

70% liner content.

Length: 210-280mm. Size: Medium, Large, XLarge.

Packing:

12 Dozen/carton

**Carton Dimension:** 

42x29x40 cms

**Carton Weight:** 

Gross Weight: 9.26kgs/carton Net Weight: 8.06kgs/carton

Volume:

0.0487CBM


Origin:

Sri Lanka

Application:

Automotive, construction, mechanical assembly, precision machinery, engineering, workshop & oil & gas Industry.





Gorilla Flex Cut C3 E142573520 E142573521 E142573522

EN 407:2004 EN 388:2016



