


# Radiant



<p>سلامة سترة الخارجي نسيج: 100% بوليستر شريط عاكس: 100% بوليستر صنع في الصين تعليمات الرعاية غسالة: 40°C (104°F) لا تستعمل بيض حديد بارد تمشتر منخفض جاف لا تستخدم التنظيف الجاف الحد الأقصى 25 يغسل</p> 	<p><b>SAFETY VEST</b> Outer Fabric: 100% Polyester Reflective Tape: 100% Polyester Made in China</p> <p><b>CARE INSTRUCTIONS:</b> Machine wash 40°C (104°F) Do not bleach Tumble dry low Cool Iron Do not dry clean Max 25 washes</p> 
---	--



Vest Label Ensures Proper Use of Performance Material and Care of Vest

Contrasting Trim Maximizes Daytime Visibility

3M2925 tape for high visibility

Fluorescent High Visibility Background Material for Daytime Visibility

## Specifications

ANSI Requirements	ANSI/ISEA 107-2010 Class 2
European Norm	EN ISO 20471:2013
Color	Yellow/Orange
Features	2" 3M2925 tape for high visibility 4 Pockets, Zipper Closure
Product Type	High Visibility
Size	S1 – S7



The American National Standard for High-Visibility Safety Apparel and Headwear, (ANSI/ISEA 107-2010), which sets the performance criteria for high-visibility apparel. This safety apparel consists of background material, retroreflective material, and combined-performance material:

- Background material is “colored fluorescent material intended to be highly conspicuous, but not intended to comply with the requirements... for retroreflective material.”
- Retroreflective material is “material that reflects and returns a relatively high proportion of light in a direction close to the direction from which it came.”
- Combined-performance material is “retroreflective material that is also a fluorescent material and can be counted toward the minimum area requirements for background material.”

ANSI/ISEA also has three numbered performance classifications for high visibility apparel:

### Performance class 1

- Minimum background material: 217 in.<sup>2</sup>
- Minimum retroreflective material: 155 in.<sup>2</sup>
- Provides the minimum amount of required material to distinguish the wearer from the environment.
- Intended for workers whose tasks don't divert their attention from approaching traffic.
- Intended for locations where the worker is separated from traffic, which is traveling no faster than 25 mph.

### Performance class 2

- Minimum background material: 775 in.<sup>2</sup>
- Minimum retroreflective material: 201 in.<sup>2</sup>
- Provides enhanced visibility during inclement weather.
- Intended for workers whose task divert their attention from approaching traffic and for those who must work near vehicles exceeding 25 mph

### Performance class 3

- Minimum background material: 1240 in.<sup>2</sup>
- Minimum retroreflective material: 310 in.<sup>2</sup>
- Provides maximum visibility for workers who have tasks that place them in imminent danger from approaching traffic
- Provides maximum visibility when the wearer must be conspicuous at a minimum distance of 1,280 feet.

**Note:** This product has specification Class 2. A fuller explanation of the standards in this area are shown below.

### EN471 - Specification for High Visibility Clothing

There are 3 classes of garment type based on the levels of conspicuity they provide. On all garments the retro-reflective tape must not be less than 50mm wide.

The table below shows typical recommended performance apparel classifications for various types of jobs. To determine the appropriate apparel, always consider the environmental condition where you'll be working and your risk of exposure:

Type of jobs	Class 1	Class 2	Class 3
shopping cart retrievers	X		
warehouse workers	X		
delivery truck drivers	X		
roadway construction workers		X	X
utility workers		X	X
surveyors		X	X
emergency responders		X	X
flaggers			X

Adapted from ANSI/ISEA 107-2010, Appendix B

**CLASS 3**  
**THE HIGHEST LEVEL OF CONSPICUITY**  
 Minimum background material 0.80m<sup>2</sup>  
 Minimum retro-reflective material 0.20m<sup>2</sup>



**CLASS 2**  
**INTERMEDIATE PROTECTION**  
 Minimum background material 0.50m<sup>2</sup>  
 Minimum retro-reflective material 0.13m<sup>2</sup>



**CLASS 1**  
**LOW LEVEL PROTECTION**  
 Minimum background material 0.14m<sup>2</sup>  
 Minimum retro-reflective material 0.20m<sup>2</sup>



## ERP Code & Packing information:

	DESCRIPTION	SIZE	QUANTITY PER CARTON	CTN L	CTN W	CTN H	GW/NW @ KG PER CARTON	
<b>Radiant - Yellow</b>	E108073101	S	100	45	25	48	14.90	14.40
	E108073102	M	100	45	25	50	14.90	14.40
	E108073103	L	100	45	25	48	14.90	14.40
	E108073104	XL	100	45	25	48	14.90	14.40
	E108073105	2XL	100	45	25	48	14.90	14.40
	E108073106	3XL	100	45	25	48	14.90	14.40
	E108073107	4XL	100	45	25	48	14.90	14.40
	E108073201	S	100	45	25	50	14.90	14.40
<b>Radiant - Orange</b>	E108073202	M	100	45	25	50	14.90	14.40
	E108073203	L	100	45	25	50	14.90	14.40
	E108073204	XL	100	45	25	50	14.90	14.40
	E108073205	2XL	100	45	25	50	14.90	14.40
	E108073206	3XL	100	45	25	50	14.90	14.40
	E108073207	4XL	100	45	25	50	14.90	14.40