## Eye Washer SS-E100

Free-Standing Eye Washer, Stainless Steel, Model: SS-E100



## Features:

Controlled, low velocity flow and uninterruptible water supply at 3gpm Deliver 11.5L of water per minute Valve actuator are easy to locate and readily accessible to user Handsfree stay open valve activate within one second

Supply: 1/2" NPT male inlet

Waste: 1-1/4" NPT female outlet

**Spray Head Assembly:** Two spray heads, each head has a dust cover, internal flow control, and filter to remove impurities from water flow

**Bowl:** 11-1/2" diameter stainless steel bowl Valve: 1/2" 304 stainless steel stay-open ball valve

Standard:

EN 15154-1:2006

EN 15154-2:2006

Packing:

1 piece / packet 1 packet / carton

Carton Dimensions: 91 x 41 x 30 cms

Carton Weight:

Gross Weight: 11.40 kgs. / carton Net Weight: 10.00 kgs. / carton

**Volume:** CBM 0.1119

ODIVI O. ITTS

**Origin:** China

Applications:

Where the eyes and face of any person may be exposed to injurious or corrosive materials, suitable facilities for quick flushing & cleansing of the eyes and face must be provided within the work area for immediate emergency use. Emergency eye/face wash facilities shall be in unobstructed and accessible locations that require no more than 10 seconds for the injured person to reach



M339671021

Connect base unit

waste receptor to waster water

Connect foot panel

chain to hand

panel small hole

Assemble base unit to water •

supplier unit

outlet

## Eye Washer SS-E100

Free-Standing Eye Washer, Stainless Steel, Model: SS-E100

Assembly & Design Specifications

Secure the entire unit

to the floor for stability

Connect hose to

the water supply

