



Addison Heights®

VINYL SIDING



A Multitude of Beauty & Value for *The Good Life*






Accessories Available from Style Crest®

Style Crest offers a full line of exterior finishes, from mounting blocks, gable vents, and shutters to complete decking and railing systems that are guaranteed to give your home maximum curb appeal.

Product Test Data
Premium Vinyl Siding
Addison Heights® Series

HOMEX® Vinyl Siding meets or exceeds all industry standards per ASTM D3679.


Siding Thickness	040" ± .001"
Specific Gravity	1.45
Tensile Strength (PSI)	7,154
Tensile Modulus (PSI)	416,900
IZOD Impact Strength @ 32°F Passes per ASTM D3679	
Heat Deflection Temp. @ 264 PSI	169°F
Coefficient of Linear Expansion	3.30 x 10 ⁻⁵
Warpage	0.00"
Heat Shrinkage	0.3%
Impact Resistance	Passes per ASTM D3679
Surface Distortion @ 140°F	0
Flame Spread Index	10
Fire Rating	Class A
Smoke Developed	395
Fuel Contribution	0
Average Time Of Burning	Self extinguished
Average Extent Of Burning	2.379mm
Weathering	Passes per ASTM D3679



Double 4" 20D4
 Length 12' - 6" | 24 Panels/Ctn. | 2 Sq./Ctn.
 20 Ctns./Crate | Ctn. Weight: 87.08 lbs.

Color Choices


02 White Birch	41 Soft Willow	47 Slate Blue	82 Meadow
11 Classic Sand	43 Pebble Clay	49 Graphite Grey	
17 Warm Sandalwood	44 Harbor Stone	52 Java	
22 Sunny Maize	46 Basket Beige	79 Seagrass	
26 Summer Wheat			



Dutchlap 4.5" 20DL45
 Length 12' - 1" | 20 Panels/Ctn. | 2 Sq./Ctn.
 16 Ctns./Crate | Ctn. Weight: 83.99 lbs.

Color Choices

02 White Birch	41 Soft Willow	47 Slate Blue	82 Meadow
11 Classic Sand	43 Pebble Clay	49 Graphite Grey	
17 Warm Sandalwood	44 Harbor Stone	52 Java	
22 Sunny Maize	46 Basket Beige	79 Seagrass	
26 Summer Wheat			



Dutchlap 5" 20DL5
 Length 12' - 0" | 20 Panels/Ctn. | 2 Sq./Ctn.
 14 Ctns./Crate | Ctn. Weight: 82.26 lbs.

Color Choices

02 White Birch	41 Soft Willow	47 Slate Blue	82 Meadow
11 Classic Sand	43 Pebble Clay	49 Graphite Grey	
17 Warm Sandalwood	44 Harbor Stone	52 Java	
22 Sunny Maize	46 Basket Beige	79 Seagrass	
26 Summer Wheat			



HOMEX® vinyl siding has the best easy-care convenience

around. Engineered with color fastness that eliminates any need for painting or staining.



.040"
THICKNESS

.040" Product Thickness provides durability and impact resistance.




Positive Locking System
Panels lock securely together for durability and ease of installation.



Reinforced Nail Hem
Creates secure attachments that can withstand gale-force winds.

PROFILE OPTIONS

- Profiles are available in Double 4, Dutchlap 4.5 and Dutchlap 5.



26 Summer Wheat



41 Soft Willow



43 Pebble Clay



52 Java



44 Harbor Stone



79 Seagrass



82 Meadow

Addison Heights®

VINYL SIDING

A Multitude of Beauty & Value for *The Good Life*

Affordable Beauty & Reliability

Addison Heights® vinyl siding offers exceptional value by combining high-quality materials, a durable .040" panel thickness, and construction features usually found only on more expensive lines.

Unlike comparable siding brands Addison Heights panels feature a full 9/16" profile height that creates distinctive shadow lines giving your home a dramatic presence.

Addison Heights features a brushed woodgrain finish and is available in a broad range of colors and three profile options allowing you to suit your individual tastes.



Go to www.vinylsiding.org for a current list of certified products and colors.



FEATURES

- This HOMEX® product is covered by a Limited Lifetime Warranty
- Attractive, brushed woodgrain embossed finish
- Deep, 9/16" profile height for distinctive shadow lines
- Durable panel construction



COLOR SELECTION

Actual product color may vary slightly from color representations shown.



02 White Birch



11 Classic Sand



17 Warm Sandalwood



22 Sunny Maize



46 Basket Beige



47 Slate Blue




49 Graphite Grey

Data Sheet

Universal Soffit

Value Performance





10" Vinyl Soffit Solid - Brushed Finish 32US10SD02

Length 12' - 0" | 20 Panels/Ctn. | 2 Sq./Ctn. | Ctn. Weight: 75.73 lbs.

10" Vinyl Soffit Vented - Brushed Finish 32US10VT02

Length 12' - 0" | 20 Panels/Ctn. | 2 Sq./Ctn. | Ctn. Weight: 75.57 lbs. Sq. In.
Vent Area Per L.F.: 3.8





12" Vinyl Soffit Solid - Brushed Finish 32US12SD02

Length 12' - 0" | 16 Panels/Ctn. - Solid | 192 Sq. Ft./Ctn. | Ctn. Weight: 71.92 lbs.

12" Vinyl Soffit Vented - Brushed Finish 32US12VT02

Length 12' - 0" | 16 Panels/Ctn. | 192 Sq. Ft./Ctn. | Ctn. Weight: 70.66 lbs. Sq. In.
Vent Area Per L.F.: 4.0



12" Vinyl Soffit Center Vented - Brushed Finish 32US12CV02

Length 12' - 0" | 16 Panels/Ctn. | 192 Sq. Ft./Ctn. | Ctn. Weight: 71.50 lbs. Sq. In.
Vent Area Per L.F.: 1.3

Note: All Universal Soffit is Available in 02 White Birch ONLY

Universal Vinyl Soffit

SCI Siding Vinyl Soffit meets or exceeds all industry standards per ASTM D3679.

Product Test Data

Soffit Thickness.....038" ± .001"
 Specific Gravity.....1.45
 Tensile Strength (PSI).....7,154
 Tensile Modulus (PSI).....416,900
 IZOD Impact Strength @ 32°F.....Passes per ASTM
 D3679 Heat Deflection Temp. @ 264 PSI.....169°F
 Coefficient of Linear Expansion.....3.30 x 10-5
 Warpage.....0.00"
 Heat Shrinkage.....0.3%

Impact Resistance.....Passes per ASTM D3679
 Surface Distortion @ 140°F.....0
 Fire Rating Class A
 Flame Spread Index.....10
 Smoke Developed.....395
 Fuel Contribution.....0
 Average Time Of Burning.....Self extinguished
 Average Extent Of Burning.....2.379 mm
 Weathering.....Passes per ASTM
 D3679