



WARRANTY & RATING



SPECIFICATIONS

- Wattage: 5W
- Voltage: AC/DC 12V - 24V
- Luminous Flux: 250lm
- Beam Angle: 120°
- Color Rendering Index (CRI): 90
- Lifespan: 30,000 hours
- Light Source: LED
- Color Temperature (CCT): 3000K Warm White
- Waterproof Rating: IP65
- Operating Temperature: -4°F-140°F
- Material: Aluminum

PRODUCT DESCRIPTION

LEONLITE's LED Fence Down Lights are perfect for fences and stair columns, offering a discreet 'Small Brim' design for downward, anti-dazzling light. Their low voltage compatibility makes them ideal for most landscape lighting systems, with a durable, waterproof build and dual port design for easy wiring.

FEATURES & BENEFITS

- Anti-glare 'Small Brim' design, neighbor-friendly lighting.
- Compatible with 12V systems, easy prosumer and contractor integration.
- Innovative double port design, concealed wiring for aesthetic appeal.
- CRI90 for true-to-life colors, ultra-bright 250LM for enhanced visibility.
- IP65 waterproof, durable oil-rubbed bronze finish, stainless steel mounting for extended outdoor use.

POWER AND ELECTRICAL FEATURES

- ETL certified for safety, this light operates on a low voltage AC/DC 12V-24V, ideal for pet and child safety and compatible with most 12V landscape systems.
- Comes with a UL-listed E215415 wire, type XTW, 20 gauge, rated for 105°C. The exposed wire length is approximately 3.94 feet (1.2 meters).

DESIGN AND STRUCTURE

- Features a 'Small Brim' anti-glare design with downward lighting to avoid disturbance to neighbors.
- Unique up & down double port design for hidden wiring, suitable for various installation locations like deck railings, porches, eaves, and trellises.



ADDITIONAL COMPONENTS

- Screws: 2 stainless steel screws for secure fitting.
- Drilling Template: 1 printed paper template for precise installati
- Mounting Bracket: 1 stainless steel bracket for robust support.
- Waterproof Connectors: 2 plastic S2 waterproof wire connectors for durable connections.
- Wall Plugs: 2 plastic wall plugs for stable anchoring.

LED AND OPTICAL PERFORMANCE


- 5W LED with a total luminous flux of 250 lumens for bright illumination.
- Features 18 SMD2835 LED beads, providing direct lighting with a warm 3000K color temperature and a high CRI of 90 for accurate color representation.

PRODUCT DIAGRAM



Size in mm
 1" = 25.4mm.

PHOTOMETRICS



Colorimetric parameters

Chromaticity coordinates: $x=0.4332$ $y=0.3995$ $u=0.2501$ $v=0.3460$ $duv=-0.0013$
 Correlated color temperature: 3027K Main wavelength : 583.2nm Color purity : 49.9%
 Luminous flux Color ratio: R=24.2%, G=74.1%, B=1.7% Peak wavelength: 626.7nm and a half Width :168.9nm

Color rendering index: Ra= 93.7

R1 =94	R2 =95	R3 =94	R4 =95	R5 =95	R6 =96	R7 =95	R8 =88
R9 =71	R10=87	R11=94	R12=80	R13=94	R14=96	R15=92	

Dual-Purpose Step and Deck Lights

Slim and safe, dual-purpose low-voltage lighting for steps and decks.




Tende Orizzontali Step & Deck Light



Retro Baffle Step & Deck Light

277V Compatible Commercial Step Lighting

Seamlessly integrates with commercial voltages.



ZincTech Commercial Upright Gradience Step & Deck Light




ZincTech Commercial Parallel Gradience Step & Deck Light



ZincTech Commercial Louvered Step & Deck Light

Classic Glow Series

Retro design meets modern lighting.



Semisfera Deck & Rail Light



Quadrifoglio Deck & Rail Light



Pro Parallel Retro Louvered Step & Deck Light

Modern Elegance Series

Blending utility with modern aesthetics.



Affusolato Deck & Rail Light



Nova Deck & Rail Light




Vertebre Deck & Rail Light

All Color Options

some models may have limited choices.



Satin Nickel



Matte Black



Oiled Rubbed Bronze

Compatible Accessories



Outdoor Transformer, AC to DC, 12V 60W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 100W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 120W, Timer & Photocell



Waterproof Wire Nuts - Large (For terminals/multiple connections, fits 12AWG - 22AWG, up to 8 wires of 16/2)



Waterproof Wire Nuts - Medium (Fits 14AWG - 22AWG, up to 3 wires of 16/2)



Low Voltage Landscape Lighting Cable, 16/2

Note: Also available in 10/2, 12/2, 14/2 sizes.



Landscape Light Wire Connector (14-16 AWG Compatible)



EasyConnect Wire Connector (14-16 AWG Compatible)