

WARRANTY & RATING



SPECIFICATIONS

- Wattage: 3 watts
- Voltage: 12V AC/DC
- Luminous Flux: 147 lumen
- Beam Angle: 65°
- Color Rendering Index (CRI): 90
- Lifespan: 40,000 hours
- Light Source: LED
- Color Temperature (CCT): 3000K
- Waterproof Rating: IP65
- Operating Temperature: -4°F to 104°F
- Material: Die-casted aluminum

PRODUCT DESCRIPTION

Discover the perfect blend of form and function with our LEONLITE LED Path Lights, featuring integrated LEDs for uniform lighting and a unique vintage design that adds a distinguished touch to your garden paths.

FEATURES & BENEFITS

- Retro flair, LED clarity.
- Natural glow, high CRI90; elevate your landscape's look.
- IP65, ETL-certified; robust for rain or shine.
- Easy install, safe design; child- and pet-friendly lighting.
- Long life, solid warranty; LEONLITE's promise for your peace of mind.

POWER AND ELECTRICAL FEATURES

- Operates on a safe 12V AC/DC power supply with a total wattage of 3W, reducing energy consumption compared to a 16W incandescent equivalent.
- Features UL-certified wiring and plug, ensuring top-tier electrical safety standards.
- The total cord length of 6.07 feet allows for flexible placement and easy power access.

DESIGN AND STRUCTURE

- Crafted from die-cast aluminum with a sleek black finish and golden/antique copper accents, this fixture adds a sophisticated touch to any outdoor setting.
- Its design supports a maximum number of connections based on the total load power, enabling expansive layout designs.



ADDITIONAL COMPONENTS

- Includes two waterproof cap connectors for secure and safe outdoor installation.


LED AND OPTICAL PERFORMANCE

- Boasts a high luminous efficacy of 100-110LM/W with a CRI of 90, casting a warm 3000K light that renders colors naturally.
- Equipped with six SMD 2835 LEDs, these lights use just 2.5W for efficient, bright, and consistent forward-facing illumination.

PRODUCT DIAGRAM



PHOTOMETRICS



Chroma Parameters

Chro.Coor.:x=0.4302 y=0.3983 u=0.2487 v=0.3454 duv=-0.0014
 CCT: 3069K Dominant Wave.:583.0nm Purity:48.7%
 Flux RGB Ratio:R=24.4%,G=73.5%,B=2.2% Peak Wave:618.3nm Half Width:161.1nm

Rendering Index:Ra= 93.7

R1 =96	R2 =99	R3 =96	R4 =95	R5 =97	R6 =95	R7 =90	R8 =82
R9 =64	R10=100	R11=98	R12=83	R13=98	R14=99	R15=91	

360° GentleGlow


Soft, all-around lighting for expansive landscape enhancement.



Piramide del Tempio LED Path Light



O-ring Unico/Colorato LED Path Light



Stella Bitta LED Path Light

EdgeGlow OneWay Light

Precise, one-sided illumination for clear path lighting without overspill.



Crescente LED Path Light



Escavatori LED Path Light



Petali Rovesciato LED Path Light

NatureDots FlexGarden Light

Brighten gardens and paths, ground or surface mount.




Emisferi Sky-up LED Path Light

Designer Crafted Landscape Lighting

Function meets art, illuminating spaces with stylish, decorative designs.



Fulmine Gold LED Path Light



Luce Fiamma LED Path Light




Quadra Rotondo LED Path Light

SmartLink


Wireless control for easy, smart outdoor lighting.



O-ring Colorato LED Path Light - Smart Control



XGEN™ Dual-spot LED Path Light




XGEN™ Smart LED Path Light

All Color Options

some models may have limited choices.



Brass Yellow



Ebony Black



oiled rubbed bronze

Compatible Accessories



Outdoor Transformer, AC to DC, 12V 60W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 100W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 120W, Timer & Photocell



LeonLite® Waterproof Wire Nuts - Large



LeonLite® Waterproof Wire Nuts - Medium



Low Voltage Landscape Lighting Cable, 100ft, 16/2



LeonLite® Landscape Light Wire Connector



LeonLite® EasyConnect Wire Connector