



## WARRANTY & RATING



## SPECIFICATIONS

- Wattage: 4W
- Voltage: AC/DC 12V
- Luminous Flux: 55lm
- Beam Angle: 360°
- Color Rendering Index (CRI): 90
- Lifespan: 40,000hrs
- Light Source: LED
- Color Temperature (CCT): 3000K warm white
- Waterproof Rating: IP65
- Operating Temperature: -4°F to 104°F
- Material: Die-casted aluminum

## PRODUCT DESCRIPTION

Set the stage in your landscape with LEONLITE's LED Pathway Lights; the integrated light source cuts maintenance, while the top ring accent light adds a subtle glow, perfect for safe evening strolls in your garden.

## FEATURES & BENEFITS

- Upper glow ring for safer, collision-free paths.
- Non-glare illumination enhances night-time visibility and ambiance.
- ETL listed, ensuring top product safety and performance standards.
- IP65 rated with a durable build for long-term outdoor use.
- 12V AC/DC for a safer garden, reducing risk around kids and pets.

## POWER AND ELECTRICAL FEATURES

- 4W power, efficiently replacing a 10W incandescent bulb, with safe 12V AC/DC operation.
- UL-listed purple copper wiring and ETL certification ensure reliable, safe installations.
- 6.07-foot (approximately 1850mm) power cord for flexible setup.

## DESIGN AND STRUCTURE

- Unique top ring design for safer, glare-free night illumination.
- Durable black aluminum and plastic build, designed for multiple connections based on transformer load.

## ADDITIONAL COMPONENTS



- Includes two waterproof cap connectors for secure and safe outdoor installation.

## LED AND OPTICAL PERFORMANCE


- Features eight SMD 2835 LEDs, High Color Rendering Index (CRI) of 90, ensuring vivid and natural light.
- Each LED has a rated power of 0.5W and operates at 220mA, combining for a total of 4W power usage.
- Exceptional luminous efficacy of 110 lumens per watt for bare LEDs, indicating high energy efficiency.

## PRODUCT DIAGRAM

Size in mm  
 1" = 25.4mm.



## PHOTOMETRICS



### Chroma Parameters

Chro.Coor.:  $x=0.4393$   $y=0.4022$   $u=0.2529$   $v=0.3473$   $duv=-0.0011$   
 CCT: 2945K Dominant Wave.: 583.4nm Purity: 52.6%  
 Flux RGB Ratio: R=24.9%, G=73.3%, B=1.8% Peak Wave: 618.1nm Half Width: 152.3nm

### Rendering Index: Ra= 93.7

R1 =95	R2 =98	R3 =98	R4 =94	R5 =95	R6 =97	R7 =91	R8 =81
R9 =59	R10=95	R11=96	R12=84	R13=96	R14=100	R15=90	

## 360° GentleGlow


Soft, all-around lighting for expansive landscape enhancement.



Piramide del Tempio LED Path Light



O-ring Unico/Colorato LED Path Light



Stella Bitta LED Path Light

## EdgeGlow OneWay Light

Precise, one-sided illumination for clear path lighting without overspill.



Crescente LED Path Light



Escavatori LED Path Light



Petali Rovesciato LED Path Light

## NatureDots FlexGarden Light

Brighten gardens and paths, ground or surface mount.




Emisferi Sky-up LED Path Light

## Designer Crafted Landscape Lighting

Function meets art, illuminating spaces with stylish, decorative designs.



Fulmine Gold LED Path Light



Luce Fiamma LED Path Light




Quadra Rotondo LED Path Light

## SmartLink

Wireless control for easy, smart outdoor lighting.



O-ring Colorato LED Path Light - Smart Control



XGEN™ Dual-spot LED Path Light




XGEN™ Smart LED Path Light

## All Color Options

some models may have limited choices.



Brass Yellow



Ebony Black



oiled rubbed bronze

## Compatible Accessories



Outdoor Transformer, AC to DC, 12V 60W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 100W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 120W, Timer & Photocell



LeonLite® Waterproof Wire Nuts - Large



LeonLite® Waterproof Wire Nuts - Medium



Low Voltage Landscape Lighting Cable, 100ft, 16/2



LeonLite® Landscape Light Wire Connector



LeonLite® EasyConnect Wire Connector