## **LeonLite**®

# LeonLite® Deck & Steps Lighting LeonLite® Tende Orizzontali Step & Deck Light

ST1SLLO-SDL3D30H-BRN-VT / ST1SLLO-SDL3D30H-SS-VT







#### **WARRANTY & RATING**





#### **SPECIFICATIONS**

· Wattage: 3W

Voltage: AC/DC 10V-16V

• Luminous Flux: 150lm

• Beam Angle: 30°

• Color Rendering Index (CRI): 90

· Lifespan: 30,000 hours

• Light Source: LED

• Color Temperature (CCT): 3000K warm white

Waterproof Rating: IP65

• Operating Temperature: -4°F to 104°F

Material: 304 stainless steel cover / Aluminum cover

#### PRODUCT DESCRIPTION

LEONLITE's Dual-Purpose Step and Deck Lights feature an ultra-slim, surface mount design, ideal for stair and railing installations. These low-voltage, 3W LED lights are safe for high-contact areas, providing consistent illumination with an integrated louver baffle to prevent glare and a frosted lens for a soft glow.

#### **FEATURES & BENEFITS**

- Ultra-Slim & Safe: Slim design with hidden blades prevents scratches, enhancing user safety.
- Glare-Free Lighting: Louvered baffle and frosted lens for a soft, even glow without harsh glare.
- Flexible Placement: Suitable for steps, railings, and stair posts due to low-voltage operation and sleek design.
- Surface Mounting: Drill-only installation, no surface cutting needed.
- Durable & Weatherproof: IP65 rated with corrosion-resistant cover, perfect for outdoor environments.

# LeonLite® Deck & Steps Lighting LeonLite® Tende Orizzontali Step & Deck Light

ST1SLLO-SDL3D30H-BRN-VT / ST1SLLO-SDL3D30H-SS-VT

#### **POWER AND ELECTRICAL FEATURES**

- ETL Certified: Ensures safety and reliability, operating at a voltage range of DC/AC 10-16V and a current of 0.0187A.
- UL Listed Wiring: Features tinned copper wires and waterproof cap connectors, with a gauge of 18AWG for secure and durable electrical connections.

#### **DESIGN AND STRUCTURE**

- Offers two models with either an oil-rubbed bronze powder-coated aluminum cover or a 304 stainless steel cover.
- Dual-Purpose Design: The ultra-slim lamp body with a hidden blade design ensures safety and versatility, suitable for mounting on steps, railings, and posts in American courtyard decks without the risk of scratches.
- Glare-Free Illumination: The louver baffle design coupled with a frosted glass lens offers a uniform glow, expanding the lighting range and reducing glare for an improved lighting experience.


#### **ADDITIONAL COMPONENTS**


- · Screws: 2 stainless steel screws.
- Wire Caps: 2 caps included.
- Expansion Screws: 2 provided for secure mounting.
- Plastic Hole Plugs: 2 plugs for installation ease.

#### LED AND OPTICAL PERFORMANCE

- Efficient Lighting: Operates at 3W power and a current of 0.0187A, producing 150 lumens.
- Quality LED Technology: Equipped with 24 SMD2835 LEDs, delivering a high color rendering index (CRI) of ≥90, ensuring vibrant and true-tolife colors.

#### PRODUCT DIAGRAM






Size in mm 1" = 25.4mm.

## LeonLite® Deck & Steps Lighting LeonLite® Tende Orizzontali Step & Deck Light

R15=94

ST1SLLO-SDL3D30H-BRN-VT / ST1SLLO-SDL3D30H-SS-VT

#### **PHOTOMETRICS**



#### Color Parameters:

Chromaticity Coordinate:x=0.4284 y=0.3982/u'=0.2476 v'=0.5178

CCT=3101K(Duv=-0.0011) Dominant WL:Ld =582.8nm Purity=48.1%

Ratio:R=24.1% G=73.1% B=2.8% Peak WL:Lp=626.9nm FWHM=171.5nm

Render Index:Ra=94.8 CRI=92.4 AvgR=92.5

R1 =96 R2 =96 R3 =94 R4 =96 R5 =96 R6 =95 R7 =95

R8 =90 R9 =76 R10=90 R11=96 R12=81 R13=96 R14=96

#### Photo Parameters:

Flux = 167.0 lm Eff. : 59.14 lm/W Fe = 596.9 mW

#### Electrical parameters:

V = 12.008 V I = 0.2351 A P = 2.823 W PF = 1.000

Status: Integral T = 124 ms Ip = 42561 (65%)

## **LeonLite**®

## **LeonLite® Deck & Steps Lighting**

\*Current offerings as of January 2024; visit leonlite.com for additional choices

#### **Dual-Purpose Step and Deck Lights**

Slim and safe, dual-purpose low-voltage lighting for steps and decks.



Tende Orizzontali Step & Deck Light



Retro Baffle Step & Deck Light

**All Color Options** 

some models may have limited choices.

Satin Nickel



Matte Black



Oiled Rubbed Bronze

### **277V Compatible Commercial Step Lighting**

Seamlessly integrates with commercial voltages.



ZincTech Commercial Upright Gradience Step & Deck Light



ZincTech Commercial Parallel Gradience Step & Deck Light



ZincTech Commercial Louvered Step & Deck Light

### **Compatible Accessories**



Outdoor Transformer, AC to DC, 12V 60W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 100W, Timer & Photocell



Outdoor Transformer, AC to DC, 12V 120W, Timer & Photocell

#### **Classic Glow Series**

Retro design meets modern lighting.



Semisfera Deck & Rail Light



Quadrifoglio Deck & Rail Light



Pro Parallel Retro Louvered Step & Deck Light

Waterproof Wire Nuts -Large(For terminals/ multiple connections, fits 12AWG - 22AWG, up to 8 wires of 16/2)



Waterproof Wire Nuts -Medium(Fits 14AWG -22AWG, up to 3 wires of 16/2)

### **Modern Elegance Series**

Blending utility with modern aesthetics.



Affusolato Deck & Rail Light



Nova Deck & Rail Light



Vertebre Deck & Rail Light



Low Voltage Landscape Lighting Cable, 16/2

Note: Also available in 10/2, 12/2, 14/2 sizes.



Landscape Light Wire Connector(14-16 AWG Compatible)



EasyConnect Wire Connector(14-16 AWG Compatible)