

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE® STANDARD ULTRA RESIN

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Epoxy constituents

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40
E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Skin irritation, Category 2 H315: Causes skin irritation.
Eye irritation, Category 2 H319: Causes serious eye irritation.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing mist or vapours.
P264 Wash skin thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P391 Collect spillage.

Hazardous components which must be listed on the label:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

Bisphenol A - epoxy resins, number average MW >700 - <1100

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No.	Classification	Concent
---------------	---------	----------------	---------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

	EC-No. Index-No. Registration number		ration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3 216-823-5 603-073-00-2 01-2119456619-26	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 2; H411 specific concentration limit Skin Irrit. 2; H315 >= 5 % Eye Irrit. 2; H319 >= 5 %	>= 70 - < 90
Reaction mass of 2,2'-[methylenebis(2, ,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4, ,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2,ylmethoxy)benzyl]phenoxy}methyl)oxirane,	- - 01-2119454392-40	Skin Irrit. 2; H315 Skin Sens. 1; H317 Aquatic Chronic 2; H411	>= 2.5 - < 10
Bisphenol A - epoxy resins, number average MW >700 - <1100	25068-38-6 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317	>= 1 - < 10

For explanation of abbreviations see section 16.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of bisphenol A and epichlorohydrin

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	25.01.2021	400001021217	17.07.2019
			Date of first issue: 20.07.2018

Print Date 17.06.2022

Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide

Carbon oxides
Halogenated compounds

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For
personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.
Dispose of rinse water in accordance with local and national
regulations.
Persons susceptible to skin sensitisation problems or asthma,
allergies, chronic or recurrent respiratory disease should not
be employed in any process in which this mixture is being
used.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated
place. Containers which are opened must be carefully
resealed and kept upright to prevent leakage. Keep in properly
labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this
SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Silica, amorphous, fumed, cryst.-free	112945-52-5	TWA (inhalable dust)	6 mg/m ³ (Silica)	GB EH40
		TWA (Respirable dust)	2.4 mg/m ³ (Silica)	GB EH40

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Workers	Inhalation	Long-term systemic effects	4.93 mg/m ³
	Workers	Dermal	Long-term systemic effects	0.75 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0.87 mg/m ³
	Consumers	Dermal	Long-term systemic effects	0.0893 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0.5 mg/kg bw/day
Bis(2-ethylhexyl) adipate	Workers	Inhalation	Long-term systemic effects	17.8 mg/m ³
	Workers	Dermal	Long-term systemic effects	25.5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	4.4 mg/m ³
	Consumers	Dermal	Long-term systemic effects	13 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	1.7 mg/kg bw/day
Silica, amorphous, fumed, cryst.-free	Workers	Inhalation	Long-term systemic effects	4 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	Fresh water	0.006 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

ne		
Remarks:	Assessment Factors	
	Marine water	0.001 mg/l
	Assessment Factors	
	Fresh water sediment	0.341 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0.034 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	0.065 mg/kg dry weight (d.w.)
	Equilibrium method	
	Sewage treatment plant	10 mg/l
	Assessment Factors	
	Secondary Poisoning	11 mg/kg
Bis(2-ethylhexyl) adipate	Soil	0.865 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Neoprene gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue:
1.2	25.01.2021	400001021217	17.07.2019
			Date of first issue: 20.07.2018

Print Date 17.06.2022

that exposures are within recommended exposure guidelines.

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	: liquid
Colour	: light cream
Odour	: slight
Odour Threshold	: No data is available on the product itself.
pH	: 6 Concentration: 500 g/l
Melting point/freezing point	: No data is available on the product itself.
Boiling point	: No data is available on the product itself.
Flash point	: 210 °C Method: Pensky-Martens closed cup
Evaporation rate	: No data is available on the product itself.
Flammability (solid, gas)	: No data is available on the product itself.
Burning rate	: No data is available on the product itself.
Upper explosion limit / Upper flammability limit	: No data is available on the product itself.
Lower explosion limit / Lower flammability limit	: No data is available on the product itself.
Vapour pressure	: 0.0001 kPa
Relative vapour density	: No data is available on the product itself.
Relative density	: No data is available on the product itself.
Density	: 1.15 g/cm ³ (25 °C)
Solubility(ies)	
Water solubility	: No data is available on the product itself.
Solubility in other solvents	: No data is available on the product itself.
Partition coefficient: n-octanol/water	: No data is available on the product itself.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Viscosity : No data is available on the product itself.

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Remarks: No mortality observed at this dose.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:
Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:
Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit
Exposure time: 4 h
Assessment: Irritating to skin.
Method: OECD Test Guideline 404

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Result: Irritating to skin.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Method: OECD Test Guideline 404

Result: Skin irritation

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rabbit

Assessment: Irritating to eyes.

Method: OECD Test Guideline 405

Result: Irritating to eyes.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Species: Rabbit

Method: OECD Test Guideline 405

Result: No eye irritation

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Eye irritation

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: The product is a skin sensitiser, sub-category 1B.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

:

Exposure routes: Skin

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Exposure routes: Skin

Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: mouse lymphoma cells

Metabolic activation: without metabolic activation

Result: positive

: Test Type: reverse mutation assay

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: Mutagenicity (Salmonella typhimurium - reverse mutation assay)

Result: negative

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: positive

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: Positive results were obtained in some in vitro tests.

: Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Genotoxicity in vivo : Test Type: in vivo assay
Test species: Mouse (male)
Cell type: Germ
Application Route: Oral
Dose: 3333, 10000 mg/kg
Result: negative

Test Type: gene mutation test
Test species: Rat (male)
Cell type: Somatic
Application Route: Oral
Dose: 50,250,500,1000 mg/kg bw/day
Method: OECD Test Guideline 488
Result: negative

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl}oxirane

:
Genotoxicity in vivo : Cell type: Somatic
Application Route: Oral
Exposure time: 48 h
Dose: 2000 mg/kg
Method: OECD Test Guideline 474
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 2000 mg/kg
Method: OECD Test Guideline 486
Result: negative

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

Germ cell mutagenicity- Assessment : No data available

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No observed adverse effect level: 15 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Mouse, male

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0, 0.1, 10, 100 mg/kg bw/day

Frequency of Treatment: 3 days/week

No-observed-effect level: 0.1 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, female

Application Route: Dermal

Exposure time: 24 month(s)

Dose: 0.1, 100, 1000 mg/kg bw/day

Frequency of Treatment: 5 days/week

No-observed-effect level: 100 mg/kg body weight

Method: OECD Test Guideline 453

Result: negative

Species: Rat, female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No observed adverse effect level: 100 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

Species: Rat, females

Application Route: Oral

Exposure time: 24 month(s)

Dose: 0, 2, 15, or 100 mg/kg bw/day

Frequency of Treatment: 7 days/week

No-observed-effect level: 2 mg/kg bw/day

Method: OECD Test Guideline 453

Result: negative

Target Organs: Digestive organs

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

Application Route: Oral

Exposure time: 24 month(s)

Dose: 15 mg/kg

Frequency of Treatment: 7 daily

Method: OECD Test Guideline 453

Result: negative

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility

: Test Type: Two-generation study

Species: Rat, male and female

Application Route: Oral

Dose: 0, 50, 180, 540 or 750 milligram per kilogram

Duration of Single Treatment: 238 d

Frequency of Treatment: 1 daily

General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight

General Toxicity F1: No-observed-effect level: 750 mg/kg body weight

Symptoms: No adverse effects

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female

Application Route: Oral

General Toxicity - Parent: No-observed-effect level: 750 mg/kg body weight

General Toxicity F1: No-observed-effect level: 750 mg/kg body weight

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic development were detected.

Components:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
Dose: 0, 30, 100 or 300 milligram per kilogram
Duration of Single Treatment: 28 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
30 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
300 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit, female
Application Route: Oral
Dose: 0, 20, 60 or 180 milligram per kilogram
Duration of Single Treatment: 13 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Developmental Toxicity: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 0, 60, 180 and 540 milligram per kilogram
Duration of Single Treatment: 10 d
Frequency of Treatment: 1 daily
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: >
540 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:

Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level:
30 mg/kg body weight
Result: No teratogenic effects

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level:
30 mg/kg body weight
Method: Other guidelines

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: oral (gavage)

Exposure time: 14 Weeks Number of exposures: 7 d

Dose: 0, 50, 250, 1000 mg/kg/day

Method: OECD Test Guideline 408

Species: Rat, male and female

NOAEL: >= 10 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 5 d

Dose: 0, 10, 100, 1000 mg/kg/day

Method: OECD Test Guideline 411

Species: Mouse, male

NOAEL: 100 mg/kg

Application Route: Skin contact

Exposure time: 13 Weeks Number of exposures: 3 d

Dose: 0, 1, 10, 100 mg/kg/day

Method: OECD Test Guideline 411

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-({2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy}methyl)oxirane

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

:
Species: Rat, male and female
NOAEL: 250 mg/kg
Application Route: Ingestion
Exposure time: 13 Weeks Number of exposures: 7 d
Method: Subchronic toxicity

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Species: Rat, male and female
NOAEL: 50 mg/kg
Application Route: Ingestion
Exposure time: 14 Weeks Number of exposures: 7 d
Method: Subchronic toxicity

Species: Rat, male and female
NOEL: 10 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks Number of exposures: 5 d
Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 : 11 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

NOEC : 4.2 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:

- Toxicity to fish : LC50 (Fish): 2.54 mg/l
Exposure time: 96 h
Method: Calculation method
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.55 mg/l
Exposure time: 48 h
Method: Calculation method
- Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 1.8 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201
- Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0.3 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211
Remarks: Information given is based on data obtained from similar substances.
- Bisphenol A - epoxy resins, number average MW >700 - <1100:
- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202
- Toxicity to algae/aquatic plants : EgC50 (Selenastrum capricornutum (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

12.2 Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge, non-adapted
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)
pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-((2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:
Biodegradability : Inoculum: activated sludge
Concentration: 3 mg/l
Result: Not biodegradable
Biodegradation: ca. 0 %
Exposure time: 28 d
Method: Directive 67/548/EEC Annex V, C.4.E.

Bisphenol A - epoxy resins, number average MW >700 - <1100:

Biodegradability : Test Type: aerobic
Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not biodegradable
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Stability in water : Degradation half life (DT50): 4.83 d (25 °C)
pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life (DT50): 7.1 d (25 °C)
pH: 9
Method: OECD Test Guideline 111

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

Remarks: Fresh water

Degradation half life (DT50): 3.58 d (25 °C)

pH: 7

Method: OECD Test Guideline 111

Remarks: Fresh water

12.3 Bioaccumulative potential

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3.242 (25 °C)
pH: 7.1
Method: OECD Test Guideline 117

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:
Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 150
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 2.7 - 3.6
Method: OECD Test Guideline 117

Bisphenol A - epoxy resins, number average MW >700 - <1100:
Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

12.4 Mobility in soil

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

Reaction mass of 2,2'-[methylenebis(2,1-phenyleneoxymethylene)]bis(oxirane) and 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]bis(oxirane) and 2-(2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy)methyl)oxirane

:
Distribution among environmental compartments : Koc: 4460
Method: OECD Test Guideline 121

Bisphenol A - epoxy resins, number average MW >700 - <1100:
Distribution among environmental compartments : Koc: 445

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

IATA

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : Miscellaneous

Packing instruction (cargo) : 964

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

aircraft)
Packing instruction : 964
(passenger aircraft)

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

IMDG

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

EmS Code : F-A, S-F

14.5 Environmental hazards

Marine pollutant : yes

ADR

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

14.5 Environmental hazards

Environmentally hazardous : yes

RID

14.1 UN number or ID number : UN 3082

14.2 UN proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (BISPHENOL A EPOXY RESIN, BISPHENOL F EPOXY RESIN)

14.3 Transport hazard class(es) : 9

14.4 Packing group : III

Labels : 9

14.5 Environmental hazards

Environmentally hazardous : yes

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version 1.2 Revision Date: 25.01.2021 SDS Number: 400001021217 Date of last issue: 17.07.2019
Date of first issue: 20.07.2018

Print Date 17.06.2022

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

Inventories

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

AICS (Australia), AIIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
GB EH40	: UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	: Long-term exposure limit (8-hour TWA reference period)

Further information

Classification of the mixture:

Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

HUNTSMAN

Enriching lives through innovation

ARALDITE® STANDARD ULTRA RESIN

Version	Revision Date:	SDS Number:	Date of last issue: 17.07.2019
1.2	25.01.2021	400001021217	Date of first issue: 20.07.2018

Print Date 17.06.2022

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version 2.3 Revision Date: 10.09.2021 SDS Number: 400001021218 Date of last issue: 25.01.2021
Date of first issue: 20.07.2018

Print Date 20.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : ARALDITE STANDARD ULTRA HARDENER

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hardener

1.3 Details of the supplier of the safety data sheet

Company : Huntsman Advanced Materials (Europe)BVBA
Address : Everslaan 45
3078 Everberg
Belgium
Telephone : +41 61 299 20 41
Telefax : +41 61 299 20 40
E-mail address of person responsible for the SDS : Global_Product_EHS_AdMat@huntsman.com

1.4 Emergency telephone number

Emergency telephone number : EUROPE: +32 35 75 1234
France ORFILA: +33(0)145425959
ASIA: +65 6336-6011
China: +86 20 39377888
+86 532 83889090
India: + 91 22 42 87 5333
Australia: 1800 786 152
New Zealand: 0800 767 437
USA: +1/800/424.9300

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Serious eye damage, Category 1 H318: Causes serious eye damage.
Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.
Long-term (chronic) aquatic hazard, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758


HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version 2.3 Revision Date: 10.09.2021 SDS Number: 400001021218 Date of last issue: 25.01.2021
Date of first issue: 20.07.2018

Print Date 20.10.2021

Hazard pictograms	:	
Signal word	:	Danger
Hazard statements	:	H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	:	Prevention: P261 Avoid breathing mist or vapours. P273 Avoid release to the environment. P280 Wear protective gloves/ eye protection/ face protection. Response: P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P391 Collect spillage.

Hazardous components which must be listed on the label:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine

Amines, polyethylenepoly-, tetraethylenepentamine fraction

Amines, polyethylenepoly-, triethylenetetramine fraction

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version 2.3 Revision Date: 10.09.2021 SDS Number: 400001021218 Date of last issue: 25.01.2021
Date of first issue: 20.07.2018

Print Date 20.10.2021

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Reaction products of fatty acid dimers and trimers, C18 (unsaturated), alkyl and fatty acids, C18 (unsaturated) alkyl with amines,, polyethylenepoly-, triethylenetetramine fraction,	Not Assigned -	Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Chronic 2; H411	>= 50 - < 70
Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine	68154-62-1 Polymer	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 30 - < 50
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7 292-587-7	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 2; H411 Acute toxicity estimate Acute oral toxicity: 1,716.2 mg/kg Acute dermal toxicity: 1,260 mg/kg	>= 5 - < 10
Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8 292-588-2	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Chronic 3; H412 EUH071	>= 0.25 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Avoid inhalation, ingestion and contact with skin and eyes.
No action shall be taken involving any personal risk or without suitable training.
It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : Exercise caution when using a high volume water jet as it may scatter and spread fire

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting	:	Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	:	Ammonia Carbon oxides Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.
Specific extinguishing methods	:	No data is available on the product itself.
Further information	:	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	:	Use personal protective equipment. Refer to protective measures listed in sections 7 and 8.
----------------------	---	------------------------------------------------------------------------------------------------

6.2 Environmental precautions

Environmental precautions	:	Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
---------------------------	---	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
-------------------------	---	-------------------------------------------------------------------------------------------------------------------------------------------------------------

6.4 Reference to other sections

For disposal considerations see section 13., See Section 1 for emergency contact information., For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this
-------------------------	---	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version 2.3 Revision Date: 10.09.2021 SDS Number: 400001021218 Date of last issue: 25.01.2021
Date of first issue: 20.07.2018

Print Date 20.10.2021

product.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in properly labelled containers.

Advice on common storage : For incompatible materials please refer to Section 10 of this SDS.

Recommended storage temperature : 2 - 40 °C

Further information on storage stability : Stable under normal conditions.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Amines, polyethylenepoly-, tetraethylenepentamine fraction	Workers	Inhalation	Long-term systemic effects	0.82 mg/m3
	Workers	Dermal	Long-term local effects	0.25 mg/cm2

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version 2.3 Revision Date: 10.09.2021 SDS Number: 400001021218 Date of last issue: 25.01.2021
Date of first issue: 20.07.2018

Print Date 20.10.2021

	Consumers	Inhalation	Long-term systemic effects	0.14 mg/m3
	Consumers	Dermal	Long-term local effects	0.021 mg/cm2
	Consumers	Oral	Long-term systemic effects	0.21 mg/kg bw/day
Amines, polyethylenepoly-, triethylenetetramine fraction	Workers	Inhalation	Long-term systemic effects	0.54 mg/m3
	Consumers	Inhalation	Long-term systemic effects	0.096 mg/m3
	Consumers	Oral	Long-term systemic effects	14 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Amines, polyethylenepoly-, tetraethylenepentamine fraction	Fresh water	0.01 mg/l
Remarks:	Assessment Factors	
	Marine water	0.001 mg/l
	Assessment Factors	
	Freshwater - intermittent	0.068 mg/l
	Assessment Factors	
	Sewage treatment plant	4.6 mg/l
	Assessment Factors	
	Fresh water sediment	3.198 mg/kg dry weight (d.w.)
	Equilibrium method	
	Marine sediment	0.32 mg/kg dry weight (d.w.)
	Equilibrium method	
	Soil	2.5 mg/kg dry weight (d.w.)
	Assessment Factors	
Amines, polyethylenepoly-, triethylenetetramine fraction	Fresh water	0.027 mg/l
	Marine water	0.003 mg/l
	Sewage treatment plant	0.13 mg/l
	Fresh water sediment	8.572 mg/kg dry weight (d.w.)
	Marine sediment	0.857 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version 2.3 Revision Date: 10.09.2021 SDS Number: 400001021218 Date of last issue: 25.01.2021
Date of first issue: 20.07.2018

Print Date 20.10.2021

	Soil	1.25 mg/kg dry weight (d.w.)
--	------	------------------------------

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Hand protection
Material : butyl-rubber
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Remarks : The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Recommended Filter type:
Combined particulates and organic vapour type

Filter type : Filter type A-P

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : yellow

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version 2.3 Revision Date: 10.09.2021 SDS Number: 400001021218 Date of last issue: 25.01.2021
Date of first issue: 20.07.2018

Print Date 20.10.2021

Odour : No data is available on the product itself.

Odour Threshold : No data is available on the product itself.

pH : 11
Concentration: 500 g/l

Melting point/freezing point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : > 150 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Burning rate : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : No data is available on the product itself.

Solubility(ies)
Water solubility : insoluble (20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Decomposition temperature : No data is available on the product itself.

Viscosity
Viscosity, dynamic : 25,000 - 30,000 mPa.s (25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : None known.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products : ammonia, anhydrous
Aldehydes
Nitrogen oxides (NO_x)
carbon monoxide
carbon dioxide
Ketones

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Acute oral toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg
Method: Calculation method

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

Acute inhalation toxicity : (Rat, male and female): Exposure time: 8 h
Test atmosphere: vapour
Method: OECD Test Guideline 403

Acute dermal toxicity - Product : Acute toxicity estimate : > 2,000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Product:

Species: Rabbit
Method: OECD Test Guideline 404
Result: Mild skin irritation
GLP: yes

Serious eye damage/eye irritation

Product:

Species: Rabbit
Assessment: Corrosive
Method: OECD Test Guideline 405
Result: Irreversible effects on the eye
GLP: yes

Remarks: May cause irreversible eye damage.

Respiratory or skin sensitisation

Product:

Assessment: No data available

Germ cell mutagenicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction

:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

: Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 487
Result: negative

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Genotoxicity in vitro : Test Type: reverse mutation assay
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Result: positive

: Test Type: sister chromatid exchange assay
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 479
Result: positive

: Test Type: gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Test species: Mouse (male and female)
Cell type: Bone marrow
Application Route: Intraperitoneal injection
Dose: 185/370/600 mg/kg
Method: OECD Test Guideline 474
Result: negative
Remarks: Information given is based on data obtained from similar substances.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Genotoxicity in vivo : Test Type: In vivo micronucleus test
Test species: Mouse (male and female)
Cell type: Bone marrow
Application Route: Intraperitoneal injection
Dose: 0 - 600 mg/kg
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity-Assessment : No data available

Carcinogenicity

Components:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species: Mouse, male

Dose: 42 mg/kg

Frequency of Treatment: 3 daily

No observed adverse effect level: \geq 50 mg/kg bw/day

Method: OECD Test Guideline 451

Result: negative

Species: Mouse, male

Application Route: Dermal

Exposure time: 104 weeks

Dose: 16.8 mg/kg

Frequency of Treatment: 3 daily

No observed adverse effect level: \geq 20 mg/kg bw/day

Method: OECD Test Guideline 451

Carcinogenicity - Assessment : No data available

Reproductive toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction

:

Effects on fertility : Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 422
Result: Animal testing did not show any effects on fertility.

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Effects on foetal development : Test Type: Pre-natal
Species: Rabbit, female
Application Route: Dermal
Dose: 5/50/125 mg/kg bw/d
Duration of Single Treatment: 13 d
General Toxicity Maternal: No-observed-effect level: 50 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: \geq 125 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 75/325/750 mg/kg bw/d
Duration of Single Treatment: 10 d
General Toxicity Maternal: No observed adverse effect level: \geq 750 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: \geq

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

750 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

Test Type: Pre-natal
Species: Rat, female
Application Route: Oral
Dose: 200/400/800 mg/kg bw(d)
Duration of Single Treatment: 14 d
General Toxicity Maternal: No-observed-effect level: 200 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: >= 400 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects
Remarks: Information given is based on data obtained from similar substances.

Amines, polyethylenepoly-, triethylenetetramine fraction:

Test Type: Pre-natal
Species: Rat
Application Route: Oral
Dose: 75/325/750 mg/kg bw/day
Duration of Single Treatment: 10 d
General Toxicity Maternal: No observed adverse effect level: >= 750 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: >= 750 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Test Type: Pre-natal
Species: Rabbit
Application Route: Dermal
Dose: 5/50/125 mg/kg bw/day
Duration of Single Treatment: 13 d
General Toxicity Maternal: No observed adverse effect level: 50 mg/kg body weight
Developmental Toxicity: No observed adverse effect level: >= 125 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Components:

Amines, polyethylenepoly-, triethylenetetramine fraction:

Reproductive toxicity - Assessment : The reprotoxic effects of Triethylenetetramine (TETA) are under further evaluation as part of the EU REACH program due in part to the aminoethyl ethanolamine (AEEA) content.

STOT - single exposure

No data available

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction

:

Species: Rat, male and female

NOAEL: 1000 mg/kg

Application Route: Ingestion

Exposure time: 6 Weeks Number of exposures: 7 d

Method: Subacute toxicity

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Species: Rat, male and female

NOAEL: 350 mg/kg

Application Route: Oral

Target Organs: Lungs

Remarks: Information given is based on data obtained from similar substances.

Species: Dog, male and female

NOAEL: 125 mg/kg

Application Route: Oral

Target Organs: Lungs

Remarks: Information given is based on data obtained from similar substances.

Species: Rat, male and female

NOAEL: 350 mg/kg

Application Route: Oral

Exposure time: 4 weeks Number of exposures: daily

Dose: 100/350/1200 mg/kg bw/d

Method: OECD Test Guideline 408

Remarks: Information given is based on data obtained from similar substances.

Species: Rat, male and female

NOAEL: 600

Application Route: oral (drinking water)

Exposure time: 92 days Dose: 120/600/3000 ppm

Method: OECD Test Guideline 408

Remarks: Information given is based on data obtained from similar substances.

Species: Mouse, male and female

NOAEL: 600

Application Route: oral (drinking water)

Exposure time: 92 days Dose: 120/600/3000 ppm

Method: OECD Test Guideline 408

Remarks: Information given is based on data obtained from similar substances.

Species: Rabbit, male and female

NOEL: >= 200 mg/kg

Application Route: Dermal

Exposure time: 20 days 6 h Number of exposures: 5 days/week

Dose: 50/100/200 mg/kg bw/day

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Method: OECD Test Guideline 410

Amines, polyethylenepoly-, triethylenetetramine fraction:

Species: Rat, male and female

NOAEL: 350 mg/kg

Application Route: Oral

Exposure time: 28 d Number of exposures: 7 d

Dose: 100/350/1000 mg/kg bw/day

Method: OECD Test Guideline 407

Target Organs: Lungs

Remarks: Information given is based on data obtained from similar substances.

Species: Dog, male and female

NOAEL: 125 mg/kg

Application Route: Oral

Remarks: Information given is based on data obtained from similar substances.

Species: Dog, male and female

NOAEL: 50 mg/kg

Application Route: Oral

Method: Subchronic toxicity

Remarks: Information given is based on data obtained from similar substances.

Species: Rat, male and female

NOAEL: 50 mg/kg

Application Route: Oral

Exposure time: 26 weeks Dose: 50/175/600 mg/kg bw/day

Method: OECD Test Guideline 408

Target Organs: Lungs

Remarks: Information given is based on data obtained from similar substances.

Species: Mouse, male and female

NOAEL: 92 mg/kg, 600 ppm

Application Route: Oral

Exposure time: 120/600/3000 ppm Method: OECD Test Guideline 408

Remarks: Information given is based on data obtained from similar substances.

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Reaction products of fatty acid dimers and trimers, C18 (unsaturated) alkyl and fatty acids, C18 (unsaturated) alkyl with amines, polyethylenepoly-, triethylenetetramine fraction

:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): 7.07 mg/l
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 5.18 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 2.43 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): 421 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

Fatty acids, C18-unsatd., dimers, polymers with oleic acid and triethylenetetramine:
Ecotoxicology Assessment
Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): 420 mg/l
End point: mortality
Exposure time: 96 h
Test Type: semi-static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 24.1 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: Tested according to Annex V of Directive 67/548/EEC.

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 6.8 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 : 97.3 mg/l
Exposure time: 2 h
Test Type: static test
Test substance: Fresh water

NOEC : 500 mg/l
Exposure time: 28 d
Method: OECD Test Guideline 216

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 1.9 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test substance: Fresh water
Method: OECD Test Guideline 202
Remarks: Information given is based on data obtained from similar substances.

Toxicity to soil dwelling organisms : NOEC: 125 mg/kg
Exposure time: 55 d

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 222

Amines, polyethylenepoly-, triethylenetetramine fraction:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 330 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: EPA OTS 797.1400

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 31.1 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water
Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae/aquatic plants : ErC50 (Selenastrum capricornutum (green algae)): 20 mg/l
Exposure time: 72 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 201

EC10 (Selenastrum capricornutum (green algae)): 1.34 mg/l
Exposure time: 72 h
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Bacteria): \geq 100 mg/l
Exposure time: 28 d
Method: OECD Test Guideline 216

EC50 (Bacteria): $>$ 100 mg/l
Exposure time: 28 h
Method: OECD Test Guideline 216

EC50 (Bacteria): 15.7 mg/l
Exposure time: 2 h
Test Type: static test
Test substance: Fresh water

NOEC (Bacteria): 1.3 mg/l
Exposure time: 2 h
Test Type: static test
Test substance: Fresh water

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC10: 1.9 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 202

Toxicity to soil dwelling organisms : NOEC: ca. 1,000 mg/kg
Exposure time: 56 d

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 222

EC50: > 1,000 mg/kg
Exposure time: 56 d
Species: Eisenia fetida (earthworms)
Method: OECD Test Guideline 222

Ecotoxicology Assessment
Acute aquatic toxicity : This product has no known ecotoxicological effects.
Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Biodegradability : Inoculum: activated sludge
Result: Not inherently biodegradable.
Biodegradation: 17 %
Exposure time: 84 d
Method: OECD Test Guideline 302 A

Test Type: aerobic
Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 162 d
Method: OECD Test Guideline 301D

Amines, polyethylenepoly-, triethylenetetramine fraction:

Biodegradability : Inoculum: activated sludge
Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 162 d
Method: OECD Test Guideline 301D

Test Type: aerobic
Inoculum: activated sludge
Result: Not inherently biodegradable.
Biodegradation: 20 %
Related to: Dissolved organic carbon (DOC)
Exposure time: 84 d
Method: OECD Test Guideline 302A

Chemical Oxygen Demand (COD) : 1,940 mg/g

12.3 Bioaccumulative potential

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:

Partition coefficient: n-octanol/water : log Pow: -2.6 (20 °C)

Amines, polyethylenepoly-, triethylenetetramine fraction:

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Partition coefficient: n-octanol/water : log Pow: -2.08 - 2.90 (20 °C)
Method: QSAR

12.4 Mobility in soil

Components:

Amines, polyethylenepoly-, tetraethylenepentamine fraction:
Distribution among environmental compartments : Koc: 3.2 - 3.7
Method: OECD Test Guideline 106

Amines, polyethylenepoly-, triethylenetetramine fraction:
Distribution among environmental compartments : Koc: 1584.9 - 5012
Method: OECD Test Guideline 106

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.

Contaminated packaging : Empty remaining contents.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number or ID number

ADR	:	UN 3082
RID	:	UN 3082
IMDG	:	UN 3082
IATA	:	UN 3082

14.2 UN proper shipping name

ADR	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYAMIDE RESIN)
RID	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYAMIDE RESIN)
IMDG	:	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (POLYAMIDE RESIN)
IATA	:	Environmentally hazardous substance, liquid, n.o.s. (POLYAMIDE RESIN)

14.3 Transport hazard class(es)

ADR	:	9
RID	:	9
IMDG	:	9
IATA	:	9

14.4 Packing group

ADR		
Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
Tunnel restriction code	:	(-)
RID		
Packing group	:	III
Classification Code	:	M6
Hazard Identification Number	:	90
Labels	:	9
IMDG		
Packing group	:	III
Labels	:	9
EmS Code	:	F-A, S-F

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

IATA (Cargo)

Packing instruction (cargo aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passenger aircraft) : 964
Packing instruction (LQ) : Y964
Packing group : III
Labels : Miscellaneous

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : yes

IATA (Cargo)

Environmentally hazardous : yes

14.6 Special precautions for user

Not applicable

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AIIC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory

Inventories

AICS (Australia), AIIC (Australia), DSL (Canada), IECSC (China), ENCS (Japan), KECI (Korea), NZIOIC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (United States of America (USA))

15.2 Chemical safety assessment

Chemical Safety Assessments for all substances in this product are either Complete or Not applicable.

SECTION 16: Other information

Full text of H-Statements

H302	: Harmful if swallowed.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH071	: Corrosive to the respiratory tract.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

HUNTSMAN

Enriching lives through innovation

ARALDITE STANDARD ULTRA HARDENER

Version	Revision Date:	SDS Number:	Date of last issue: 25.01.2021
2.3	10.09.2021	400001021218	Date of first issue: 20.07.2018

Print Date 20.10.2021

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

Further information

Classification of the mixture:

Eye Dam. 1	H318
Skin Sens. 1	H317
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.