



profichip® VPC3+S

PROFIBUS® DP Slave Controller with Serial Interface



- SPI, I2C, parallel interface
- 4 kB communication RAM
- Function and software compatible with VPC3+C and SPC3 from Siemens
- Supports PROFIBUS DP-V0, DP-V1 and DP-V2 protocols
- HW-PLL for DP-V2 ISOM
- Ultra low power, Vcc 3.3 V
- Software stack and Evaluation kit
- BGA48 / LQFP48 package or proficonn[®] module



The smallest PROFIBUS slave ASIC of them all

Description

profichip's VPC3+S is a communication chip with an 8-bit parallel, SPI, or I²C microprocessor interface for intelligent PROFIBUS Slave applications.


Operation

The VPC3+S handels the message and address identification, checks the data security sequences and protocol processes for PROFIBUS DP. It also supports acyclic communication and alarm messages, described in the DP-V1 extension.

Features described in the DP-V2 extension, as Slave-to-Slave communication Data eXchange Broadcast (DXB), clock synchronization, and the Isochronous-Mode (IsoM), are also provided.

Data Transmission

Automatic baud rate recognition and support of data transmission rates up to 12 Mbit/s, the complete PROFIBUS DP protocol integration, 4 kB communication RAM, and flexible processor interfaces are features to create state-of-the-art PROFIBUS Slave applications.



Compatible with



YASKAWA Europe GmbH

Hugo-Junkers-Str. 13 90411 Nuremberg Germany

Profichip USA, Inc.

980 Birmingham Rd. Ste 721 Alpharetta, GA 30004 USA

+1 (678) 880-6910

sales@profichipusa.com www.profichipusa.com 01/2023 | YEU_PROFICHIP_VPC3+S

