



N2LOK

Hardware Trading Pty Ltd

INOXUS
SERIES

LIMITED WARRANTY
7
YEAR
MECHANICAL

LIMITED WARRANTY
5
YEAR
FINISH

Installation Instructions for Mortise Rebate Kit

Installation Instruction for Mortise Rebate Kit

- Center the Face Plate of Mortise Lock with the Rebate Pedestal to the Centerline of the Swinging/Free Door edge, trace outline of the Rebate Pedestal on the high and low side of Door edge. Chisel out of the high side of the door edge by 238mm(9-11/32") height and 13mm(1/2") deep for the Rebate Pedestal, until the Face Plate of Mortise seats flush to the remaining high side of door edge. Mark screw hole location and drill 2mm(3/32") pilot hole for the Long fixing screws.
- Once the high side of the door edge has been carefully chiseled out cleanly & level to the low side, the Template provided with the Mortise Lock can now be placed on the High side of the Rebate to mark your chosen backset for the Spindle & Euro Cylinder holes.
- Prepare & Drill the Swinging/Free Door in accordance with the Mortise Lock Instruction Sheet & Template, then install Mortise Lock with the longer fixing screws through the Mortise Lock then Rebate Pedestal & finally into the Door & tighten until firm & flush with the high side of the Rebate.
- Close the Swinging/Free Door against the Fixed Door & Mark the Rebate Striker position in the same length as the Mortise Lock Face Plate, then reopen the Door.
- Place Rebate Striker Plate on the centerline of the door jamb on the Fixed Door, lining up the top & bottom to the position marks from the last step then outline clearly with pencil. Chisel out the high side of the door jamb by 242mm height and deep enough for the Rebate Strike to sit flush with the low side of the Rebate.
- Once the outline area on the high side has been chiseled out cleanly & the same on the low side of the Rebate to follow the remaining outline of the Rebate Striker so it sits flush with the low side of the Rebate. In accordance with the Mortise Lock Instructions prepare the Strike Cavity one done place the Strike over the Strike Cavity & in position then tighten with the fixing screws. Once tightened the small return "fence" at the back of the Rebate Striker should be exactly the same height as the high side of the Rebate.
Your Installation is now complete & ready for use.



N2LOK

This product is warranted to be free from mechanical & workmanship defects for 7 years and free from finish & surface defects for 5 years from the original date of purchase. Should a mechanical or finish defect occur within this warranty period just return the product along with proof of purchase to point of purchase for replacement. Premature finish deterioration due to the use of solvents, acid cleaners, paints, climatic conditions i.e. salt air or surface abrasion by keys or jewellery is not considered a defect & thus not covered by this warranty. The same applies for mechanical failure due to the incorrect installation, misuse or abuse will not be covered by this warranty. The removal & refitting of the product & any associated handling & transportation costs is not covered by this warranty. N2LOK reserves the right to modify product styles & finishes without notification. If the same product model is no longer available a similar product model will be supplied. Any accessories, spare parts & trim purchased separately to complete & compliment the lockset or hardware are not covered by this warranty.
**Matte Black finish warranty is 12 months only

LIMITED WARRANTY
7
YEAR
MECHANICAL

LIMITED WARRANTY
5
YEAR
FINISH