

# Safety Data Sheet (SDS)

## SLOW UNIVERSAL REDUCER



### 1. PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 Product identifiers

Product name : SLOW UNIVERSAL REDUCER  
 Product identifier : NA-IPR-S  
 Product Family : SOLVENT BLEND

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses : URETHANE AND ENAMEL PAINT REDUCTION  
 SUITABLE FOR: COLOR COAT, CLEAR COAT, SINGLE STAGE, PRIMERS AND SEALERS.

#### 1.3 Details of the supplier of the safety data sheet

Company : NANOSKIN Car Care Products  
 Total Import Solutions, Inc.  
 14700 Radburn Ave.  
 Santa Fe Springs, CA 90670

Telephone : [562-691-6818](tel:562-691-6818)

Fax : [562-483-8333](tel:562-483-8333)

#### 1.4 Emergency telephone number

Emergency phone # : PERS NORTH AMERICA 1-800-633-8253  
 INTERNATIONAL 1-801-629-0667

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### GHS Classification in accordance with 29 CFR 1910(OSHA HCS)

H225 Highly flammable liquid and vapour.

H227: Combustible liquid.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

##### Precautionary Statements

##### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
 No smoking.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

Modified 1/10/2016

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention. P331 Do NOT induce vomiting.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337+P313: If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P363: Wash contaminated clothing before reuse.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/ container to an approved waste disposal plant.

**2.2 GHS Label elements, including precautionary statements**

Pictogram

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS number	Warnings	Concentration
ACETONE	67-64-1	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336	10-15%
TOLUENE	108-88-3	Flam. Liq. 2; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; H225, H304, H315, H336, H361, H373, H401	10-15%
2-BUTOXYETHANOL	111-76-2	Flam. Liq. 4; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; H227, H312 + H332, H315, H319	30-40%
n-BUTYL ACETATE	123-86-4	Flam. Liq. 3; STOT SE 3; Aquatic Acute 3; H226, H336, H402	30-35%

Modified 1/10/2016


#### 4. FIRST AID MEASURES

##### First aid procedures

###### After inhalation:

Get victim to fresh air. Give artificial respiration or oxygen if breathing has stopped. Get prompt medical attention. Do not give fluids if victim is unconscious. If victim is conscious, rinse mouth with water and contact emergency number listed in section 1.4.

###### After contact with skin:

Immediately wash skin with soap and water. May cause irritation. Seek medical attention if irritation or allergic reaction is present.

###### After contact with eyes:

Immediately flush eyes with running water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek prompt medical attention if redness or irritation occurs. Avoid agitation. Remove contact lenses if able.

###### After ingestion:

Rinse mouth with water, contact poison control center or emergency number listed in section 1.4. Never give anything by mouth to an unconscious person.

###### Advice to doctor / Treatment:

None known.

#### 5. FIRE FIGHTING MEASURES

**FIRE HAZARD** Fire hazard : DIRECT FIRE HAZARD. Highly flammable. Gas/vapour flammable with air within explosion limits.

**INDIRECT FIRE HAZARD** May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".

**EXPLOSION HAZARD** Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".

**REACTIVITY** Upon combustion: CO and CO<sub>2</sub> are formed. Violent to explosive reaction with many compounds. Prolonged storage: on exposure to light: release of harmful gases/vapours. Reacts violently with (strong) oxidizers: peroxidation resulting in increased fire or explosion risk.

##### FIREFIGHTING INSTRUCTIONS

Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat.

After cooling: persistent risk of physical explosion.

##### PROTECTION DURING FIREFIGHTING

Heat/fire exposure: compressed air/oxygen apparatus.

#### 6. ACCIDENTAL RELEASE MEASURES

**PROTECTIVE EQUIPMENT** Gloves. Protective goggles. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus.

**EMERGENCY PROCEDURES** Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes.

##### FOR EMERGENCY RESPONDERS

Modified 1/10/2016

**PROTECTIVE EQUIPMENT  
EMERGENCY PROCEDURES**Equip cleanup crew with proper protection.  
Ventilate area.

SEE SECTION 8 FOR PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

**7. HANDLING AND STORAGE****HANDLING**

Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Avoid prolonged and repeated contact with skin. Keep container tightly closed. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

**STORAGE**

Store with caution. Do not store in temperatures above 80F. Bottle/container may swell and or fumes accumulate. Store in adequate ventilation.

**HYGEINE**

Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guideline Comments****Exposure Limits:**

<b>COMPONENT</b>	<b>CAS NUMBER</b>	<b>VALUE</b>	<b>CONTROL PARAMETERS</b>	<b>BASIS</b>
TOLUENE	108-88-3	TWA	100 ppm 375 mg/m <sup>3</sup>	USA. OSHA <small>TABLE Z-1</small>
		STEL	150 ppm 560 mg/m <sup>3</sup>	
		TWA	200PPM	TABLE Z-2
		CEIL	300 ppm	
		Peak	500 ppm	
		TWA	20 ppm	USA. ACGIH (TLV)
		REMARKS	Visual impairment Female reproductive	Pregnancy loss
n-Butyl acetate	123-86-4	TWA	100 ppm 375 mg/m <sup>3</sup>	USA. NIOSH
		ST	150 ppm 560 mg/m <sup>3</sup>	
		TWA	150 ppm USA.	ACGIH (TLV)
		REMARKS	Upper Respiratory Tract irritation Eye irritation	
		TWA	150.000000 ppm	USA. ACGIH (TLV)
		REMARKS	Upper Respiratory Tract irritation Eye irritation	
		STEL	200 ppm	USA. ACGIH (TLV)
		REMARKS	Upper Respiratory Tract irritation Eye irritation	
		STEL	200.000000 ppm	USA. ACGIH (TLV)
		REMARKS	Upper Respiratory Tract irritation Eye irritation	
ACETONE	67-64-1	TWA	150.000000 ppm 710.000000 mg/m <sup>3</sup>	
		TWA	150.000000 ppm 710.000000 mg/m <sup>3</sup>	USA. NIOSH
		ST	200.000000 ppm 950.000000 mg/m <sup>3</sup>	
		TWA	500 ppm USA ACGIH ACGIH STEL (ppm) 750 ppm	
		TWA	2400 mg/m <sup>3</sup> U	
2-BUTOXYETHANOL	111-76-2	TWA	1000 ppm	
		TWA	20.000000 ppm USA. ACGIH (TLV)	
		The value in mg/m <sup>3</sup> is approximate.		

**BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS**

<b>COMPONENT</b>	<b>CAS NUMBER</b>	<b>PARAMETER</b>	<b>VALUE</b>	<b>BIOLOGICAL SPECIMEN</b>
------------------	-------------------	------------------	--------------	----------------------------

Modified 1/10/2016

Toluene	108-88-3	Toluene	0.0200 mg/l	In blood ACGIH - Biological Exposure Indices (BEI) Remarks Prior to last shift of workweek
		Toluene	0.0300 mg/l	Urine ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)		
		o-Cresol	0.3000 mg/g	Urine ACGIH - Biological Exposure Indices (BEI)
		End of shift (As soon as possible after exposure ceases)		

**ENGINEERING CONTROLS** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

**Materials for protective clothing :** Use butyl rubber of at least .3mm thickness. Avoid nitrile and pvc protection.

<b>Hand protection</b>	Please use gloves with the above materials recommendation.
<b>Eye protection</b>	Protective goggles.
<b>Skin and body protection</b>	Head/neck protection. Protective clothing.
<b>Respiratory protection</b>	Wear gas mask with filter type A if conc. in air > exposure limit.
<b>Other information</b>	Do not eat, drink or smoke during use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical State</b>	liquid
<b>Appearance</b>	Clear liquid solvent
<b>Particle Size</b>	Not applicable
<b>Odor</b>	Aromatic
<b>Odor Threshold</b>	No Available Data
<b>Molecular Formula</b>	Mixture
<b>Molecular Weight</b>	Mixture
<b>Boiling Point</b>	85-112C
<b>Decomposition Temperature</b>	No Available Data
<b>Melting point</b>	No Available Data
<b>Freezing Point</b>	No Available Data
<b>Relative Density</b>	~.90g/cm <sup>3</sup>
<b>Bulk Density</b>	No Available Data
<b>Solubility in Water</b>	No Available Data
<b>Solubility in other liquids</b>	No Available Data
<b>Flash point</b>	19C

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Avoid extreme temperatures.
<b>Hazardous Decomposition Products</b>	Carbon Oxides.
<b>Possibility of Hazardous Reactions</b>	Do not bring into contact with oxidizers.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

<b>N-BUTYL ACETATE</b>	LD50 Oral - Rat - female - 10,760 mg/kg (OECD Test Guideline 423)
	LC50 Inhalation - Rat - male and female - 4 h - > 21 mg/l (OCED 403)
	LD50 Dermal - Rabbit - male and female - > 14,112 mg/kg (OECD Guideline 402)
<b>ACETONE</b>	LD50 oral rat 5800 mg/kg (Rat; Experimental value,Rat; Experimental value)
	LD50 dermal rabbit 20000 mg/kg (Rabbit; Experimental value)

Modified 1/10/2016

	LC50 inhalation rat (mg/l) 71 mg/l/4h (76 mg/l/4h; Rat; Rat; Experimental value; Experimental value,76 mg/l/4h; Rat; Rat; Experimental value; Experimental value)
	LC50 inhalation rat (ppm) 30000 ppm/4h (Rat; Experimental value,Rat; Experimental value)
<b>2-BUTOXYETHANOL</b>	LD50 Oral - Rat - male - 880 mg/kg (OECD Test Guideline 401)
<b>TOLUENE</b>	LD50 Oral - Rat - > 5,580 mg/kg LC50 Inhalation - Rat - 4 h - 12,500 - 28,800 mg/m3 LD50 Dermal - Rabbit - 12,196 mg/kg No data available
<b>SKIN CORROSION/IRRITATION</b>	SKIN-RABBIT 4H
<b>RESPIRATORY</b>	NO DATA AVAILABLE
<b>SERIOUS EYE DAMAGE/IRRITATION</b>	Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2) CAUSES EYE IRRITATION/DAMAGE
<b>GERM CELL MUTAGENICITY</b>	Rat Liver DNA damage IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene) 3 - Group 3: Not classifiable as to its carcinogenicity to humans (2-Butoxyethanol) INSUFFICIENT DATA FROM OTHER REGULATORY GROUPS TO ASCERTAIN HAZARD FACTORS.
<b>Reproductive toxicity</b>	Damage to fetus possible Suspected human reproductive toxicant Reproductive toxicity - Rat - Inhalation Paternal Effects: Spermatogenesis (including genetic material, sperm morphology,motility, and count). Experiments have shown reproductive toxicity effects in male and female laboratory animals. Overexposure may cause reproductive disorder(s) based on tests with laboratory animals
<b>Developmental Toxicity</b>	Rat - Oral Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Human exposure above 200 ppm can be expected to cause narcosis, damage to the kidney and liver and present an abnormal blood picture showing erythropenia, reticulocytosis, granulocytosis, leukocytosis, and would be likely to cause fragility of erythrocytes and hematuria. Swallowing of 2-butoxyethanol results in a sour taste that turns to a burning sensation and is followed by numbness of the tongue which indicates paralysis of the sensory nerve endings., Central nervous system depression, Headache, stupor, numbness of the tongue, loss of taste, narcosis Stomach - Irregularities - Based on Human Evidence Stomach - Irregularities - Based on Human Evidence

## 12. ECOLOGICAL TOXICITY

### TOXICITY

<b>N-BUTYL ACETATE</b>	aerobic - Exposure time 28 d Result: 83 % - Readily biodegradable
Toxicity to fish flow-through test	LC50 - Pimephales promelas (fathead minnow) - 18 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates static test	EC50 - Daphnia (water flea) - 44 mg/l - 48 h Toxicity to algae static test EC50 - Desmodesmus subspicatus (Scenedesmus subspicatus) - 674.7 mg/l - 72 h
<b>2-BUTOXYETHANOL</b>	aerobic - Exposure time 28 d Result: 90.4 % - Readily biodegradable
Toxicity to fish static test	LC50 - Oncorhynchus mykiss (rainbow trout) - 1,474 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates Immobilization	EC50 - Daphnia magna (Water flea) - 1,550 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae Growth inhibition	EC50 - Pseudokirchneriella subcapitata (green algae) - 1,840 mg/l - 72 h (OECD Test Guideline 201)
<b>ACETONE</b>	Readily biodegradable in soil and water.

Modified 1/10/2016

	LC50 fishes 1 6210 mg/l (96 h; Pimephales promelas; NOMINAL CONCENTRATION)
	EC50 Daphnia 1 8800 mg/l (48 h; Daphnia pulex)
<b>Toluene</b>	Leuciscus idus (Golden orfe) - 3 d - 0.05 mg/l Bioconcentration factor (BCF): 90
Toxicity to fish	LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d
Toxicity to daphnia and other aquatic invertebrates	EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h
Toxicity to algae	EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h

### 13. DISPOSAL CONSIDERATIONS

Product Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging** Dispose of as unused product.

### 14. TRANSPORT INFORMATION

#### Shipping Information

UN 1993 - Flammable liquids n.o.s. Class 3, PGII

NFPA

#### Special Shipping Information

Not applicable.

#### HMIS

**HEALTH** 2

**FLAMMABILITY** 2

**REACTIVITY** 0

### 15. REGULATORY INFORMATION

#### United States

SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313:

Toluene CAS-No. 108-88-3 Revision Date 2007-07-01

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

Toluene CAS-No. 108-88-3 Revision Date 2007-07-01

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

n-Butyl acetate CAS-No. 123-86-4 Revision Date 1993-04-24

#### Pennsylvania Right To Know Components

Toluene CAS-No. 108-88-3 Revision Date 2007-07-01

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

Modified 1/10/2016

n-Butyl acetate CAS-No. 123-86-4 Revision Date 1993-04-24

New Jersey Right To Know Components

Toluene CAS-No. 108-88-3 Revision Date 2007-07-01

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

n-Butyl acetate CAS-No. 123-86-4 Revision Date 1993-04-24

California Prop. 65 Components

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene CAS-No. 108-88-3 Revision Date 2009-02-01

## 16. OTHER INFORMATION

**SDS Prepared by  
Disclaimer**

### **Total Import Solutions, Inc. dba NANOSKIN Car Care Products**

This health and safety information is correct to the best of our knowledge and belief at the date of its publication, but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, to maintain revised copies of this information to be requested. When applicable, revised copies shall be sent to customers whom have been directly supplied with this substance. It must be known that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the user. The information given in the Data Sheet is designed only as guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this sheet.