

# Safety Data Sheet (SDS)

## LOW ODOR MASTIC REMOVER



### 1. PRODUCT AND COMPANY IDENTIFICATION

#### 1.1 Product identifiers

Product name : LOW ODOR MASTIC REMOVER  
 Product identifier : NA-LOM  
 Product Family : SOLVENT BLEND

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses : For cleaning fiberglass and asbestos surfaces prior to painting. For mastic removal of asphalt, petroleum based greases and more.

#### 1.3 Details of the supplier of the safety data sheet

Company : NANOSKIN Car Care Products  
 Total Import Solutions, Inc.  
 14700 Radburn Ave.  
 Santa Fe Springs, CA 90670  
 Telephone : [562-691-6818](tel:562-691-6818)  
 Fax : [562-483-8333](tel:562-483-8333)

#### 1.4 Emergency telephone number

Emergency phone # : PERS NORTH AMERICA 1-800-633-8253  
 INTERNATIONAL 1-801-629-0667

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### GHS Classification in accordance with 29 CFR 1910(OSHA HCS)

H225 Highly flammable liquid and vapour.

H227: Combustible liquid.

H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H401 Toxic to aquatic life.

##### Precautionary Statements

##### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
 No smoking.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

Modified 1/10/2016

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

**Response:**

H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

**Precautionary Statements:**

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

**2.2 GHS Label elements, including precautionary statements**

Pictogram

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Component	CAS number	Warnings	Concentration
2-BUTOXYETHANOL	111-76-2	Flam. Liq. 4; Acute Tox. 4; Skin Irrit. 2; Eye Irrit. 2A; H227, H312 + H332, H315, H319	1-10%
STODDARD SOLVENT	64742-96-7	Flam. Liq. 4; skin irrit. 2; eye irrit 2A	90-100%

Modified 1/10/2016


#### 4. FIRST AID MEASURES

##### First aid procedures

###### After inhalation:

Get victim to fresh air. Give artificial respiration or oxygen if breathing has stopped. Get prompt medical attention. Do not give fluids if victim is unconscious. If victim is conscious, rinse mouth with water and contact emergency number listed in section 1.4.

###### After contact with skin:

Immediately wash skin with soap and water. May cause irritation. Seek medical attention if irritation or allergic reaction is present.

###### After contact with eyes:

Immediately flush eyes with running water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek prompt medical attention if redness or irritation occurs. Avoid agitation. Remove contact lenses if able.

###### After ingestion:

Rinse mouth with water, contact poison control center or emergency number listed in section 1.4. Never give anything by mouth to an unconscious person.

###### Advice to doctor / Treatment:

None known.

#### 5. FIRE FIGHTING MEASURES

##### FIRE HAZARD

Fire hazard : DIRECT FIRE HAZARD. Highly flammable. Gas/vapour flammable with air within explosion limits.

##### INDIRECT FIRE HAZARD

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. Reactions involving a fire hazard: see "Reactivity Hazard".

##### EXPLOSION HAZARD

##### EXPLOSION

may be

Hazard".

Gas/vapour explosive with air within explosion limits. INDIRECT HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. Ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".

##### REACTIVITY

Upon combustion: CO and CO<sub>2</sub> are formed. Violent to explosive reaction with many compounds. Prolonged storage: on exposure to light: release of harmful gases/vapours. Reacts violently with (strong) oxidizers: peroxidation resulting in increased fire or explosion risk.

##### FIREFIGHTING INSTRUCTIONS

Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

##### PROTECTION DURING FIREFIGHTING

Heat/fire exposure: compressed air/oxygen apparatus.

#### 6. ACCIDENTAL RELEASE MEASURES

##### PROTECTIVE EQUIPMENT

Gloves. Protective goggles. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus.

##### EMERGENCY PROCEDURES

Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no

Modified 1/10/2016

smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes.

**FOR EMERGENCY RESPONDERS**

**PROTECTIVE EQUIPMENT** Equip cleanup crew with proper protection.

**EMERGENCY PROCEDURES** Ventilate area.

SEE SECTION 8 FOR PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

**7. HANDLING AND STORAGE**

**HANDLING** Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Avoid prolonged and repeated contact with skin. Keep container tightly closed. Measure the concentration in the air regularly. Work under local exhaust/ventilation.

**STORAGE** Store with caution. Do not store in temperatures above 80F. Bottle/container may swell and or fumes accumulate. Store in adequate ventilation.

**HYGEINE** Do not eat, drink or smoke when using this product. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

Exposure Guideline Comments		Exposure Limits:		
COMPONENT	CAS NUMBER	VALUE	CONTROL PARAMETERS	BASIS
Distillates (petroleum), hydrotreated light	64742-47-8	TWA	500 ppm 2,000 mg/m <sup>3</sup>	
		OSHA Z-1 TWA	200 mg/m <sup>3</sup> (as total hydrocarbon vapor)	
		ACGIH TWA	400 ppm 1,600 mg/m <sup>3</sup>	
Solvent naphtha (petroleum), heavy aliph.	64742-96-7	TWA	200 mg/m <sup>3</sup> (as total hydrocarbon vapor)	ACGIH
2-BUTOXYETHANOL	111-76-2	TWA	20.000000 ppm USA.	ACGIH (TLV)

The value in mg/m<sup>3</sup> is approximate.

**ENGINEERING CONTROLS** Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

**Materials for protective clothing :** Use butyl rubber of at least .3mm thickness. Avoid nitrile and pvc protection.

**Hand protection** Please use gloves with the above materials recommendation.

**Eye protection** Protective goggles.

**Skin and body protection** Head/neck protection. Protective clothing.

**Respiratory protection** Wear gas mask with filter type A if conc. in air > exposure limit.

**Other information** Do not eat, drink or smoke during use.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical State</b>	liquid
<b>Appearance</b>	Clear liquid solvent
<b>Particle Size</b>	Not applicable
<b>Odor</b>	Aromatic

Modified 1/10/2016

<b>Odor Threshold</b>	No Available Data
<b>Molecular Formula</b>	Mixture
<b>Molecular Weight</b>	Mixture
<b>Boiling Point</b>	200 - 300 °C
<b>Decomposition Temperature</b>	No Available Data
<b>Melting point</b>	No Available Data
<b>Freezing Point</b>	No Available Data
<b>Relative Density</b>	~.825g/cm <sup>3</sup>
<b>Bulk Density</b>	No Available Data
<b>Solubility in Water</b>	No Available Data
<b>Solubility in other liquids</b>	No Available Data
<b>Flash point</b>	80 - 96 °C

## 10. STABILITY AND REACTIVITY

<b>Chemical Stability</b>	Stable under normal conditions.
<b>Conditions to Avoid</b>	Avoid extreme temperatures.
<b>Hazardous Decomposition Products</b>	Carbon Oxides.
<b>Possibility of Hazardous Reactions</b>	Do not bring into contact with oxidizers.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

**2-BUTOXYETHANOL** LD50 Oral - Rat - male - 880 mg/kg (OECD Test Guideline 401)

### Solvent naphtha (petroleum), heavy aliph.

64742-47-8: Acute oral toxicity : LD50 (rat, male and female): > 5,000 mg/kg

Method: Fixed dose procedure GLP: yes Acute inhalation toxicity : Remarks:

No data available Acute dermal toxicity : LD50 (rabbit, male and female): >

2,000 mg/kg Method: Fixed dose procedure GLP: yes

## 12. ECOLOGICAL TOXICITY

### TOXICITY

<b>2-BUTOXYETHANOL</b>	aerobic - Exposure time 28 d Result: 90.4 % - Readily biodegradable
Toxicity to fish static test	LC50 - Oncorhynchus mykiss (rainbow trout) - 1,474 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates Immobilization	EC50 - Daphnia magna (Water flea) - 1,550 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae Growth inhibition	EC50 - Pseudokirchneriella subcapitata (green algae) - 1,840 mg/l - 72 h (OECD Test Guideline 201)

### Solvent Naptha (petroleum), heavy aliph.

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 25 mg/l Exposure time: 96 h

Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 203 GLP: yes Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l Exposure time: 48 h Test Type: static test Analytical monitoring: yes Method: OECD Test Guideline 202 GLP: yes

Modified 1/10/2016

**13. DISPOSAL CONSIDERATIONS**

Product Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

**Contaminated packaging** Dispose of as unused product.

**14. TRANSPORT INFORMATION****Shipping Information**

DOT Proper Shipping Name UN1263, Paint Related Material, 3, PGII DOT Hazard Class: 3 DOT Hazard Label: FLAMMABLE LIQUID UN/NA Number: UN1263 Packing Group: II

**Special Shipping Information**

Not applicable.

**HMIS**

**HEALTH** 2

**FLAMMABILITY** 2

**REACTIVITY** 0

**15. REGULATORY INFORMATION****United States**

SARA 302 Components No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components The following components are subject to reporting levels established by SARA Title III, Section 313:

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

**SARA 311/312 Hazards**

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components**

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

**Pennsylvania Right To Know Components**

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

64742-47-8 Distillates (petroleum), hydrotreated light 0 - 100 %

64742-96-7 Solvent naphtha (petroleum), heavy aliph

**New Jersey Right To Know Components**

2-Butoxyethanol CAS-No. 111-76-2 Revision Date 1993-04-24

64742-47-8 Distillates (petroleum), hydrotreated light 0 - 100 %

64742-96-7 Solvent naphtha (petroleum), heavy aliph

**California Prop. 65 Components**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**16. OTHER INFORMATION****SDS Prepared by**

**Total Import Solutions, Inc. dba NANOSKIN Car Care Products**

**Disclaimer**

This health and safety information is correct to the best of our knowledge and belief at the date of its publication, but we cannot accept liability for any loss,

Modified 1/10/2016

injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, to maintain revised copies of this information to be requested. When applicable, revised copies shall be sent to customers whom have been directly supplied with this substance. It must be known that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the user. The information given in the Data Sheet is designed only as guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this sheet.