



2 FINISHING

3 PROTECTION



XTRA MORDENTE





PRODUCT DESCRIPTION

Extra cutting polishing compound used either to remove marks and P600-P800 sand scratches (according to the hardness of treated resins) or to restore high-oxidized gelcoats very fast and well, without overheating the surface. It assures a high quality finish without marks and haze as well as with low particles' over-splatting. Its specific viscosity allows an easy, clean and even application. Further, its new revolutionary formula has been designed to remain wet for longer time, thus avoiding drying-up on the surface and on the pad.

PHYSICAL PROPERTIES

Colour: White

Physical form: Creamy Odour: Light and pleasant

Density: 1,66 g/ml

Flammability: Not flammable

Type of surface: grp, gelcoat, epoxy

HOW TO USE

Mix well, then apply by variable speed polisher, selecting either an anti-scratch wool pad SL3 for a balanced cutting-polishing action or ST1 for a more aggressive one. Apply a small quantity of compound on the polisher-pad. Let the polisher turn at low revolutions, speeding them up (800-2500 RPM) while spreading the paste with crossed movements. Pay attention at not overheating the surface. If necessary, please repeat the application more times. Eventually, wipe it off with a clean cloth.

PRODUCT INFORMATION

Packaging	Code	Pcs/Box
1 kg	600685	16
3 kg	600686	4

INSTRUCTIONS FOR USE










CROSSED MOVEMENTS

RECOMMENDATIONS









MIX BEFORE USE

SMALL QUANTITY

CLOSE THE CAP

STORAGE

FOLLOWING STEPS



