



SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : STOP MOISI

Product description : Mildew remover for fabrics

UFI : VJV1-R0YM-Y00C-9NY7

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Registered company name: MATT CHEM PRODUCT SAS

Address : 37, rue de Fontenay 92220 Bagneux FRANCE

Telephone : +33 (0) 1 42 53 73 73

Email : info@mattchem.fr

Urgences antipoison (24h/24, 7j/7, grand public et professionnels de santé) : 03 83 22 50 50. Urgence vitale, faire le 15

1.4. Emergency telephone number : +33 (0)1-45-42-59-59.

Association/Organisation : FRANCE : ORFILA - INRS - <http://www.centres-antipoison.net>.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Acute inhalation toxicity, Category 4 (Acute Tox. 4, H332).

Skin corrosion, Category 1B (Skin Corr. 1B, H314).

Serious eye damage, Category 1 (Eye Dam. 1, H318).

Contact with acids liberates toxic gas (EUH031).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

GHS07

Signal Word :

DANGER

Product identifiers :

EC 231-836-6

EC 215-181-3

Hazard statements :

H314

H332

EUH031

Precautionary statements - Prevention :

P280

Precautionary statements - Response :

P303 + P361 + P353

P305 + P351 + P338

P310

P363

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances \geq 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	Classification (EC) 1272/2008	Note	%
INDEX: 00002318366 CAS: 7758-19-2 EC: 231-836-6 REACH: 01-2119529240-51-0003 CHLORITE DE SOUDE	GHS06, GHS05, GHS09, GHS08, GHS03 Dgr Ox. Liq. 1, H271 Acute Tox. 3, H301 Acute Tox. 2, H310 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT RE 2, H373 Aquatic Chronic 3, H412 Aquatic Acute 1, H400 M Acute = 1 EUH:031		2.5 <= x % < 10
INDEX: 019_002_00_8 CAS: 1310-58-3 EC: 215-181-3 REACH: 01-2119487136-33 POTASSIUM HYDROXIDE	GHS07, GHS05 Dgr Met. Corr. 1, H290 Acute Tox. 4, H302 Skin Corr. 1A, H314	[1]	0 <= x % < 2.5
INDEX: 068439 57 6 CAS: 68439-57-6 EC: 270-407-8 REACH: 01-2119513401-57 ALPHA OLÉFINE SULFONÉE, SEL SODIQUE	GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318		0 <= x % < 2.5
INDEX: 3332_27_2 CAS: 3332-27-2 EC: 222-059-3 REACH: 01-2119949262-37 MYRISTYL DIMETHYLAMINE OXIDE	GHS05, GHS09 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Acute 1, H400 M Acute = 1		0 <= x % < 2.5
INDEX: I1643_20_5 CAS: 1643-20-5 EC: 216-700-6 REACH: 01-2120068065-58-0000 DODECYLDIMETHYLAMINE OXIDE	GHS05, GHS07, GHS09 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 1		0 <= x % < 2.5

Specific concentration limits:

Identification	Specific concentration limits	ATE
INDEX: 019_002_00_8 CAS: 1310-58-3 EC: 215-181-3 REACH: 01-2119487136-33 POTASSIUM HYDROXIDE	Skin Corr. 1A: H314 C>= 5% Skin Corr. 1B: H314 2% <= C < 5% Skin Irrit. 2: H315 0.5% <= C < 2% Eye Dam. 1: H318 C>= 2% Eye Irrit. 2: H319 0.5% <= C < 2%	dermal: ATE = 1350 mg/kg BW
INDEX: I1643_20_5 CAS: 1643-20-5 EC: 216-700-6 REACH: 01-2120068065-58-0000 DODECYLDIMETHYLAMINE OXIDE		oral: ATE = 1500 mg/kg BW

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Do not proceed with mouth-to-mouth or mouth-to-nose resuscitation. Use the appropriate equipment.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

Seek medical attention immediately, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

- phosgene (CCl₂O)

- chlorine (Cl₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralize with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Fire prevention :

Handle in well-ventilated areas.

Prevent access by unauthorized personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed in a dry, well-ventilated place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1310-58-3			2 mg/m ³		

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
1310-58-3	-	-	-	2	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1310-58-3		2 mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

POTASSIUM HYDROXIDE (CAS: 1310-58-3)

Final use: Workers.

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL : 1 mg of substance/m³

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166. In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours. Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1. Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- PVC (polyvinyl chloride)
- Body protection

Avoid skin contact.

Wear suitable protective clothing. Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Wear suitable protective clothing and, in particular, an apron and boots. These items of clothing shall be maintained in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Anti-gas and vapor filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	
Physical state :	Fluid liquid.
Colour Unspecified	
Odour	
Odour threshold :	Not stated.
Melting point	
Melting point/melting range :	Not specified.
Freezing point	
Freezing point / Freezing range :	Not stated.
Boiling point or initial boiling point and boiling range	
Boiling point/boiling range :	Not specified.
Flammability	
Flammability (solid, gas) :	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%) :	Not stated.
Explosive properties, upper explosivity limit (%) :	Not stated.
Flash point	
Flash point interval :	Not relevant.
Auto-ignition temperature	
Self-ignition temperature :	Not specified.
Decomposition temperature	
Decomposition point/decomposition range :	Not specified.
pH	
pH :	13.30 . Strongly basic.
pH (aqueous solution) :	Not stated.
Kinematic viscosity	
Viscosity :	Not stated.
Solubility	
Water solubility :	Dilutable.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C) :	Not relevant.
Density and/or relative density	
Density :	= 1
Relative vapour density	
Vapour density :	Not stated.
9.2. Other information	
No data available.	
9.2.1. Information with regard to physical hazard classes	
No data available.	
9.2.2. Other safety characteristics	
No data available.	

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

This mixture reacts with acids, releasing toxic gases in dangerous quantities.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- frost

10.5. Incompatible materials

Keep away from :

- acids

Releases a toxic gas when in contact with acids.

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)

- phosgene (CCl₂O)

- chlorine (Cl₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Harmful by inhalation.

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure between three minutes and one hour.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

11.1.1. Substances

Acute toxicity :

POTASSIUM HYDROXIDE (CAS: 1310-58-3)

Dermal route : LD50 = 1350 mg/kg
Species : Rabbit

DODECYLDIMETHYLAMINE OXIDE (CAS: 1643-20-5)

Oral route : LD50 > 2000 mg/kg

ALPHA OLÉFINE SULFONÉE, SEL SODIQUE (CAS: 68439-57-6)

Oral route : LD50 > 2310 mg/kg

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 6300 mg/kg

Species : Rabbit

11.1.2. Mixture

No toxicological data available for the mixture.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

ALPHA OLÉFINE SULFONÉE, SEL SODIQUE (CAS: 68439-57-6)

Fish toxicity : LC50 = 12.2 mg/l

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 = 4.53 mg/l

Species : Daphnia magna

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 = 5.2 mg/l

ISO 10253 (Water quality - Marine Algal Growth Inhibition Test with Skeletonema costatum and Phaeodactylum tricornutum)

POTASSIUM HYDROXIDE (CAS: 1310-58-3)

Fish toxicity : LC50 80 mg/l

Species : Gambusia affinis

Duration of exposure : 96 h

Crustacean toxicity : EC50 270 mg/l

Species : Daphnia magna

Duration of exposure : 24 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

ALPHA OLÉFINE SULFONÉE, SEL SODIQUE (CAS: 68439-57-6)

Biodegradability : Rapidly degradable.

POTASSIUM HYDROXIDE (CAS: 1310-58-3)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

ALPHA OLÉFINE SULFONÉE, SEL SODIQUE (CAS: 68439-57-6)

Octanol/water partition coefficient : log K_{ow} = 0.3

POTASSIUM HYDROXIDE (CAS: 1310-58-3)

Octanol/water partition coefficient : log K_{ow} < 3.

Bioaccumulation : BCF < 100.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2017 - IMDG 2016 - ICAO/IATA 2017).

14.1. UN number

3267

14.2. UN proper shipping name

UN3267=CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(chlorite de soude)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ.	Provis	EQ	Cat.	Tunnel
	8	C7	III	8	80	5L	274	E1	3	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	8	-	III	5L	F-A,S-B	223 274	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager.	Cargo	Cargo	note	EQ
	8	-	III	852	5L	856	60L	A3 A803	E1
	8	-	III	Y841	1L	-	-	A3 A803	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>.

Particular provisions :

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H271 May cause fire or explosion; strong oxidiser.

H290 May be corrosive to metals.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H310 Fatal in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated exposure .

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

EUH031 Contact with acids liberates toxic gas.

Abbreviations and acronyms :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

EACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

BW : Body Weight

DNEL : Derived No-Effect Level

UFI : Unique formulation identifier.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.