

Continental 
The Future in Motion



Continental racing tires:
For ultimate performance
in racing applications.

www.conti-moto.com

ContiTrack

NEW

New developed slick tire for the ultimate racing and track day performance (NHS).

- › Sustainable performance together with higher durability.
- › New carcass construction for significantly greater braking stability, precise turn-in and noticeably better corner exit traction.
- › Completely new compound variations, adapted to Supersport and superbikes.
- › Innovative, completely new developed contour with the dimensions 120/75 R 17 and 200/65 R 17 for nearly all modern superbikes.



ZeroDegree

Inch	Size	TL/TT	Compound	Article No.	Remarks
------	------	-------	----------	-------------	---------

Front wheel

17"	120/70 R 17 NHS	TL	ContiTrack soft	02 44 403	New, from 1 st quarter of 2016
	120/70 R 17 NHS	TL	ContiTrack medium	02 44 404	New, from 1 st quarter of 2016
	120/75 R 17 NHS	TL	ContiTrack soft	02 44 391	New, from 2 nd quarter of 2016
	120/75 R 17 NHS	TL	ContiTrack medium	02 44 405	New, from 2 nd quarter of 2016


Rear wheel

17"	160/60 R 17 NHS	TL	ContiTrack soft	02 44 407	New, from 2 nd quarter of 2016
	160/60 R 17 NHS	TL	ContiTrack medium	02 44 408	New, from 2 nd quarter of 2016
	160/60 R 17 NHS	TL	ContiTrack hard	02 44 409	New, from 2 nd quarter of 2016
	180/60 R 17 NHS	TL	ContiTrack soft	02 44 410	New, from 1 st quarter of 2016
	180/60 R 17 NHS	TL	ContiTrack medium	02 44 411	New, from 1 st quarter of 2016
	180/60 R 17 NHS	TL	ContiTrack hard	02 44 412	New, from 1 st quarter of 2016
	190/60 R 17 NHS	TL	ContiTrack soft	02 44 413	New, from 1 st quarter of 2016
	190/60 R 17 NHS	TL	ContiTrack medium	02 44 414	New, from 1 st quarter of 2016
	190/60 R 17 NHS	TL	ContiTrack hard	02 44 415	New, from 1 st quarter of 2016
	200/65 R 17 NHS	TL	ContiTrack soft	02 44 392	New, from 2 nd quarter of 2016
	200/65 R 17 NHS	TL	ContiTrack medium	02 44 417	New, from 2 nd quarter of 2016

Applications:

160/60 R 17	4 ½" and 5" rims	for supermoto / mono class
180/60 R 17	5 ½" rims	for supersport bikes
190/60 R 17	5 ½" and 6" rims	for supersport bikes and superbikes
200/65 R 17	6" rims	for superbikes

Modification options:



+ Corner exit traction

- Braking stability

To adjust the transmission ratio to the larger tires, use a chain wheel with one additional tooth. The chassis geometry can be determined using the „Rear wheel measurements“ table.

Compound variations:

Soft	Sprint racing, one-day training; good at high outdoor temperatures
Medium	Sprint racing, long-distance racing, 1-2 day training; for a wide temperature range
Hard	Long-distance racing, multi-day training; good at low outdoor temperatures

Recommendation:

Front wheel	Soft
Rear wheel	Medium



ContiTrack

NEW

New developed slick tire for the ultimate racing and track day performance (NHS).

Recommended tire pressure:


For racing use: After at least an hour with electric blankets at 80 °C. The tire pressure should be measured and adjusted directly after the first short session.

ContiTrack	Front	Rear
Hot (80 °C)	2.25 bar	1.55 - 1.6 bar

Rear wheel dimensions

Size	Diameter	Circumference	Width
160/60 R 17	631 mm	1982 mm	160 mm
180/60 R 17	649 mm	2039 mm	184 mm
190/60 R 17 - on 5 1/2" rims	655 mm	2058 mm	186 mm
190/60 R 17 - on 6" rims	655 mm	2058 mm	192 mm
200/65 R 17	662 mm	2080 mm	200 mm

Circumference:
entire tread



ContiRace *ATTACK* Comp.

High performance tire for the race track.
(soft/medium)

- › High performance race tire available in various compounds for the perfect adaptation to different conditions.
- › MultiGrip Technology ensures high mileage, for endurance racing or track days.
- › Street legal use up to 270 km/h (169 mph).



Inch	Size	LI	SI	TL/TT	Compound	Article No.	Remarks	
17"	120/70 ZR 17	M/C	58	W	TL	Soft	02 44 265	
	120/70 ZR 17	M/C	58	W	TL	Medium	02 44 266	

Front wheel

Rear wheel

17"	160/60 ZR 17	M/C	69	W	TL	Soft	02 44 017	
	160/60 ZR 17	M/C	69	W	TL	Medium	02 44 259	
	180/60 ZR 17	M/C	75	W	TL	Soft	02 44 173	
	180/60 ZR 17	M/C	75	W	TL	Medium	02 44 077	
	190/55 ZR 17	M/C	75	W	TL	Soft	02 44 019	
	190/55 ZR 17	M/C	75	W	TL	Medium	02 44 270	

Recommended tire pressure:

For racing use: After at least an hour with electric blankets at 80 °C. The tire pressure should be measured and adjusted directly after the first short session.

ContiRaceAttack Comp.	Front	Rear
Cold	2.1 bar	160 - 1.5 bar 180 - 1.4 bar 190 - 1.3 bar
Hot (80 °C)	2.25 bar	not above 1.7 bar

ContiRace **ATTACK** Comp.End.

Street race tire:

Translates race performance to the road.

- › Real high performance race tire for street legal use.
- › Developed on the racetrack to give race performance in a road tire.
- › Used in worldwide Endurance Racing.
- › Precise handling with an increased footprint at extreme lean angles for more grip in corners due to an optimized front tire contour.



Inch	Size	LI	SI	TL/TT	Article No.	Remarks
------	------	----	----	-------	-------------	---------

Front wheel

17"	120/70 ZR 17	M/C	(58 W)	TL	02 44 151	
-----	--------------	-----	--------	----	-----------	--

Rear wheel

17"	160/60 ZR 17	M/C	(69 W)	TL	02 44 155	
	180/55 ZR 17	M/C	(73 W)	TL	02 44 152	
	180/60 ZR 17	M/C	(75 W)	TL	02 44 337	
	190/50 ZR 17	M/C	(73 W)	TL	02 44 154	
	190/55 ZR 17	M/C	(75 W)	TL	02 44 153	
	200/55 ZR 17	M/C	(78 W)	TL	02 44 327	

Recommended tire pressure:

For racing use: After at least an hour with electric blankets at 80 °C. The tire pressure should be measured and adjusted directly after the first short session.

Use without electric blankets:

ContiRaceAttack Comp.End.	Front	Rear
Cold	2.1 bar	1.8 bar

Use with electric blankets:

ContiRaceAttack Comp.End.	Front	Rear
Cold (measurement before electric blanket)	2.1 bar	160 - 1.6 bar 180 - 1.5 bar 190 - 1.4 bar
Hot (80 °C)	2.25 bar	1.6 - 1.8 bar

ContiRace **ATTACK** Rain

Competition rain tire (NHS).

- › Innovative pattern design to ensure optimal water clearance and high grip in extreme wet track conditions.
- › Controllable ride with high feedback characteristics providing excellent traction even under hard riding conditions due to a state-of-the-art racing rain compound.



Inch	Size	LI	SI	TL/TT	Article No.	Remarks
------	------	----	----	-------	-------------	---------

Front wheel

17"	120/70 R 17	NHS		TL	02 44 263	
-----	-------------	-----	--	----	-----------	--

Rear wheel

17"	180/55 R 17	NHS		TL	02 44 264	
	190/55 R 17	NHS		TL	02 44 107	

Recommended tire pressure:

Tip: Use the tire without the tire warmer so that the driver can get used to the increasing grip. It is, however, also possible to pre-heat the tire. **WARNING!** Tire pressure is dependent on the outdoor temperature.

Use without electric blankets:

ContiRaceAttack Rain	Front	Rear
Cold	2.1 - 2.3 bar	2.1 - 2.3 bar

Use with electric blankets:

ContiRaceAttack Rain	Front	Rear
Hot (40 °C)	max. 2.4 bar	max. 2.4 bar

ContiRoad **ATTACK 2 CR**

High performance classic racing tire.

- › Newly developed product available in all the most commonly used sizes and additionally in CR versions, with a racing compound that ensures better grip and a special carcass design for better feedback in racing events.
- › Exceptionally easy handling with ultra high grip and enhanced cornering stability.
- › Superb control and optimum feedback at the stability limits.
- › 0° steel belted design for enhanced stability and feedback when braking and accelerating out of curves. TractionSkin ensures extremely safe and short run-in time.
- › The tried and tested “MultiGrip” technology makes for extended mileage and maximum grip in extreme banking maneuvers.



Inch	Size	LI	SI	TL/TT	Article No.	Remarks
------	------	----	----	-------	-------------	---------

Front wheel

18"	100/90 R 18	M/C	56	V	TL	02 44 275	
	110/80 ZR 18	M/C	(58	W)	TL	02 44 199	

Rear wheel

18"	130/80 R 18	M/C	66	V	TL	02 44 276	
	130/80 R 18	M/C	66	V	TL	C 02 44 381	reinforced carcass
	150/65 R 18	M/C	69	H	TL	02 44 150	

Rim classifications

Front wheel

Size	Standard rim (ETRTO)
100/90 R 18 M/C 56V TL	2.50 x 18; 2.75 x 18
110/80 ZR 18 M/C (58W) TL	2.50 x 18; 2.75 x 18; 3.00 x 18

Rear wheel


Size	Standard rim (ETRTO)
130/80 R 18 M/C 66V TL	3.00 x 18; 3.50 x 18
130/80 R 18 M/C 66V TL	3.00 x 18; 3.50 x 18
150/65 R 18 M/C 69H TL	4.00 x 18; 4.25 x 18; 4.50 x 18

Recommended tire pressure:

ContiRoadAttack 2 CR	Front	Rear
Cold	100 - 2.1 - 2.2 bar 110 - 2.2 - 2.3 bar	130 - 2.0 - 2.2 bar 150 - 1.8 - 2.00 bar

When do I use which tire?

The tire temperature should be measured directly after the first turn and the tire pressure should be adjusted.



ContiTrack:

- › For road racing and race training.
- › Use with tire warmers recommended.
- › NHS - Not road legal.

ContiRaceAttack Comp. (soft / medium):

- › For race training and road racing.
- › Use with tire warmers recommended.
- › Road legal up to 270 km/h.

ContiRaceAttack Comp.End.:

- › For driving and race training in dry conditions.
- › Use without tire warmers possible.
- › Road legal.

ContiSportAttack 3:

- › Street and hypersport tire for initial experiences in driving and race training.
- › „The perfect choice in imperfect conditions on the race track!“ e.g. in mixed conditions and cool outdoor temperatures.
- › Tire pressure must be adjusted for the race track.
After use on the race track, don't forget to readjust the tire pressure! Note vehicle manufacturer tire pressure recommendations!

ContiSportAttack 3	Front	Rear
Race track (cold)	2.1 bar	1.8 bar
Road	2.5 bar	2.9 bar

ContiRaceAttack Rain:

- › For use on completely wet race tracks.

ContiRoadAttack 2 CR:

- › 18" racing tire for racing use on classic motorcycles.
- › Road legal.

Continental Reifen Deutschland GmbH

Business Unit Motorcycle Tires
Continentalstraße 3 - 5
34497 Korbach
Germany




Postbox 11 20
34481 Korbach
Germany

Phone: +49.511 9 38 - 01
Fax: +49.5631 58 - 22 40
E-Mail: service.motorrad@conti.de
Internet: www.conti-moto.com

Legal Notice:

Continental Reifen Deutschland GmbH accepts no liability in conjunction with this publication. To the extent permitted by law, any liability for any direct, indirect, incidental, consequential or punitive damages of any kind arising out of the use of the information included in this publication is hereby excluded.

Your local dealer.



Further information can be obtained from
www.conti-moto.com