

xtracycle

ALL IN ONE RACK INSTALLATION 2023

all in one

INSTALLING THE ALL IN ONE RACK

01

Clear off all accessories (if needed)



02

There are four rack locks, two wedding rings, and a tailpiece we will need to loosen

*front rack locks




03

*rear rack locks



04


*wedding rings



05


Remove the LT2 rack by pulling up on each leg until the rack is fully removed. Be aware there are three pieces of hardware per leg of the LT2 rack. With the front rack locks having the wedding rings.

*pay attention which leg each racklock comes off of, so that we can orient them correctly with the new All In One rack



06

Make sure to leave the rack sleeve aligned with the slot in the frame



07

08

Apply grease, if available, to inside rack ports



09

You'll need the 4 sets of O-rings and racklocks for the next step. Please discard the wedding rings, they are no longer needed




10

Insert one racklock and o-ring per leg, using the orientation from earlier, before inserting your new All In One rack into your bike frame. *each racklock should have the logos facing out towards the front or rear of the bike and the bolts facing the towards the outside of the bike



11

When inserting each leg, make sure each leg is bottomed out and fully inserted. Guide the O-ring to rest on top of the compression sleeve




12

Cover the O-ring and compression sleeve with the racklock, making sure to fully set the racklock.



13
You'll feel a little pop once fully seated.
Tighten each rack lock bolt to snug.



14
You're all done! Enjoy your new rack



