» SILENT **CEILING CASSETTE RANGEHOOD**
with automatic power-off // **CC-PARA2S, CC-PARA2W**

schweigen

Available in White or Stainless Steel

Modular
With the flexibility of this design, you can create your configurations of 2, 3 or 4 units – whatever best suits your home and kitchen environment*.

Stainless Steel or White Finish
Suitable for all kitchens in either stainless steel or white. It's both contemporary and durable.

Perimeter Aspiration
Uses an additional panel to create a venturi effect, which helps capture smoke, steam, grease and oil more effectively.

Dishwasher Safe Aluminium Filters
Durable materials that (when regularly maintained) can be run through your dishwasher.

Silent Motor System, up to 3200m³/hr
Enjoy cooking in peace without motor noise from your appliance.

Automatic Power-off
Select this function and the hood will switch off automatically after 15 minutes.

LED Lighting
Innovative wide-angle LED lighting system increases the aesthetic value of the appliance.

4 Extraction Speeds with Remote Control
From mild Western style cooking to traditional Eastern cuisine, select the speed that best suits your needs.

GOOD DESIGN AWARD® WINNER

REMOTE CONTROL | PA PERIMETER ASPIRATION | SILENT SYSTEM | FRESH ODOUR REMOVAL | DUCTING INCLUDED | LIFETIME★★★★★ FILTER WARRANTY | E ENERGY EFFICIENT | 5YR WARRANTY | 10YR MOTOR WARRANTY

www.schweigen.com.au

» SILENT **CEILING CASSETTE RANGEHOOD**
with automatic power-off // **CC-PARA2S, CC-PARA2W**

PRODUCT DETAILS

- stainless steel or white
- Perimeter Aspiration
- easy-remove, dishwasher safe aluminium filters
- silent Isodrive® motor
- powerful, silent operation
- automatic power-off
- LED illumination
- 4 extraction fan speeds with remote control
- 5 Year Warranty

- individual module dimensions: (W x D) 360 x 360 mm
- 1 x control module, + 1 x subordinates
- 2 x aluminium filters
- 10 amp power connection required

ISODRIVE POWER OPTIONS

- **SP** – single external motor,
  - 1600m³/h airflow,
  - 200mm SteelFlex™ ducting (6m),
  - install roof/wall

- **SE** - single external motor
  - 3200 m³/h airflow
  - 250mm SteelFlex™ ducting (4m)
  - 200mm SteelFlex™ ducting (2m)
  - SE accessory kit required
  - install roof/wall
- 10 Year Warranty

MODEL OPTIONS

CC-PARA2S, 2 modules (stainless steel)
CC-PARA2W, 2 modules (white)
*May require a bulkead for installation

Note: Please confirm the module configuration and motor power with your representative before ordering.

NOTE

The ducting vent can be mounted either to the side or top of the unit.

130 265
ø150
360 360
ø150
Cutout 340 x 340
310
220

Measurements in mm.