


- 1 Cut a mounting hole 35mm in diameter.
- 2 Fit Rubber Ring into groove on the mixer base.
- 3 Fit hoses through the mounting hole and place the mixer over the mounting hole.

4a SINK MIXER
Fit Plastic Spacer over Threaded Tail (supplied with Sink Mixers). Fit Rubber Gasket over Threaded Tail and Screw on Black Locknut to secure the mixer.

4b BASIN MIXER
Fit Rubber Gasket and Metal Disc over Threaded Tail and Screw on Black Locknut to secure the mixer.

5 Connect Red-Marking hose to hot water supply and Blue-Marking hose to cold water supply.

6 Turn on water supply and check for leaks.



recommended working pressure
150-500 KPa



maximum hot water temperature
75 degrees

NOTE:

- If the pressure exceeds or is likely to exceed 550kpa, an approved pressure limiting device must be installed.
 - Flush out all pipe work prior to installation.
 - If the water temperature exceeds 75°C, an approved tempering valve must be fitted.
 - Installation should comply with Australian standard AS3500.1 or relevant local authority requirements.
- Showers may not be suitable for use within:
- Gravity-fed water systems
 - Some instantaneous hot water systems; or

- Pressure supply less than 150kPa;

NOTE: The 500kPa maximum water supply pressure does not apply to fire service outlets.

Failure to comply with the above may void all warranties.

WARRANTY:

Please refer to the full warranty statement enclosed with the product before installing. Or visit www.phoenixtapware.com.au to download a copy.

MAINTENANCE AND CARE:

- Chrome plated surfaces should be cleaned with mild liquid detergent or soap and water;
- Do not use cream cleaners or citrus based cleaning products, as they are abrasive.
- Use of unsuitable cleaning agents may damage the surface. Any damage caused in this way will not be covered by warranty.

DISCLAIMER:

While we aim to ensure the specifications shown are correct at the time of printing, Phoenix Tapware reserves the right to make modifications without prior notice. Always use the physical product measurements for mark-ups and roughing-in as the line drawing shown may differ from the actual product over time.

*All measurements are shown in millimeters.