

Bowerbird X3

Specification:

Voltage input: AC220V 47-63Hz, PF:>0.95, Could customized DC24V

Rated Power:40W (32W@220V Full on)

Luminaire Efficiency: 41lm/W,3PCS 14W Full RGBAWUV 500mA Driving, 1220Lumens.

LED Color: R=625nm, G=525nm, B=450nm, offer multi-Color mixing, SDC<0.005.

Field Angle(10%): standard 51° (4280Cd on axis with LMTXL43HY)、37° optional.

Control signal:Meet E1.11 – 2004 USITT DMX512-A, could also be Constant Voltage PWM Dimming.

DMX Channels:LM-DMXA0 2.4GHz Wireless, compatible with PAD PEN, 6CH,7CH,8CH、10CH,11CH optional

Dimming Curve: 32 bit linear diming, PWM>600Hz, flicker free

Housing material: ADC12 Diecast, Matte black, customized other color and barndoor.

Safty: Class II, 3C*1mm² VDE cable for power, shield cable for signal, both daisy chain.

Operate temperature:-20~+45°C, Light board peak temperature 30°C

Cerficated:Product pass CE, Rohs Etc.Flame Rating V-1, Protect Rated IP65.

Weight: 1KG, with 2mm thick double bracket.

Size: 103*181*207mm

Features:

Patent apearance design,original from Bowerbird, share beauty of the nature.

Small body but big wisdom,almost 1000 colorful Lumens output, variavle light distribution.

Good color mixing,SDC<0.005,stable Color among all fixtures.

Whole lamp body fully used as heat sink, support heatsink 30W at 30°C rise,with NTC

LED display could show DMX signal situation, 2minutes no operation no display

RF-ID 7 independent DMX wireless Univers to be used.

5 dimming curve including Dim4 theatre standard strict smooth dimming

With waterproof air vent to balance pressure. get rid of mosuisture on glass innerface.



RED

RED+WHITE

GREEN+WHITE

BIUE+WHITE

DMX

IP65

DMX

5dB

Medium Spot light

Bowerbird X3

