

Especificaciones

Cámara

Sensor	CMOS de 1/1,7 pulgadas Píxeles efectivos: 48 MP
Lente	FOV: Equivalente a 155° Distancia focal: 12,7 mm Distancia focal: 2,34 mm Apertura: f/2,8 Modo de enfoque: FF Rango de enfoque: 0,6 m a ∞
Rango ISO	100-6400 (Automático) 100-25600 (Manual)
Velocidad de obturación	Vídeo: 1/8000-1/50 s Foto: 1/8000-1/50 s
Modo de fotografía fija	Un solo tiro
Tamaño máximo de imagen	4000×3000
Formato de foto	jpeg
Resolución de video	Con DJI Goggles 2: 4K@30/50/60fps 2.7K@30/50/60/100/120fps 1080p@30/50/60/100/120fps Con DJI FPV Goggles V2: 4K@30/50/60fps 2.7K @30/50/60/100/120fps 1080p@30/50/60/100/120fps
Formato de video	MP4
Tasa de bits de video máxima	150Mbps
Modo de color	Estándar D-Cinelike
DIA	Compatible con RockSteady y HorizonSteady Se puede desactivar
Corrección de distorsión	Admite el modo normal, el modo ancho y el modo ultra ancho

Sistema de archivos compatible exFAT (recomendado)
FAT32

cardán

Rango Mecánico Inclinación: -95° a 75°

Rango Controlable Inclinación: -80° a +65°

Estabilización Eje único (inclinación)

Velocidad máxima de control 60°/segundo

Angular Vibration Range $\pm 0.01^\circ$

Electronic Roll Axis Real-time screen correction is unavailable during recording, but can be applied to the footage recorded on the

Aircraft

Model QF2W4K

Takeoff Weight Approx. 410 g

Dimensions (L×W×H) 180×180×80 mm

Diagonal Distance 120 mm

Max Ascent Speed 6 m/s (Normal Mode, Sport Mode)

Max Descent Speed 6 m/s (Normal Mode, Sport Mode)

Max Speed ^[1] 8 m/s (Normal Mode)
14 m/s (Sport Mode)
27 m/s (Manual Mode)

Maximum Takeoff Altitude 5000 m

Max Hover Time Approx. 18 mins ^[2]

Max Flight Distance 11.6 km

Max Wind Speed Resistance 10.7 m/s (Level 5)

Operating Temperature Range -10° to 40° C (14° to 104° F)

Transmission Power (EIRP) FCC: < 33 dBm
CE: < 14 dBm
SRRC: < 30 dBm

Antennas Dual Antennas, 2T2R

GNSS GPS + Galileo + BeiDou

Hovering Accuracy Range Vertical:
 ± 0.1 m (with Vision Positioning)
 ± 0.5 m (with GNSS Positioning)

Horizontal:
±0.3 m (with Vision Positioning)
±1.5 m (with GNSS Positioning)

Supported SD Cards microSD (up to 256 GB)

Recommended microSD Cards SanDisk Extreme U3 V30 A1 32GB microSDXC
SanDisk Extreme Pro U3 V30 A1 32GB microSDXC
Kingston Canvas Go!Plus U3 V30 A2 64GB microSDXC
Kingston Canvas React Plus U3 V90 A1 64GB microSDXC
Kingston Canvas React Plus U3 V90 A1 128GB microSDXC
Kingston Canvas React Plus U3 V90 A1 256GB microSDXC
Samsung PRO Plus U3 V30 A2 256GB microSDXC

Internal Storage 20 GB

Sensing System

Downward (Binocular Vision and ToF) ^[3] ToF Effective Measurement Height: 10 m
Precise Hovering Range: 0.5-10 m
Vision Sensor Hovering Range: 0.5-20 m

Operating Environment Diffuse reflective surfaces with a clear pattern > 20% (such as walls, trees, or people)
Adequate lighting (lux > 15, normal indoor lighting conditions)

Intelligent Flight Battery

Battery Capacity 2420 mAh

Voltage 14.76 V

Charging Voltage Limit 17 V

Type Li-ion

Chemical System LiNiMnCoO₂

Energy 35.71 Wh@0.5C

Discharge Rate Typical: 7C

Weight Approx. 162 g

Charging Temperature Range 5° to 40° C (41° to 104° F)

Video Transmission

Communication Frequency 2.400-2.4835 GHz (RX only)
5.725-5.850 GHz (RX and TX) ^[4]

Communication Bandwidth Max 40 MHz

Live View Quality and Latency ^[5] With DJI FPV Goggles V2:
810p/120fps Video Transmission Quality: The video transmission latency is lower than 28 ms.
810p/60fps Video Transmission Quality: The video transmission latency is lower than 40 ms.

With DJI Goggles 2:

1080p/100fps Video Transmission Quality: The video transmission latency is as low as 30 ms.

1080p/60fps Video Transmission Quality: The video transmission latency is as low as 40 ms.

Max Video Transmission Bitrate ^[6]	50 Mbps
Max Video Transmission Range ^[7]	10 km (FCC), 2 km (CE), 6 km (SRRC)
Audio Transmission	N/A

DJI Goggles 2

Model	RCDS18
Weight	Approx. 290 g (headband included)
Dimensions (L×W×H)	With antennas folded: 167.40×103.90×81.31 mm With antennas unfolded: 196.69×103.90×104.61 mm
Screen Size (single screen)	0.49-inch
Resolution (single screen)	1920×1080
Refresh Rate	Up to 100 Hz
Interpupillary Distance Range	56-72 mm
Diopter Adjustment Range	-8.0 D to +2.0 D
FOV (single screen)	51°
Communication Frequency	2.400-2.4835 GHz 5.725-5.850 GHz ^[4]
Transmission Power (EIRP)	2.4 GHz: < 30 dBm (FCC), < 20 dBm (CE/SRRC/KC) 5.8 GHz ^[4] : < 30 dBm (FCC), < 23 dBm (SRRC), < 14 dBm (CE/KC)
Wi-Fi Protocol	Wi-Fi 802.11b/a/g/n/ac
Wi-Fi Communication Frequency	2.400-2.4835 GHz 5.150-5.250 GHz (indoor use only) ^[8] 5.725-5.850 GHz ^[4]
Wi-Fi Transmission Power (EIRP)	2.4 GHz: < 20 dBm (FCC/CE/SRRC/KC) 5.1 GHz ^[8] : < 20 dBm (FCC/CE/KC) 5.8 GHz ^[4] : < 20 dBm (FCC/SRRC/KC), < 14 dBm (CE)
Bluetooth Protocol	Bluetooth 5.2
Bluetooth Communication Frequency	2.400-2.4835 GHz
Bluetooth Transmission Power (EIRP)	< 8 dBm
Max Video Transmission Bitrate ^[6]	50 Mbps

Video Recording Format	MOV
Supported Video and Audio Playback Formats	MP4 and MOV (video coding formats: H.264 and H.265; audio format: ACC, PCM)
Wi-Fi Wireless Streaming	Supports DLNA Protocol
Operating Temperature Range	-10° to 40° C (14° to 104° F)
Power Input	DJI Goggles 2 Battery
Supported SD Cards	microSD (up to 256 GB)

DJI Goggles 2 Battery

Capacity	1800 mAh
Voltage	7-9 V (1.5 A)
Type	Li-ion
Chemical System	LiNiMnCoO ₂
Energy	18 Wh
Charging Temperature Range	0° to 45° C (32° to 113° F)
Max Charging Power	12.6 W (5 V/2 A, 9 V/1.4 A)
Weight	Approx. 122 g
Dimensions (L×W×H)	73.04×40.96×26 mm
Operating Time	Approx. 2 hours

DJI FPV Goggles V2

Model	FGDB28
Weight	Approx. 420 g (headband and antennas included)
Supported Video and Audio Playback Formats	MP4, MOV, MKV (video coding format: H.264; audio formats: AAC-LC, AAC-HE, AC-3, MP3)
Operating Temperature Range	0° to 40° C (32° to 104° F)
Video Recording Format	MOV (video coding format: H.264)
FOV	30° to 54°, adjustable Image Size: 50% to 100%
Communication Frequency	2.400-2.4835 GHz 5.725-5.850 GHz ^[4]
Max Video Transmission Bitrate ^[6]	50 Mbps

Dimensions (L×W×H)	Without antennas: 184×122×110 mm With antennas: 202×126×110 mm
Transmission Power (EIRP)	2.400-2.4835 GHz FCC: ≤ 28.5 dBm CE: ≤ 20 dBm SRRC: ≤ 20 dBm 5.725-5.850 GHz ^[4] FCC: ≤ 31.5 dBm CE: ≤ 14 dBm SRRC: ≤ 19 dBm
Screen Size (single screen)	2-inch
Power Input	Dedicated DJI Goggles batteries
Supported SD Cards	microSD (up to 256 GB)
Communication Bandwidth	Max 40 MHz
Interpupillary Distance Range	58-70 mm
Refresh Rate	144 Hz
Screen Resolution	1440×810

DJI FPV Goggles V2 Battery

Weight	Approx. 119 g
Dimensions (L×W×H)	73.04×40.96×26 mm
Capacity	1800 mAh
Voltage	Max 9 V
Chemical System	LiNiMnCoO ₂
Type	Li-Po 2S
Energy	18 Wh
Charging Temperature Range	0° to 45° C (32° to 113° F)
Max Charging Power	10 W
Operating Time	Approx. 110 mins

DJI Motion Controller

Model	FC7BMC
Weight	Approx. 167 g

Communication Frequency	2.400-2.4835 GHz 5.725-5.850 GHz ^[4]
Transmission Power (EIRP)	2.4 GHz: ≤ 28.5 dBm (FCC), ≤ 20 dBm (CE/SRRC) 5.8 GHz ^[4] : ≤ 31.5 dBm (FCC), ≤ 19 dBm (SRRC), ≤ 14 dBm (CE)
Operating Temperature Range	-10° to 40° C (14° to 104° F)
Operating Time	Approx. 5 hours

DJI FPV Remote Controller 2

Model	FC7BGC
Weight	Approx. 346 g
Communication Frequency	2.400-2.4835 GHz 5.725-5.850 GHz ^[4]
Transmission Power (EIRP)	2.4 GHz: ≤ 28.5 dBm (FCC), ≤ 20 dBm (CE/SRRC) 5.8 GHz ^[4] : ≤ 31.5 dBm (FCC), ≤ 19 dBm (SRRC), ≤ 14 dBm (CE)
Dimensions (L×W×H)	190×140×51 mm
Operating Time	Approx. 9 hours
Operating Temperature Range	-10° to 40° C (14° to 104° F)
Charging Time	2.5 hours

Other

Footnotes	<ol style="list-style-type: none"> The max flight speed is subject to dynamic local restrictions. Please abide by local laws and regulations when flying. Tested when hovering in an environment without wind or interference. DJI Avata only supports downward obstacle sensing when used with DJI FPV Remote Controller 2, or DJI Mot Controller in N Mode and S Mode. The 5.8 GHz frequency band is currently banned in certain countries or regions. For details, please refer to local laws and regulations. Tested in an outdoor open environment without interference. The video transmission latency data varies with different models. Tested in an outdoor open environment without interference. The video transmission bitrate varies with different environments. FCC compliant and tested in an outdoor open environment without interference. Data is tested under different standards in an outdoor open environment without interference. Only to serve as a reference for the max one-way communication distance without considering RTH. Please pay attention to the RTH prompts during actual flight. The max one-way communication distance of DJI Avata in countries/regions of different standards: FCC: United States, Australia, Canada, Hong Kong, Taiwan, Chile, Colombia, Puerto Rico, and other regions. SRRC: Mainland China. CE: UK, France, Germany, Portugal, Spain, Switzerland, Macau, New Zealand, UAE, and other regions. The 5.1 GHz frequency band is currently banned in China and Thailand. For details, please refer to local laws and regulations.
-----------	---

Product Categories	Where to Buy	Fly Safe	Explore	Community
Consumer	DJI Online Store	Fly Safe	Newsroom	SkyPixel
Professional	Flagship Stores	DJI Flying Tips	Events	DJI Forum

Enterprise	DJI-Operated Stores	Support	Buying Guides	Developer
Components	Retail Stores	Product Support	STEAM Education	Subscribe
Service Plans	Enterprise Retailers	Service Request and Inquiry	Mini Drones	Get the latest news from
DJI Care Refresh	Agricultural Drone Dealer	Help Center	DJI Camera Drones	<input type="text" value="Your email address"/>
DJI Care Refresh +	Pro Retailers	After-Sales Service Policies		
DJI Care Pro	DJI Store App	Download Center		
Osmo Shield	Cooperation	Security and Privacy		
DJI Care Enterprise	Become a Dealer			
DJI Maintenance Program	Apply For Authorized Store			

