

ROUND 45 D 60

PATENTED

WALK BEHIND SCRUBBER DRYERS ROUND 45 - WITH TRACTION

Round 45 D 60 TOUCH is the renowned Ghibli & Wirbel's scrubber dryer. The innovative and functional design guarantees the right ergonomics and comfort in the daily activities. The technical features and the high level innovations – 45 liters tank capacity, three hours running time, the control panel with display, the double brush pressure, the “silent mode”-function, the new chemical mixing system – make Round 45 something unique in its market segment, ideal for effective cleaning results in every kind of floor/environment. The wide cleaning path (2 x 12” brushes) and the adjustable speed (up to 5 km/h) allow a productivity of 3050 m²/h. ROUND 45 is now available with two important upgrades: • thanks to the new sensor TOUCH SYSTEM, Ghibli & Wirbel patented, ROUND 45 can be moved and controlled only using a thumb: intuitive, user friendly and reliable. • ECO SYSTEM, the new program on the control panel, which optimizes consumptions, making ROUND 45 eco-friendly. Environmental care and good performance at the same time.




Control panel with display



Password for reliability and ease of use



Touch System



“Built in” solution tank filter



Debris tray + vacuum filter



Adjustable and compact squeegee



Eco System



Chemical mixing system

PRODUCT IDENTIFICATION

| TYPE | REF. NO. | PIECES/PALLET |
|-----------------------------|------------|---------------|
| ROUND 45 D 60 TOUCH | 10.4223.00 | 1 |
| ROUND 45 D 60 BC CHEM TOUCH | 17.4223.00 | 1 |

TECHNICAL DATA

| FEATURES | | |
|--|---|-------------------|
| Cleaning width | mm | 600 |
| Squeegee width | mm | 750 |
| Productivity (theoretical - practical) | m ² /h | 3050 - 1830 |
| Power supply | | Battery 24V |
| Installed power | W | 1190 |
| Advancement | | with traction |
| IP code | | IPX3 |
| BATTERIES | | |
| Type | Gel battery set (2 pcs) 12V 105Ah (***) | |
| Running time | h - min | 2 h and 30 min |
| Battery compartment dimensions x No | mm x No | 340x340x285 X 1 |
| BRUSHES | | |
| Pad diameter x No | mm - inch x No | 310 - 12" x 2 |
| Motor rating x No | W x No | 450 x 1 |
| Motor speed | rpm | 200 |
| Down pressure - Contact pressure | Kg - g/cm ² | 27 - 27 ; 32 - 32 |
| TRACTION | | |
| Motor rating | W | 180 |
| Driving speed | Km/h | 5 |
| Hill climbing ability (full load) | % | 2 |
| VACUUM | | |
| Motor rating | W | 550 |
| Vacuum | mbar - mmH ₂ O | 1250 |
| Airflow rating | l/s | 30 |
| Noise level | dB(A) | 63/57 * |

| TANK | | |
|-------------------------------|----|---------------|
| Type | | Double tank |
| Cleaning solution tank | l | 45 |
| Recovery tank | l | 47 |
| Weight (empty/with batteries) | Kg | 116 / 196 |
| Dimensions | mm | 1125x670x1040 |

STANDARD ACCESSORIES

| TYPE | REF. NO. |
|---|------------|
| Solution tank filling hose | 30.0024.00 |
| 12" Polypropylene brush ø 0.7 (**) | 40.0001.00 |
| On board charger 24 V 9 A (***) | 22.0623.00 |
| Gel battery set (2 pcs) 12V 105Ah (***) | 18.0001.00 |
| Detachable brush deck splash guard (without bristles) | 24.0266.00 |
| Brush deck splash guard bristles | 40.4007.00 |
| Set front+rear natural rubber squeegee blades | 96.0091.01 |
| Chemical mixing system (***) | 96.0048.00 |
| Extra weight for squeegee (1x700 g (**)(****)) | 96.0171.00 |

OPTIONAL ACCESSORIES

| TYPE | REF. NO. |
|---|------------|
| 12" Polypropylene brush ø 0.9 | 40.0101.00 |
| 12" Polypropylene brush ø 1.2 | 40.0301.00 |
| 12" Tynex brush grit ø 1.2 grit 80 | 40.0201.00 |
| Pad holder 290 mm (for 12" pad) | 40.1001.00 |
| Set front + rear polyurethane squeegee blades | 96.0055.00 |

(*) Silent mode function

(**) 2 on standard equipment

(***) For BC CHEM version

(****) You can use maximum two weights until you reach 1400 g of total additional weight