



NIGHTOPTIX™

## Lightweight Thermal Goggles SCOTOPIA-G

SCOTOPIA-G is the thermal imaging goggle system designed for all categories of customers. It has a full-size ergonomic and tactile keypad, hard-anodized aluminum body, and superb optics. Its unbeatable real-life performance is complemented by best-in-class battery life. Features include fully waterproof design, precisely machined body and outstanding build quality. SCOTOPIA-G is perfect for 24/7 observation and detection for any purpose (wildlife, perimeter security, outdoor activities).



### KEY FEATURES

- ◆ Auto-NUC FPA: 384x288 and 640x480  
50Hz Refresh Rate
- ◆ Moose Detection Range: up to 830m  
Optional Built-In Video Recorder
- ◆ Up to 8 Hours Battery Life  
ITAR-Free System: Available for Export

### MAIN APPLICATIONS

- ◆ Perimeter Security  
Law Enforcement
- ◆ Wildlife Observation  
Surveillance
- ◆ Border Patrol  
Reconnaissance



NIGHTOPTIX™

## Lightweight Thermal Goggles SCOTOPIA-G

	G38	G64
Optical Magnification	1.5X	1X
Objective Lens	25mm, f/1.0	
Field of View	14.9°x11.2°	24.5°x18.5°
Focusing Range	0.25m .. Infinity	
FPA Resolution and Pitch	384x288, 17µm	640x480, 17µ
FPA Type	Uncooled, a-Si, Shutterless, Silent, Auto-NUC (Uninterrupted Operation)	
FPA Sensitivity	<60mK	
FPA Refresh Rate	50Hz	
Digital Zoom	2X and 4X	
Display	Dual-AMOLED, Colour, 800x600	
Imaging Modes	1 Monochrome + 8 Colour	
Digital Video Recorder	Optional: Built-In with microSD Card or External with SD Card	
Detection Moose (1.7x0.5m)	Up to 830m	
Detection Vehicle (2.3x2.3m)	Up to 1130m	
Accepted Batteries	4pcs AA, any kind: Lithium, Rechargeable, Alkaline, etc.	
Battery Life	Up to 8 Hours	
Environmental Protection	IP66, IP67 or Better	
Dimensions	112x138x55mm	
Weight	455 grams	
Operating Temperature	-40°C .. +50°C	
Warranty	5 Years, Limited	
Export	**Export Permit required. Nightoptix can assist in obtaining the required permit	



NIGHTOPTIX™

## Lightweight Thermal Goggles SCOTOPIA-G

### DISTINCTIVE FEATURES

- High-Resolution Uncooled FPAs: 384x288 or 640x480  
Fast Refresh Rate: 50Hz
- Quality and “Fast” Low-F-Number Germanium Lenses  
Ultra-Low Power Consumption
- Optional Built-In Video Recorder  
Can be Mounted on Head Gears and Helmet Mounts
- Stadiametric Rangefinder (SRF)  
Stow Safety Feature (SSF)
- Completely Silent System Operation  
Interchangeable Optics
- Precision-Machined Rugged Aluminum Body  
Video-out for External Display and Recording
- High-Resolution Colour AMOLED Displays 800x600  
24-hour Operation
- Manual and Automatic FPA Sensitivity Adjustment  
Manual Display Brightness Adjustment
- Black Hot / White Hot Polarity Control  
Universal Power Solution: AA, USB-powered, etc.
- Complete Dust- and Waterproof Protection





NIGHTOPTIX™

## Lightweight Thermal Goggles SCOTOPIA-G

### STANDARD ACCESSORIES: WHAT'S IN THE BOX



Main Unit



Neck Strap



USB Power  
Cable



Video-Out  
Cable



Quick-Swap  
Battery Holders



Soft Carrying  
Pouch



Hard Waterproof  
Case


### OPTIONAL ACCESSORIES



Standard Head Gear PHG-7 (non-flip-up. Compatible with PVS-style bracket only, comes with 3 brow pads, 1-way adjustment)



Flip-up Head Gear HG-714M (Compatible with PVS-style bracket only, 2-way adjustment)



Advanced Flip-Up Helmet Mount HM-714XM-C (Complete kit with straps. Available in both PVS-style and Dove-Tail style configurations, 4-way adjustment)



Advanced Flip-Up Helmet Mount HM-714XM-SR ("Shroud-Ready" version compatible with ops-core style helmets. Available in both PVS-style and Dove-Tail style configurations, 4-way adjustment)



NIGHTOPTIX™

## Lightweight Thermal Goggles SCOTOPIA-G

### OPTIONAL ACCESSORIES (CONTINUED)



Low-Profile Flip-Up Helmet Mount HM-714LP-SR (“Shroud-Ready” version compatible with ops-core style helmets. Available in both PVS-style and Dove-Tail style configurations, 3-way adjustment)



Advanced Flip-Up Helmet Mount HM-714LP-C (Complete kit with straps. Available in both PVS-style and Dove-Tail style configurations, 3-way adjustment)



Built-In Video Recorder (comes with 32GB microSD card and SD adapter)



Interchange Lens GLI-50 (50mm f/1.0) with long-range adapter



External Video Recorder with SD Card



Wired Remote Control with Video-Out



Video-Out to USB Adapter



Portable Head-Mounted Display HMD-800/HMD-800-MOD (streams thermal video directly from the device)