



a.

High-end Residential Series



Product Introduction

Yeelight Pro whole-house smart lighting lineup features four major series: P, S, E and M, covering professional-grade smart lighting products, all-inclusive smart control, interactive products, as well as prime fittings and accessories. To offer you an inclusive and professional smart lighting solution, we go above and beyond!

Series P refers to the ultra-high-end products in Yeelight Pro whole-house smart lighting, setting the bar in the industry. Empowered by industry-disruptive technology and brand-new smart lighting concept, Series P offers SkyLight series, surface Mounted magnetic tracks, sensor series, etc. An ultimate lighting experience with Yeelight is set and ready!

Series E is a professional and cost-effective selection in Yeelight Pro family. Its downlight features professional performance that far exceeds standard-grade lighting products, such as deep anti-glare and dimming precision of one thousandth, providing you with a prime lighting experience at a desirable cost.

Series S the lighting without the main lamp, is the flagship product in Yeelight Pro whole-house smart lighting. With dimming precision of one ten thousandth, deep anti-glare, high CRI, low power consumption and other leading advantages, Series S supports smart light sources, smart interaction, and smart control. It is designed for spatial villa, satisfying the needs of high-end users.

Series M is a standard product line in Yeelight Pro whole-house smart lighting. It covers anti-glare downlight, superb ceiling lamp and ambient lights, providing young people who pursue a smart lifestyle with a trustworthy journey.



Magnetic Tracks

P20 Surface Mounted Magnetic Track Lights

- | Dimming precision of one ten thousandth
- | Track as thin as 5 mm
- | Surface Mounted light for simple installation
- | One gang one way switch
- | A diverse selection of luminaires



P20 Surface Mounted Magnetic Track Lights

Surface Mounted Magnetic Profile Light

30cm

Product Model YLP104



Product Size

Beam Angle

Power

305*31*12mm

\

6W

Color Temperature

CRI

2700-6000K

Ra≥90

P20 Surface Mounted Magnetic Track Lights

Surface Mounted Magnetic Profile Light

60cm

Product Model YLP105



Product Size

Beam Angle

Power

605*31*12mm

\

12W

Color Temperature

CRI

2700-6000K

Ra≥90

P20 Surface Mounted Magnetic Track Lights

Surface Mounted Magnetic Grille Light

Product Model YLP106

5 heads



Product Size

Beam Angle

Power

Color Temperature

CRI

137*33*48mm

/

6W

2700-6000K

Ra≥90

P20 Surface Mounted Magnetic Track Lights

Surface Mounted Magnetic Grille Light

Product Model YLP107

10 heads



Product Size

Beam Angle

Power

Color Temperature

CRI

270*32*48mm

/

12W

2700-6000K

Ra≥90

P20 Surface Mounted Magnetic Track Lights

Surface Mounted Magnetic Folding Spotlight

5 heads

Product Model YLP108



Product Size	Beam Angle	Power	Color Temperature	CRI
135*32*87mm	/	13.5W	2700-6000K	Ra≥90

P20 Surface Mounted Magnetic Track Lights

Surface Mounted Magnetic Folding Spotlight

Product Model YLP109



Product Size	Beam Angle	Power	Color Temperature	CRI
118*42*100mm	15°	7W	2700-6000K	Ra≥90
118*42*100mm	24°	7W	2700-6000K	Ra≥90

P20 Surface Mounted Magnetic Track Lights

Suspended Power

120W

Product Model YLP103



Product Size

Beam Angle

Power

Color Temperature

CRI

216*31*92mm

/

120W

/

/

High-end Residential

S21 Recessed Downlight

- Dimming precision of one ten thousandth
- Low standby power consumption < 0.1W
- Module-based design
- Deep anti-glare UGR < 2
- Die-cast aluminum for quick cool-off
- Dimmable and tunable COB



S21 Recessed Downlight

Narrow Edge Round

Product Model YLP014+YLP015
Product Size $\Phi 83 \times 80$ mm



Opening Size

Beam Angle

Power




$\Phi 75$ mm	15°	10W
$\Phi 75$ mm	24°	10W
$\Phi 75$ mm	36°	10W

Color Temperature

Luminous Flux

CRI


2700-6000K	600lm	Ra > 90
2700-6000K	600lm	Ra > 90
2700-6000K	600lm	Ra > 90






High-end Residential S21 Recessed Downlight

Narrow Edge, Square

Product Model YLP009
Product Size $\phi 83 \times 109 \text{mm}$



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
75*75mm	15°	10W	2700-6000K	600lm	Ra > 90
75*75mm	24°	10W	2700-6000K	600lm	Ra > 90
75*75mm	36°	10W	2700-6000K	600lm	Ra > 90






High-end Residential S21 Recessed Downlight

No Edge, Round

Product Model YLP014+YLP016+YLP030
Product Size $\phi 83 \times 80 \text{mm}$



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
$\Phi 75 \text{mm}$	15°	10W	2700-6000K	600lm	Ra > 90
$\Phi 75 \text{mm}$	24°	10W	2700-6000K	600lm	Ra > 90
$\Phi 75 \text{mm}$	36°	10W	2700-6000K	600lm	Ra > 90



High-end Residential

S20 Recessed Downlight

- |Dimming precision of one ten thousandth
- |Die-cast aluminum for quick cool-off
- |Low standby power consumption <0.1W
- |Dimmable and tunable COB
- |Deep anti-glare UGR <2



S20 Recessed Downlight

Narrow Edge, Square

Product Model YLP009+YLP010
Product Size 83*83*108mm



Opening Size

Beam Angle

Power

75*75mm

15°

10W

75*75mm

24°

10W

75*75mm

36°

10W

Color Temperature

Luminous Flux

CRI

2800-6000K

600lm

Ra > 90

2800-6000K




600lm

Ra > 90

2800-6000K

600lm

Ra > 90



High-end Residential 520 Recessed Downlight




Round 3"

Product Model YLP014+YLP017

Product Size 83*83*80mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
Φ75mm	15°	10W	2800-6000K	600lm	Ra > 90
Φ75mm	24°	10W	2800-6000K	600lm	Ra > 90
Φ75mm	36°	10W	2800-6000K	600lm	Ra > 90



High-end Residential 520 Recessed Downlight




Round 2.5"

Product Model YLP010

Product Size φ76*69mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
Φ65mm	15°	10W	2800-6000K	500lm	Ra > 90
Φ65mm	24°	10W	2800-6000K	500lm	Ra > 90
Φ65mm	36°	10W	2800-6000K	500lm	Ra > 90



High-end Residential

E20 Recessed Downlight

- | Dimming precision of one ten thousandth
- | Dimmable and tunable COB
- | Die-cast aluminum for quick cool-off
- | Luminous efficiency > 56lm/w
- | 65mm ultra-thin anti-glare design
- | Spotlight UGR<9



E20 Recessed Downlight

Round Downlight

Product Model YLP074
Product size $\phi 84 \times 55 \text{mm}$



Opening Size

Beam Angle

Power

 $\phi 75 \text{mm}$

80°

8W

Color Temperature


Luminous Flux

CRI

2700-6000K

400lm

Ra > 90






High-end Residential E20 Recessed Downlight

Round Spotlight 3"

Product Model YLP053
Product Size $\Phi 84 \times 63 \text{mm}$



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
$\Phi 75 \text{mm}$	15°	8W	2700-6000K	450lm	Ra > 90
$\Phi 75 \text{mm}$	24°	8W	2700-6000K	450lm	Ra > 90
$\Phi 75 \text{mm}$	36°	8W	2700-6000K	450lm	Ra > 90



High-end Residential



M20 Recessed Downlight

- | Stepless Dimming
- | Dimmable and tunable COB
- | 65mm ultra-thin anti-glare design
- | Built-in power supply

M20 Recessed Downlight

Cylinder Light 3"

Product Model: YLP074
Product size: $\phi 84 \times 55$ mm




Opening Size	Beam Angle	Power
--------------	------------	-------

$\phi 75$ mm	70°	5W
--------------	-----	----

Color Temperature	Luminous Flux	CRI
-------------------	---------------	-----

2700-6000K	350lm	Ra > 80
------------	-------	---------



High-end Residential M20 Recessed Downlight

Cylinder Light 3.5"

Product Model ylp032
Product Size $\Phi 113 \times 81.5 \text{mm}$



Opening Size

$\Phi 95 \text{mm}$

Beam Angle

70°

Power

8W

Color Temperature


2700-6000K

Luminous Flux

500lm

CRI

Ra > 80



High-end Residential M20 Recessed Spotlight

Round Tunable White

Product Model YLP034
Product Size $\Phi 85 \times 73.5 \text{mm}$



Opening Size

$\Phi 75 \text{mm}$

Beam Angle

24°

Power

5W

Color Temperature


2700-6000K

Luminous Flux

300lm

CRI

Ra > 80



High-end Residential

S21 Double Exposed Downlights

- | Dimming precision of one ten thousandth
- | Large luminous flux of 1000lm
- | Standby power consumption < 0.1W
- | Dimmable and tunable COB
- | Built-in power supply | Exposed install sets no limit
- | Die-cast aluminum for quick cool-off



S21 Double Exposed Downlights

Dual Light

Black | White

Product Model: YLP036



Opening Size

146*76*95mm

146*76*95mm

Beam Angle

30°

45°

Power

16W

16W

Color Temperature

2800-6000K

2800-6000K

Luminous Flux



1000lm

1000lm

CRI

Ra > 90

Ra > 90



High-end Residential



S21 Low Voltage Light Strip

- | No perceptible luminance difference in 20 meters
- | Minimal color distortion
- | Dimming precision of one ten thousandth
- | Dual color COB free from visible particulates

S21 Smart Light Strip

Low Voltage Light Strip



Product Model	Product Name	Power
YLP081	5m-COB	6.5W/m
YLP041	5m-TPE	6.5W/m
YLP080	10m-TPE	6.5W/m
YLP042	Power supply for low-voltage light strip	120W

Color Temperature	Luminous Flux	Specifications
2700-6000K	600lm/m	5000*10*1.7mm
2700-6000K	600lm/m	5000*12*6mm
2700-6000K	600lm/m	10000*12*6mm
/	/	330*45*35mm

S20 Smart Light Strip

High Voltage Light Strip



Product Model	Power	Color	Temperature
YLP003 (Light Strip)	4W/m		2700-6500K
YLP003 ((Adapter)	120W		Dual Output

Luminous Flux	Specifications
500lm/m	5000*12*7mm
/	135*55*35mm

High-end Residential

S20 Smart Bulb

Product Model YLP004

**Product Size**

Φ60*110mm

Power

6W

Color Temperature

2700-6500K

Luminous Flux

500lm

Screw Size

E27

Stepless dimming RA90 CRI
2700-6500K Stepless dimming E27 Screw

High-end Residential

M20 Smart Bulb

Product Model YLP040

**Product Size**

Φ43*112mm

Power

4W

Color Temperature

2700-6500K

Luminous Flux

450lm

Screw Size

E27

Narrow as φ43mm
Stepless dimming
Ra90 CRI
Suitable for mini lamps

Magnetic Track

S21 Magnetic Track Lighting

- | Dimming precision of one ten thousandth
- | Flexible control of each light
- | Convenient magnetic plug
- | Exposed and embedded are optional
- | An array of designs at your disposal



S21 Magnetic Track Lighting

Magnetic Floodlight

30cm

Product Model: YLP054



Product Size	Beam Angle	Power
307*32*59mm	\	5W

Color Temperature	Luminous Flux	CRI
2700-6000K	250lm	Ra > 90

Magnetic Track

Magnetic Floodlight

Product Model: YLP071

60cm



Product Size

Beam Angle

Power

Color Temperature

Luminous Flux

CRI

607*32*59.66mm

/

10W

2700-6000K

500lm

Ra > 90

Magnetic Track

Magnetic Grille Lamp
5-Head

Product Model: YLP055



Product Size

Beam Angle

Power

Color Temperature

Luminous Flux

CRI

140*32*50.78mm


32°

5W

2700-6000K

270lm

Ra > 90




Magnetic Track

Magnetic Grille Lamp

Product Model YLP056



Product Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
272*32*58mm	32°	10W	2700-6000K	540lm	Ra > 90




Magnetic Track

Magnetic Folding Spotlight

Product Model YLP057



Product Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
138*35*155mm	32°	10W	2700-6000K	400lm	Ra > 90



Magnetic Track

Magnetic Track
Spotlight

Product Model YLP05B



Product Size

Beam Angle

Power

Color Temperature

Luminous Flux

CRI

152*48*126.5mm

15°

10W

2700-6000K

600lm

Ra > 90

152*48*126.5mm



24°

10W

2700-6000K

600lm

Ra > 90



Magnetic Track

Magnetic Pendant
Light30cm

Product Model YLP059



Product Size

Beam Angle

Power

Color Temperature

Luminous Flux

CRI

131*55*633.7mm


24°

10W

2700-6000K

500lm

Ra > 90



Magnetic Track

S21 Track Accessories



Magnetic Track Embedded
Product Model YLP078
1m/2m, mounting holes included



Vertical Angle L-Shaped Magnetic Corner Track Embedded
Product Model YLP076
Vertical fix, breakover device included



Horizontal L-Shaped Magnetic Corner Track Embedded
Product Model YLP075
Horizontal fix, breakover device included



Magnetic Power Input Connector
Product Model YLP067
External DC power supply



Magnetic Track Fixing
Product Model YLP068
Track splicing and fixing



Magnetic Track Exposed
Product Model YLP063
1m, mounting holes included



Vertical Angle L-Shaped Magnetic Corner Track Exposed
Product Model YLP065
Vertical fix, breakover device included



Horizontal L-Shaped Magnetic Corner Track Exposed
Product Model YLP064
Horizontal fix, breakover device included



Magnetic 2-Head Connector
Product Model YLP0672
Circuit conductor for non-linear or post mounting



Magnetic Connector
Product Model YLP066
Circuit conductor, recommended to use before mounting



Magnetic Track Exposed
Product Model YLP093
1m, mounting holes included



Vertical Angle L-Shaped Magnetic Corner Track Exposed
Product Model YLP062
Vertical fix, breakover device included



Horizontal L-Shaped Magnetic Corner Track Exposed
Product Model YLP061
Horizontal fix, breakover device included

Magnetic Track

S20 Track Spotlight

- | Dimming precision of one ten thousandth
- | Die-cast aluminum for quick cool-off
- | Low standby power consumption < 0.1W
- | Black or white optional
- | Light source and power supply all-in-one



S20 Track Spotlight

Three-Line Track Lighting
Black / White

Product Model YL P007



Product Size

Beam Angle

Power

φ 55*151.5mm

15°

10W

φ 55*151.5mm

24°

10W

Color Temperature

Luminous Flux

CRI

2800-6000K



550lm

Ra > 90

2800-6000K

550lm

Ra > 90



Yeelight Rooflight



Clear
Blue Sky



30°
Beam Angle



Parallel
Light Ray



Advanced
Dimming Technology



Rayleigh
Scattering




Group
Installation



Sunlight/
Moonlight Mode

Rayleigh scattering



The Courtyard, the Memory, the Sky

The courtyard culture sets the tone of classical Chinese architecture. Picturing the rugged stonewalls with the sky in the middle, you stand between the primitive bricks and tiles, embracing the perfect melody of the home and nature. Today, however, towering mega-cities drive us far from nature, far from the natural tranquility of crystal sky. How to lighten your room with the brightness of sky? Yeelight Rooflight is your answer.

Blue Sky Simulation

Why is the sky blue? Under the high-altitude scattering effect, the short-wave blue-violet sunlight is scattered to the atmosphere. This phenomenon is known as Rayleigh scattering, while Yeelight Rooflight used nano polymer materials to simulate the high-altitude Rayleigh scattering effect, inviting the blue to home.

Optics Expertise

Let Blue Sky Refreshes Your Home

Yeelight Rooflight renders an azure light that is more intense than the sky with well-designed innovations such as the light source selected, the unique lens, and the anti-glare system.

Natural and Pure

A Piece of Art as Thin as 19cm

It is a seemingly unrealistic task to fit 10,000 meters of clear sky on the roof. After countless trials and errors, Yeelight engineers perfectly married up the optical system and scattering system, and polished the product to 19cm, making the in-home sky a reality.



Rooflight Specifications

Name	Yeelight Pro P20 Rooflight	Yeelight Rooflight S2101
Model	YPGJD-0001	YPGJD-0002
Rated input	220V ~ 50/60Hz 0.4A	220V ~ 50/60Hz 0.42A
Rated power	80W(15×7.2W/LED module)	85W(15×7.2W/LED module)
Power factor	0.90	
Luminous flux	2500lm	2700lm
Color temperature	8000K	
CRI	90	
Luminous flux angle	27°	
Dimensions	598×434×190mm	
Hole size	Installation on aluminum gusset ceiling: 300mm×600mm Installation with a hanging rope (protruding frame) : 636×327mm Installation with a hanging rope (recessed frame): 660×351mm	
Operating temperature	-10°C~40°C	
Operating humidity	0-85%RH	
Wireless connection	Bluetooth 4.2 BLE	Not supported



Group Installation

Unleash Your Creativity with DIY Design

The Rooflight can be paired from all sides, allowing you more choices to install them in just the way you want.

Adjustable Luminance

Natural and Dynamic

Now with the brightness adjustment precision of 0.01%, you can enjoy a much smoother dimming.

Take full control of your Yeelight Pro smart system with App, HomeKit, and Google Assistant.



Application Scenarios Home



Application Scenarios Commercial



b.
**Hotel/Real
Estate Engineering**






Hotel/Real Estate Engineering

Recessed Anti-glare Downlight 3"

φ 82*85mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
75mm	15°	10W	2700K-6500K	570lm	Ra > 90
75mm	24°	10W	2700K-6500K	650lm	Ra > 90
75mm	36°	10W	2700K-6500K	750lm	Ra > 90






Hotel/Real Estate Engineering

Recessed Anti-glare Downlight 2.5"

φ 71*80mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
65mm	15°	8W	2700K-6500K	500lm	Ra > 90
65mm	24°	8W	2700K-6500K	500lm	Ra > 90
65mm	36°	8W	2700K-6500K	500lm	Ra > 90






Hotel/Real Estate Engineering

Recessed Anti-glare Downlight 4"

φ 115*120mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
100mm	15°	20W	2700K-6500K	1700lm	Ra > 90
100mm	24°	20W	2700K-6500K	2000lm	Ra > 90
100mm	36°	20W	2700K-6500K	2070lm	Ra > 90







Hotel/Real Estate Engineering

Recessed Anti-glare Downlight 4"

φ 115*120mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
100mm	15°	30W	2700K-6500K	2800lm	Ra > 90
100mm	24°	30W	2700K-6500K	3000lm	Ra > 90
100mm	36°	30W	2700K-6500K	3080lm	Ra > 90
100mm	48°	30W	2700K-6500K	3080lm	Ra > 90






Hotel/Real Estate Engineering

Recessed Frameless Anti-glare Downlight 3"

φ 75*85mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
75mm	15°	10W	2700K-6500K	570lm	Ra > 90
75mm	24°	10W	2700K-6500K	650lm	Ra > 90
75mm	36°	10W	2700K-6500K	750lm	Ra > 90






Hotel/Real Estate Engineering

Recessed Anti-glare Downlight 2.5"

φ 65*80mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
65mm	15°	8W	2700K-6500K	500lm	Ra > 90
65mm	24°	8W	2700K-6500K	500lm	Ra > 90
65mm	36°	8W	2700K-6500K	500lm	Ra > 90









Hotel/Real Estate Engineering

Recessed Frameless Anti-glare Downlight

85*85*115mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
75mm*75mm	15°	10W	2700K-6500K	710lm	Ra > 90
75mm*75mm	24°	10W	2700K-6500K	820lm	Ra > 90
75mm*75mm	36°	10W	2700K-6500K	830lm	Ra > 90
95mm*95mm	15°	20W	2700K-6500K	1500lm	Ra > 90
95mm*95mm	24°	20W	2700K-6500K	1700lm	Ra > 90
95mm*95mm	36°	20W	2700K-6500K	1770lm	Ra > 90







Hotel/Real Estate Engineering

High-voltage Track Lighting (3-Circuit)



Product Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
φ 60*150mm	15°	10W	2700K-6500K	1000lm	Ra > 90
φ 60*150mm	24°	10W	2700K-6500K	1000lm	Ra > 90
φ 60*150mm	15°	20W	2700K-6500K	1600lm	Ra > 90
φ 60*150mm	24°	20W	2700K-6500K	1600lm	Ra > 90






Hotel/Real Estate Engineering

Retractable Multi-angle Downlight

φ 98*120mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
90mm	15°	10W	2700K-6500K	670lm	Ra > 90
90mm	24°	10W	2700K-6500K	670lm	Ra > 90
90mm	36°	10W	2700K-6500K	670lm	Ra > 90
90mm	15°	20W	2700K-6500K	1200lm	Ra > 90
90mm	24°	20W	2700K-6500K	1310lm	Ra > 90
90mm	36°	20W	2700K-6500K	1380lm	Ra > 90




Hotel/Real Estate Engineering

Smart Wall Washer

φ 88*80mm
φ 115*110mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
75mm	48°	10W	2700K-6500K	480lm	Ra > 90
95mm	86°	20W	2700K-6500K	1120lm	Ra > 90






Hotel/Real Estate Engineering

Recessed Deep Anti-glare Downlight

φ 52*90mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
45mm	15°	8W	2700K-6500K	300lm	Ra > 90
45mm	24°	8W	2700K-6500K	410lm	Ra > 90
45mm	36°	8W	2700K-6500K	460lm	Ra > 90






Hotel/Real Estate Engineering

Recessed Single Downlight

115*115*90mm 135*135*120mm
135*135*130mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
95*95mm	18° /24° /38° /60°	10W	2700K-6500K	800lm	Ra > 90
115*115mm	15° /24° /40°	20W	2700K-6500K	1800lm	Ra > 90
115*115mm	15° /24° /40°	30W	2700K-6500K	2400lm	Ra > 90






Hotel/Real Estate Engineering

Recessed Double Downlight

115*210*95mm 135*250*120mm
135*250*130mm



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
95*190mm	18° /24° /38° /60°	2*10w	2700K-6500K	800lm	Ra > 90
115*230mm	15° /24° /40°	2*20w	2700K-6500K	1800lm	Ra > 90
115*230mm	15° /24° /40°	2*30w	2700K-6500K	2400lm	Ra > 90



Hotel/Real Estate Engineering

Low-voltage Tunable \ color light strip



Product/ Installation Size

Beam Angle


Power

Color Temperature

Luminous Flux

CRI

5mm*240LEDs/m	120°	8/12/20W/m	2700K-6500K	640 / 960 / 1600lm	Ra > 90
8mm*120LEDs/m	120°	8/12/20W/m	2700K-6500K	720 / 1080 / 1800lm	Ra > 90
10mm*216LEDs/m	120°	8/12/20W/m	2700K-6500K	720 / 1080 / 1800lm	Ra > 90
12mm*96LEDs/m	120°	14W/m	RGBW 4000K	/	Ra > 90



Hotel/Real Estate Engineering

Tunable \ silicone color light strip



Product/ Installation Size

Beam Angle


Power

Color Temperature

Luminous Flux

CRI

16mm*16mm*216LEDs/m	120°	8/12/14W/m	2700K-6500K	480 / 630 / 860lm	Ra > 90
16mm*16mm*96LEDs/m	120°	14W/m	RGBW 4000K	/	Ra > 90



Hotel/Real Estate Engineering

Light Strip Power Module



Product Category	Product Size	Power	Color Temperature	Luminous Flux	CRI
DC-DC module (dual color temperatures)	95*45*25mm	120W	2700K-6500K	/	/
DC-DC module (RGBW)	126*40*25mm	120W	RGBW	/	/

Hotel/Real Estate Engineering

Constant Voltage Driver

Engineering model



Product Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
105*50*28mm	/	60W	/	/	/
139*55*28mm	/	100W	/	/	/
178*61*28mm	/	150W	/	/	/
178*61*28mm	/	200W	/	/	/
215*61*30mm	/	250W	/	/	/
215*61*30mm	/	300W	/	/	/

Hotel/Real Estate Engineering

Constant Voltage Driver

Ultra-thin model



Product Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
171*54*16mm	/	30W	/	/	/
220*55*16.5mm	/	40W	/	/	/
220*55*16.5mm	/	45W	/	/	/
238*55*16.5mm	/	60W	/	/	/
310*70*16.5mm	/	120W	/	/	/

Hotel/Real Estate Engineering

Smart Bathroom Master



Product Size	Power	Color Temperature	Luminous Flux	Rated Input
620*320*120mm	2750W	4000K	1000lm+	220V~ 50Hz (L、N)

C.
Exhibition Hall






Exhibition Hall

Recessed Downlight



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
85mm	120°	10W	2700K-6500K	580lm	Ra > 90
90mm	120°	15W	2700K-6500K	840lm	Ra > 90
110-115mm	120°	20W	2700K-6500K	1190lm	Ra > 90
160-180mm	120°	20W	2700K-6500K	1230lm	Ra > 90
205-220mm	120°	30W	2700K-6500K	1760lm	Ra > 90









Exhibition Hall

Deep Anti-glare Downlight



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
75mm	15°	10W	2700K-6500K	600lm	Ra > 90
75mm	24°	10W	2700K-6500K	600lm	Ra > 90
75mm	36°	10W	2700K-6500K	600lm	Ra > 90
95mm	15°	20W	2700K-6500K	1330lm	Ra > 90
95mm	24°	20W	2700K-6500K	1330lm	Ra > 90
95mm	36°	20W	2700K-6500K	1330lm	Ra > 90






Exhibition Hall

Gimbal Downlight



Opening Size	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
95mm	15°	20W	2700K-6500K	1660lm	Ra > 90
95mm	24°	20W	2700K-6500K	1660lm	Ra > 90
95mm	36°	20W	2700K-6500K	1660lm	Ra > 90



d.
Office Engineering




Office Engineering

Smart Straight Down Panel Light

600*600 (Aluminum plate)
1200*300(Aluminum plate)




Installation Method	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
Recessed 600*600mm	120°	40W	2700-6500K	4040lm	Ra>80
Recessed 1200*300mm	120°	40W	2700-6500K	4040lm	Ra>80




Office Engineering

Smart Straight Down Panel Light

595*595 (mineral wool panel)
1195*295(mineral wool panel)



Installation Method	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
Recessed 600*600mm	120°	40W	2700-6500K	4040lm	Ra>80
Recessed 1200*300mm	120°	40W	2700-6500K	4040lm	Ra>80



Office Engineering

Prismatic Profile Light Downlight

LS3570



Installation Method

Beam Angle

Power

Color Temperature

Luminous Flux

CRI

1200*35*70mm


120°

40W

3000K/4000K/5000K

2900lm

Ra>80



Office Engineering

Profile Light with Reflector Downlight and uplight

LS3570



Product Size

Beam Angle

Power

Color Temperature

Luminous Flux

CRI

1288*35*70mm


34°

40W

3000K/4000K/5000K

4130lm

Ra>80




Office Engineering

Prismatic Profile Light Downlight

LS5065



Installation Method	Beam Angle	Power	Color Temperature	Luminous Flux	CRI
1200*50*65mm	120°	40W	2700K-6500K	3360lm	Ra>80



e.
Smart Accessories



Gateway

S20 Gateway (BLE Mesh)

Product Model YLWG01YL

Size 84x84x21 mm

Materials ABS

A smooth smart lighting experience is guaranteed with Yeelight Pro S20 Mesh Gateway that supports two access modes: WLAN connection and Wi-Fi connection. It can deliver more stable performance with WLAN connection.

Curtain Motor

S20 Smart Curtain Motor

Product Model YLP012

Product Size 322*40*40mm(±1mm)

Power 22W

Auto on/off
Multiple control methods
Smart connection of lights and fixtures

Switch Module

S20 Two-way Control Module

Product Model YLA1006

Product Size 49.5*46.2*24.5mm

Specification 10A/2500W

Remote control Timer switch
Make traditional appliances smart in seconds
Smart control at your fingertips

Switch Module

S21 VRF Air conditioner thermostat

Product Model YL P091

Product Size 106*91*58mm

Specification Rated Input: DC12V

Fullscreen for a minimalist interface
The new timer function allows users to set the schedule with a single tap before bedtime
Capable of controlling 95% of the air conditioning brands on the market

Gateway

S20 Bluetooth Mesh Network

Product Model YLCGQ0111

installation /

Specifications 100-240V AC 50Hz/60Hz

Support network and Wi-Fi. Routing chip supports Yeelight Pro system and HomeKit

Smart Control

S21 Full-screen Switch

Product Model YLP029

installation Neutral wire and live wire

Product Size 86mm* 86mm *21mm

Stable and consistent routing chip
 Integrated Yeelight Pro and Mi Home
 480P HD multi-touch screen with oleophobic anti-fingerprint coating
 Built-in speaker and light sensor
 Auto-brightness and auto dark mode
 Lifetime OTA upgrade service

Smart Control

S21 Smart Scene Switch

Product Model YLP083 YLP082

installation Neutral wire and live wire

Product Size 86mm*86mm

Grey or white optional; glass panel
 Smart lighting experience with high-quality scene switch
 All at your fingertips

Smart Control

S20 Smart Scene Switch 4 Keys



Product Model YLKG002 YLK002-A

Product Size 86×86mm

installation 4-key panel 4-key surface mount

Smart scene at your fingertips
Minimalism frameless design

Smart Control

S20 Smart Scene Switch 8 Keys



Product Model YLKG002 YLKG002-A

Product Size 86 × 86mm

installation 8-key panel 8-key surface mount

Smart scene at your fingertips
Minimalism frameless design

Smart Control

S21 Smart Scene Switch 1/2/3 Keys



Product Model YLP089 YLP088 YLP087 YLP086 YLP085 YLP084

Product Size 86×86mm

installation Neutral wire and live wire

Bluetooth control and wireless connection
Non-smart light becomes smart in seconds

Smart Control

M20 Rotary Switch



Product Model YLP090

Product Size $\Phi 66.5 \times 34 \text{mm}$

Specifications Battery-powered

Bluetooth control and wireless connection,
simple and push

Sensor

S21 Motion Sensor



Product Model YPCGQ-0004

Surface Mount

Specifications Battery-powered

Detect the movement of human or animals
Adjustable angle with magnetic design
Easy install with surface mount
All-device smart connection

Sensor

P20 Human Presence Sensor



Product Model YLP092

Product Size $48 \times 26 \times 78 \text{mm}$

Specifications Battery-powered

Automotive millimetre-wave radar
Micromotion sensor and easy installation

Yeelight provides professional smart dimming drivers



Constant current power supply 20W, 40W

16 levels available

Dimming precision of one ten thousandth

Single and double color temperature adjustable



Constant current power supply 60W, 120W

3 levels available

Dimming precision of one ten thousandth

Single and double color temperature adjustable



DC-DC dual color temperature, RGBW module

Maximum power: 120W

- 2700K-6500K

YEELIGHT

www.yeelight.com

F10-B4, Bldg B, International Innovation Park, 169 Songling Rd., Laoshan,
Qingdao, 266101

Official Distributor:



Visit us at www.yeelight.co for more information
Please contact us at **+65 8110 1888 / +65 81107888**

Email us at enquiry@tradegallery.co

Address: **61 Upper Paya Lebar Rd**
#01-02 , 01-03, 01- 04 Singapore 534816

