



PROFESSIONAL GRADE ROOFING & WATERPROOFING

PRODUCT CATALOG



APOC is the destination for professional grade roofing and waterproofing products that maximize productivity, profitability, and energy efficiency. With a focus on quality and innovation, APOC products have set the standard for the industry and are the choice of top contractors.

TABLE OF CONTENTS

	FELTS & UNDERLAYMENTS	3
	ACRYLIC COATINGS	4
	SILICONE COATINGS	4
	PRIMERS & BASE COATS	5
	ALUMINUM COATINGS	6
	ASPHALT COATINGS	7
	CEMENTS	8 & 9
	ADHESIVES	9
ı	ROOF & CONSTRUCTION PATCHES, SEALANTS, & ADHESIVES	10
	ACCESSORIES	10 & 11
	SPRAY FOAM	11





APOC 26 TUFF-FELT®

PREMIUM ROOF UNDERLAYMENT

- Excellent for steep-slope roofing
- Can be installed under all types of building materials
- Type II #30, ASTM D226, ASTM D4869, CSA A123.3-05 UL classified, Miami-Dade approved
- Size: 36"x72"



AP-0029

APOC 29 TUFF-FELT®

PREMIUM ROOF UNDERLAYMENT

- Excellent for steep-slope roofing
- Can be installed under all types of building materials
- Type II #30, ASTM D4869, CSA A123.3-05 UL classified
- Size: 36"x72"



AP-6500-45

CX-L CROSSOVER™

HYBRID ROOF UNDERLAYMENT

- Greater uplift with fewer fasteners
- Waterproof & nail sealable membrane
- 60 day exposure
- ASTM D4869, ASTM D226, ASTM D1970, UL classified, Miami-Dade approved
- Size: 37.25"x 145"



AP-4100-2

SB-1 SELF-BOND™

PREMIUM ALL-PURPOSE ROOF UNDERLAYMENT

- High strength reinforcement, exceptional elasticity and a non-skid mineral finish
- Can be installed under all types of building materials
- 90 day exposure
- Type II #30, ASTM D4869, CSA A123.3-05 UL classified
- Size: Approx 2. squares



AP-4200-2

FT³ FLEECE-TOP

FLEECE-TOP ROOF UNDERLAYMENT

- Ideal under tile, metal & with mechanical attachment
- Waterproof & nail sealable membrane
- 180 day exposure
- ASTM D1970, Miami-Dade approved
- Size: Approx. 2 squares



AP-4300-2

HT³ HIGH TEMPERATURE

HIGH TEMPERATURE ROOF UNDERLAYMENT

- Withstands extreme heat & high temp applications up to 265°F
- Ideal under metal, tile & other roof systems
- ASTM D1970, UL classified, TDI listed, Miami-Dade approved
- 180 day exposure
- Size: Approx. 2 squares



AP-4320-2

HT² HIGH TEMPERATURE

HIGH TEMPERATURE ROOF UNDERLAYMENT

- Withstands extreme heat & high temp applications up to 265°F
- Ideal under metal, tile & other roof systems
- ASTM D1970
- 90 day exposure
- Size: Approx. 2 squares





APOC 247 ENERGY-ARMOR®

SUN-SHIELD® WHITE ELASTOMERIC ROOF COATING

- Protects, reflects and cools roofs
- · Extremely flexible resists cracking
- CRRC, Title 24, ASTM D6083, Miami-Dade approved
- Sizes: 5G, 55G, 275G



AP-248

APOC 248 ENERGY-ARMOR®

ARIZONA HIGH PERFORMANCE WHITE ELASTOMERIC ROOF COATING

- · Protects, reflects and cools roofs
- Ideal for extreme heat & cold environments
 great tensile and elongation
- CRRC, Title 24, ASTM D6083, UL classified, Miami-Dade approved
- Sizes: 5G, 55G, 275G



AP-252

Also available in tan.

APOC 252 ENERGY-ARMOR®

SUN-WHIITE® PREMIUM WHITE ELASTOMERIC ROOF COATING

- Protects, reflects and cools roofs
- Ideal for extreme heat and cold environments - great tensile and elongation
- Never-crack finish urethane modified
- CRRC, Title 24, ASTM D6083, UL classified, Miami-Dade approved
- Sizes: 5G, 55G, 275G



AP-258

APOC 258 ENERGY-ARMOR®

ULTRA 100% ELASTOMERIC ROOF COATING

- Protects, reflects and cools roofs
- Never-crack finish titanium fortified finish
- Mold and mildew resistant film
- CRRC, Title 24, ASTM D6083, UL classified, Miami-Dade approved
- Sizes: 275G

SIILCONE COATINGS



AP-585

Also available in tan.

High build formula available (AP-585HB)

APOC 585 ARMOR FLEX®

LIQUID SILICONE ROOF MEMBRANE

- Protects, reflects and cools roofs
- 90% solids extreme durability
- Resists ponding water
- · Cures quickly, even in cool temperatures
- CRRC, Title 24, ASTM D6694, UL classified, Miami-Dade approved
- Sizes: 5G, 55G, 275G



AP-587

APOC 587 ARMOR FLEX®

MIRACLE ROOF MAINTAINABLE SILICONE COATING

- Protects, reflects and cools roofs
- Bond and adhere to silicone coatings and sealants
- Resists ponding water
- CRRC, ASTM D6694, Miami-Dade approved
- Sizes: 5G





AP-583

APOC 583 ARMOR-BASE®

WATERBORNE BLEED-BLOCKING PRIMER

- Prepares surface for silcone coatings
- Helps reduce bleed-through and promotes adhesion
- Boosts long-term performance
- · Distinct blue color for even coverage
- Sizes: 5G, 55G, 275G



AP-230

APOC 230 ENERGY-ARMOR®

BLEED-BLOCK ELASTOMERIC BASE COAT

- Prepares surface for elastomeric coatings
- Helps reduce bleed-through and promotes adhesion
- · Boosts long-term performance
- Distinct gray color for even coverage
- Sizes: 5G, 55G, 275G

APOC Source APOC

AP-290

APOC 290 SECURE-PRIME®

SELF-ADHERED MEMBRANE PRIMER

- Improves adhesion of self-adhered membranes
- Improves long-term performance
- Improves coataimg adhesion around problem areas
- Distinct blue color for even coverage
- Sizes: 3.5G & 1G



AP-291

APOC 291

RUST INHIBITING PRIMER

- Improves adhesion and long-term performance
- Prepares surface for reflective coatings
- Stops rust formation
- Distinct rust red color for even coverage
- Sizes: 5G



AP-296

APOC 296

SINGLE PLY ADHESIVE PRIMER

- Improves adhesion and long-term performance
- Prepares surface for reflective coatings
- Distinct blue color for even coverage
- Sizes: 5G, 55G



AP-103

APOC 103 BOND N' PRIME®

ASPHALT PRIMER

- Penetrates & restores ideal under BUR and coatings
- Promotes a strong bond
- Great for asphalt/BUR/concrete, metal, mod-bit and wood
- Meets ASTM D41 & Miami-Dade approved
- Sizes: Aerosol, 1G, 5G, 55G





APOC 207 SILVER-GUARD®

NON-FIBERED ALUMINUM ROOF COATING

- Protects, reflects and cools roofs
- Extends roof life
- · Rust inhibiting
- Bright silver finish
- ASTM D2824, Miami-Dade approved
- Sizes: 5G, 55G



AP-208

APOC 208

FIBERED ALUMINUM ROOF COATING

- Protects, reflects and cools roofs
- Extends roof life
- Rust inhibiting
- Bright silver finish
- ASTM D2824, UL classified, Miami-Dade approved
- Sizes: 5G



AP-211

APOC 211 LIQUID-SILVER®

PREMIUM NON-FIBERED ALUMINUM ROOF COATING

- Protects, reflects and cools roofs
- Extends roof life
- Added durability premium aluminum
- ASTM D2824, UL classified, Miami-Dade approved

• Sizes: 5G



AP-212

APOC 212 LIQUID-SILVER®

PREMIUM FIBERED ALUMINUM ROOF COATING

- Protects, reflects and cools roofs
- Extends roof life
- Added durability premium aluminum
- ASTM D2824 ASTM D3805, UL classified, Miami-Dade approved
- Sizes: 5G, 55G

APOC MASTERWORKS EDUCATION & TRAINING

APOC offers a variety of training programs designed specifically for contractors. Our programs are designed to educate installers on the proper and efficient application of APOC products and systems and bring awareness of new technologies and products, application techniques, new codes and regulations, and industry updates.

Visit www.apoc.com/pages/education to view training dates and sign up for a course.









AP-139

APOC 139

RUBBERIZED ASPHALT COATING & ADHESIVE

- Renews worn roof surfaces
- Bond mod-bit rolls and built-up roof plies
- Dampproof exterior below grade foundation walls
- ASTM D3019
- Sizes: 5G



AP-200

APOC 200 RAINSHIELD®

NON-FIBERED ROOF & FOUNDATION COATING

- Waterproofs and restores roofs
- Rust inhibiting
- Penetrator and sealer for a variety of exterior concrete and masonry surfaces
- ASTM D3019
- Sizes: 5G, 55G



AP-202

APOC 202 RAINSHIELD®

FIBERED ROOF & FOUNDATION COATING

- Waterproofs and restores roofs
- Rust inhibiting
- Penetrator and sealer for a variety
 of exterior concrete and masonry surfaces
- ASTM D3019, Miami-Dade approved
- Sizes: 5G, 55G



AP-300 Spray grade available (AP-300-S)

APOC 300

NON-FIBERED ASPHALT EMULSION

- Ideal for reinforced restoration
- Below grade exterior dampproofing
- Base coat for reflective coatings
- ASTM D1227, ICC ESR-3796, UL classified, Miami-Dade approved
- Sizes: 5G, 275G



AP-302

APOC 302 PRO-GARD

FIBERED ASPHALT EMULSION

- Base coat for polyester systems
- · Below grade exterior dampproofing
- Restores and protects
- Ideal with silicones and elastomerics
- ASTM D1227, UL classified, Miami-Dade approved
- Sizes: 5G, 55G, 275G



AP-525

APOC 525

THERMOPLASTIC SURFACING COMPOUND

- Renews asphalt surfaces
- Resists ponding water
- Ideal for waterproofing BUR, coal tar modified and gravel roofs
- ASTM D3019, UL classified, Miami-Dade approved
- Sizes: 5G





AP-037

APOC 037

PLASTIC ROOF CEMENT

- Seals splits and cracks
- · All purpose mastic
- · Miami-Dade approved
- Sizes: 3G, 5G



AP-101

PLASTIC ROOF CEMENT

LACTIO ROOF OLIVILINI

- Seals splits and cracks
- All purpose mastic
- · Vertical application will not sag

APOC 101 WORK-HORSE

- Miami-Dade approved
- Sizes: 3G, 5G



AP-109

APOC 109

ASPHALT ROOF CEMENT

- Leak repair
- Vertical application will not sag
- Wet or dry application bonds underwater
- ASTM D3409, ASTM D4586, Miami-Dade approved
- Sizes: 10oz. 1G. 3G. 5G



AP-115

APOC 115 BLACK GOLD®

LIQUID RUBBER FLASHING CEMENT

- All weather/season
- Rubberized resists cracking for long term repairs
- Wet/dry application bonds underwater ASTM D6511, ASTM D3409, Miami-Dade approved
- Sizes: 3G, 5G



AP-121

APOC 121

ARIZONA PLASTIC ROOF CEMENT

- Leak repair
- Vertical applications will not sag
- · Heavy duty mastic
- ASTM D4586
- Sizes: 5G



AP-122

APOC 122 AQUA BOND

WET/DRY FLASHING CEMENT

- Leak Repair
- Vertical Applications will not sag
- Excellent bond/adhesion underwater
 great for emergency repairs
- Wide application temperature range
- Spreads easily
- Miami-Dade approved
- Sizes: 5G



AP-128

APOC 128 ALL PRO

SBS MODIFIED FLASHING CEMENT

- Rubberized resists cracking for long term repairs
- · Wide application temperature range
- ASTM D4586, ASTM D3409, Miami-Dade approved
- Sizes: 5G



AP-133

APOC 133 PROLASTIC

THERMOPLASTIC SURFACING COMPOUND

- Renews asphalt surfaces
- Resists ponding water
- Ideal for waterproofing BUR, coal tar modified and gravel roofs
- ASTM D3019, UL classified, Miami-Dade approved
- Sizes: 3G, 5G





APOC 365

RUBBERIZED FLASHING CEMENT

- All weather/season
- Rubberized resists cracking for long term repairs
- · Vertical application will not sag
- Wet/dry application bonds underwater
- · Spreads easily
- ASTM D3409, ASTM D4586, Miami-dade approved
- Sizes: 10oz, 1G, 3G

ADHESIVES



AP-107

APOC 107

COLD APPLIED ROLL ROOF ADHESIVE

- Mod-bit adhesive
- Bonds plies in built up
- Renews worn asphalt roof surfaces
- ASTM D3019, UL classified, Miami-Dade approved
- Sizes: 5G, 275G



AP-139

APOC 139

RUBBERIZED ASPHALT COATING & ADHESIVE

- Renews worn roof surfaces
- Bond mod-bit rolls and built-up roof plies
- Dampproof exterior below grade foundation walls
- ASTM D3019
- Sizes: 5G



ROOF & CONSTRUCTION PATCHES, SEALANTS & ADHESIVES



AP-264 Also available

APOC 264

ELASTOMERIC ROOF PATCH

- For use with elastomeric roof coatings
- 100% waterproof urethane technology
- UV stable prevents deterioration
- ASTM D1475, ASTM D2196, ASTM D2939, TAS 139, Miami Dade approved
- Sizes: 10oz, 1G, 3.5G, 5G



AP-515

APOC 515 LIQUID FLASH®

PERMANENT DETAIL SEALANT

- For use with elastomeric roof coatings
- 100% waterproof urethane technology
- UV stable prevents deterioration
- ASTM D1475, ASTM D2196, ASTM D2939, TAS 139, Miami Dade approved
- Sizes: 10oz. 1G. 3.5G. 5G



AP-501

APOC 501 SUPER-FLASH®

NEOPRENE FLASHING SEALANT

- Permanent, leak proof seal
- Superior wet surface adhesion bonds underwater
- Extreme versatility compatible with various surfaces
- ASTM D4586. ASTM D3409. ASTM D6511
- Sizes: 10oz. 3G

APOL

AP-581

APOC 581

SILICONE ROOF PATCH

- For use with silicone roof coatings
- 100% silicone ultimate durability & flexibility
- Wide application temps (35-110°F)
- Resists ponding water
- ASTM C920
- Sizes: 2G



AP-5070

APOC 5070

TRI-POLYMER WATERPROOFING SEALANT

- Wide application temperatures (0-110°F)
- UV stable
- Paintable/coatable
- ASTM C661, C794, C679, C1250, C793, C734



Also available



APOC AP-1®

CONSTRUCTION SEALANT & ADHESIVE

- Heavy duty adhesive
- Wide application temperatures (0-140°F)
- Low VOC/low odor
- Paintable/coatable
- ASTM C920

ACCESSORIES



AP-482 Available in soft

or firm.

APOC 482

POLYESTER REINFORCEMENT FABRIC

- Reinforces adds strength and durability
- For use with asphalt emulsion, solvent-based c process systems. cements, neoprene sealants, asphalt coatings, white roof mastic and white elastomeric coatings
- Weight: 2.7 oz./sq. yd
- Available width: 40"



APOC 483

SOFT POLYESTER REINFORCEMENT FABRIC

- Reinforces adds strength and durability
- For use with asphalt emulsion, solventbased cold process systems. cements, neoprene sealants, asphalt coatings, white roof mastic and white elastomeric coatings
- Weight: 3 oz./sq. yd
- Available widths: 4", 6", 12", 20", 40"







APOC 470

ASPHALT SATURATED REINFORCING FABRIC

- Extends repair life
- Open mesh for superior bond
- For use with asphalt-based products
- Available widths: 3", 4", 6", 12"



Available in white, black & fleece-top.

APOC INCREDIBLE TAPE

HEAVY DUTY ALL PURPOSE TAPE

- Saves time and labor
- Ideal with all roof coatings
- Permanent bond and instant seal
- Widths available: white (4",6", 12")

 black (6")

 fleece (4",6")



AP-11

APOC 11

WHITE TOP CERAMIC ROOFING GRANULES

- Ceramic coated high quality mineral rock
- · Covers asphalt bleed out
- Adds UV protection protects premature aging
- · White granules



AP-801

APOC 801

HEAVY DUTY ROOF CLEANER

- Removes tough stains and promotes coating adhesion
- · Removes mold and mildew stains
- · Cleans dirt and soot
- Biodegradable non-corrosive formula
- · Bleach free and solvent free
- Sizes: 1G (concentrated formula makes up to 20 gallons)

SPRAY FOAM



AP-700

APOC 700 ARMOR FLASH SPF

LOW PRESSURE SPRAY POLYURETHANE FOAM

- High density roofing patch & repair spray foam product
- Fast & easy to use
- Fills gaps, cracks, and holes
- Low GWP blowing agent
- · Portable and disposable kit
- Size: 115 board feet



AP-701

APOC 701 POLYSET ROOF SEAL

MULTI-PURPOSE PREMIUM FOAM SEALANT

- Provides a temporary "night seal"
- Easily removable
- No power required
- Portable and disposable kit
- Low GWP blowing agent
- Size: 2,741 ft @ 1" bead



AP-705

APOC 705 POLYSET RTA-1

LOW PRESSURE ROOF TILE ADHESIVE FOAM

- Virtually eliminates deck penetrations and tile damage from mechanical fasteners
- Prevents tile chattering
- Miami-Dade approved, low GWP blowing agent, IAPMO UES ER-639
- Sizes: 24oz straw foam (31 tiles),
 23lb cylinder foam (474 tiles)

