

# APOC Foam System HFO A-side ICP Construction Inc.

Version No: 1.3

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **08/24/2022** Print Date: **08/24/2022** S.GHS.USA.EN

#### **SECTION 1 Identification**

#### **Product Identifier**

Product name	APOC Foam System HFO A-side			
Synonyms	Not Available			
Proper shipping name	Chemical under pressure, n.o.s. (Hydrofluoroolefin, Nitrogen)			
Other means of identification	Not Available			

#### Recommended use of the chemical and restrictions on use

Relevant identified uses Low pressure polyurethane foam. Side A Component. For PROFESSIONAL USE ONLY

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.			
Address	60 Dascomb Road Andover, MA 01810 United States			
Telephone	-667-5119 1-978-623-9987			
Fax	Not Available			
Website	www.icpgroup.com			
Email	sds@icpgroup.com			

#### Emergency phone number

Association / Organisation	ChemTel	
Emergency telephone numbers	1-800-255-3924	
Other emergency telephone numbers	1-813-248-0585	

#### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Serious Eye Damage/Eye Irritation Category 2A, Sensitisation (Respiratory) Category 1, Specific Target Organ Toxicity - Repeated Exposure Category 2, Acute Toxicity (Inhalation) Category 4, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Skin Corrosion/Irritation Category 2, Gases Under Pressure (Compressed Gas), Sensitisation (Skin) Category 1, Carcinogenicity Category 2

#### Label elements

Hazard pictogram(s)







Signal word

Danger

#### Hazard statement(s)

H31

Causes serious eye irritation.

Version No: **1.3** Page **2** of **12** Issue Date: **08/24/2022** 

#### **APOC Foam System HFO A-side**

Print Date: **08/24/2022** 

H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.			
H373	May cause damage to organs through prolonged or repeated exposure. (Respiratory system) (Inhalation)			
H332	Harmful if inhaled.			
H335	May cause respiratory irritation.			
H315	Causes skin irritation.			
H280	Contains gas under pressure; may explode if heated.			
H317	May cause an allergic skin reaction.			
H351	Suspected of causing cancer.			

#### Hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) Prevention

P202 Do not handle until all safety precautions have been read and understood			
P260	Do not breathe gas.		
P262	Do not get in eyes, on skin, or on clothing		
P264	Wash hands and other skin areas exposed to material thoroughly after handling		
P271	Use only outdoors or in a well-ventilated area.		
P280	Wear protective gloves, protective clothing and eye protection		
P284	Wear respiratory protection		

#### Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.			
P342+P311	P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/physician/first aider.			
P305+P351+P338	15+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.			
P302+P352+P333+P313 IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention				

#### Precautionary statement(s) Storage

P405	Store locked up.	
P410+P403	Protect from sunlight. Store in a well-ventilated place.	
P403+P233 Store in a well-ventilated place. Keep container tightly closed.		

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Not Applicable

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name	
101-68-8	30-60	4.4'-diphenylmethane diisocyanate (MDI)	
9016-87-9	30-60	polymeric diphenylmethane diisocyanate	
29118-24-9	5-10	1,3,3,3-tetrafluoropropene	
7727-37-9.	<5	nitrogen	

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### **SECTION 4 First-aid measures**

#### Description of first aid measures

**Eye Contact** 

- If product comes in contact with eyes remove the patient from gas source or contaminated area.
- ► Take the patient to the nearest eye wash, shower or other source of clean water.
- Open the eyelid(s) wide to allow the material to evaporate.
- Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.
- The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.
- Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s)
- ► Transport to hospital or doctor.
- Even when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.
- If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.

Version No: 1.3 Page 3 of 12 Issue Date: 08/24/2022 Print Date: 08/24/2022

#### **APOC Foam System HFO A-side**

Ensure verbal communication and physical contact with the patient. DO NOT allow the patient to rub the eyes DO NOT allow the patient to tightly shut the eyes DO NOT introduce oil or ointment into the eye(s) without medical advice DO NOT use hot or tepid water. If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Skin Contact Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor Following uptake by inhalation, move person to an area free from risk of further exposure. Oxygen or artificial respiration should be administered as needed. Asthmatic-type symptoms may develop and may be immediate or delayed up to several hours. Treatment is essentially symptomatic. A physician should be consulted. Following exposure to gas, remove the patient from the gas source or contaminated area. NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer. Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. If the patient is not breathing spontaneously, administer rescue breathing Inhalation If the patient does not have a pulse, administer CPR. If medical oxygen and appropriately trained personnel are available, administer 100% oxygen. Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further instruction. Keep the patient warm, comfortable and at rest while awaiting medical care. MONITOR THE BREATHING AND PULSE, CONTINUOUSLY Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if necessary. Ingestion Not considered a normal route of entry.

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

For gas exposures:

BASIC TREATMENT

Establish a patent airway with suction where necessary.

- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- ▶ Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- ► Anticipate seizures.

#### ADVANCED TREATMENT

- ▶ Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For sub-chronic and chronic exposures to isocyanates:

- This material may be a potent pulmonary sensitiser which causes bronchospasm even in patients without prior airway hyperreactivity.
- Clinical symptoms of exposure involve mucosal irritation of respiratory and gastrointestinal tracts
- Conjunctival irritation, skin inflammation (erythema, pain vesiculation) and gastrointestinal disturbances occur soon after exposure.
- Pulmonary symptoms include cough, burning, substernal pain and dyspnoea.
- Some cross-sensitivity occurs between different isocyanates
- Noncardiogenic pulmonary oedema and bronchospasm are the most serious consequences of exposure. Markedly symptomatic patients should receive oxygen, ventilatory support and an intravenous line.
- Treatment for asthma includes inhaled sympathomimetics (epinephrine [adrenalin], terbutaline) and steroids.
- Activated charcoal (1 g/kg) and a cathartic (sorbitol, magnesium citrate) may be useful for ingestion.
- Mydriatics, systemic analgesics and topical antibiotics (Sulamyd) may be used for corneal abrasions.
- There is no effective therapy for sensitised workers.

[Ellenhorn and Barceloux; Medical Toxicology]

NOTE: Isocyanates cause airway restriction in naive individuals with the degree of response dependant on the concentration and duration of exposure. They induce smooth muscle contraction which leads to bronchoconstrictive episodes. Acute changes in lung function, such as decreased FEV1, may not represent sensitivity. [Karol & Jin, Frontiers in Molecular Toxicology, pp 56-61, 1992]

Personnel who work with isocyanates, isocyanate prepolymers or polyisocyanates should have a pre-placement medical examination and periodic examinations thereafter, including a pulmonary function test. Anyone with a medical history of chronic respiratory disease, asthmatic or bronchial attacks, indications of allergic responses, recurrent eczema or sensitisation conditions of the skin should not handle or work with isocyanates. Anyone who develops chronic respiratory distress when working with isocyanates should be removed from exposure and examined by a physician. Further exposure must be avoided if a sensitivity to isocyanates or polyisocyanates has developed.

#### **SECTION 5 Fire-fighting measures**

#### **Extinguishing media**

- Small quantities of water in contact with hot liquid may react violently with generation of a large volume of rapidly expanding hot sticky semi-solid foam.
- Presents additional hazard when fire fighting in a confined space

Version No: 1.3 Page 4 of 12 Issue Date: 08/24/2022

#### **APOC Foam System HFO A-side**

Print Date: 08/24/2022

- ▶ Cooling with flooding quantities of water reduces this risk.
- Dry chemical powder.
- ► BCF (where regulations permit).
- Carbon dioxide.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

#### **GENERAL** Fire Fighting ▶ Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus. Fight fire from a safe distance, with adequate cover. - Combustible. - Moderate fire hazard when exposed to heat or flame. - When heated to high temperatures decomposes rapidly generating vapour which pressures and may then rupture containers with release of flammable and highly toxic isocyanate vapour. Containers may explode when heated - Ruptured cylinders may rocket May burn but does not ignite easily. Fire exposed cylinders may vent contents through pressure relief devices thereby increasing vapour concentration.. Fire may produce irritating, poisonous or corrosive gases. Fire/Explosion Hazard Decomposition may produce toxic fumes of: carbon monoxide (CO) carbon dioxide (CO2) isocyanates hydrogen cyanide and minor amounts of nitrogen oxides (NOx) other pyrolysis products typical of burning organic material.

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

Minor Spills	<ul> <li>Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used.</li> <li>DO NOT enter confined spaces where gas may have accumulated.</li> </ul>
	For isocyanate spills of less than 40 litres (2 m2):  Evacuate area from everybody not dealing with the emergency, keep them upwind and prevent further access, remove ignition sources and
	if inside building, ventilate area as well as possible.  Notify supervision and others as necessary.
	<ul> <li>Put on personal protective equipment (suitable respiratory protection, face and eye protection, protective suit, gloves and impermeable boots).</li> </ul>
	Avoid contamination with water, alkalies and detergent solutions.
	Material reacts with water and generates gas, pressurises containers with even drum rupture resulting.
Major Spills	PONOT reseal container if contamination is suspected.
	DO NOT touch the spill material     Clear area of all unprotected personnel and move upwind.
	Alert Emergency Authority and advise them of the location and nature of hazard.
	Wear full body clothing with breathing apparatus.  * Wear full body clothing with breathing apparatus.
	Remove leaking cylinders to a safe place.  Remove leaking cylinders to a safe place.
	▶ Fit vent pipes. Release pressure under safe, controlled conditions
	▶ Burn issuing gas at vent pipes.
	DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 Handling and storage**

Precautions for safe handling  Safe handling	Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal.  Use only properly specified equipment which is suitable for this product, its supply pressure and temperature      The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines.      Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended.      DO NOT transfer gas from one cylinder to another.
Other information	Consider storage under inert gas.

Version No: **1.3** Page **5** of **12** Issue Date: **08/24/2022** 

#### **APOC Foam System HFO A-side**

Print Date: 08/24/2022

- Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open.
- Such compounds should be sited and built in accordance with statutory requirements.
- ▶ The storage compound should be kept clear and access restricted to authorised personnel only.

#### Conditions for safe storage, including any incompatibilities

#### Suitable container

- Cylinder:
- ▶ Ensure the use of equipment rated for cylinder pressure.
- ▶ Ensure the use of compatible materials of construction
- ► Valve protection cap to be in place until cylinder is secured, connected.

### Storage incompatibility

- · Avoid reaction with water, alcohols and detergent solutions. Isocyanates are electrophiles, and as such they are reactive toward a variety of nucleophiles including alcohols, amines, and even water. Upon treatment with an alcohol, an isocyanate forms a urethane linkage.
  - A range of exothermic decomposition energies for isocyanates is given as 20-30 kJ/mol.
- The relationship between energy of decomposition and processing hazards has been the subject of discussion; it is suggested that values of energy released per unit of mass, rather than on a molar basis (J/g) be used in the assessment.
- For example, in 'open vessel processes' (with man-hole size openings, in an industrial setting), substances with exothermic decomposition energies below 500 J/g are unlikely to present a danger, whilst those in 'closed vessel processes' (opening is a safety valve or bursting disk) present some danger where the decomposition energy exceeds 150 J/g.
- Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances

#### **SECTION 8 Exposure controls / personal protection**

#### Control parameters

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	4,4'-diphenylmethane diisocyanate (MDI)	Methylene bisphenyl isocyanate (MDI)	Not Available	Not Available	0.02 ppm / 0.2 mg/m3	Not Available
US NIOSH Recommended Exposure Limits (RELs)	4,4'-diphenylmethane diisocyanate (MDI)	Methylene bisphenyl isocyanate	0.005 ppm / 0.05 mg/m3	Not Available	0.020 (10-minute) ppm / 0.2 (10-minute) mg/m3	Not Available

#### Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3	
4,4'-diphenylmethane diisocyanate (MDI)	0.45 mg/m3	Not Available	Not Available	
polymeric diphenylmethane diisocyanate	0.15 mg/m3	3.6 mg/m3	22 mg/m3	
1,3,3,3-tetrafluoropropene	1,400 ppm	Not Available	Not Available	
nitrogen	7.96E+05 ppm	8.32E+05 ppm	8.69E+05 ppm	

Ingredient	Original IDLH	Revised IDLH
4,4'-diphenylmethane diisocyanate (MDI)	75 mg/m3	Not Available
polymeric diphenylmethane diisocyanate	Not Available	Not Available
1,3,3,3-tetrafluoropropene	Not Available	Not Available
nitrogen	Not Available	Not Available

#### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit				
polymeric diphenylmethane diisocyanate	E	≤ 0.1 ppm				
Notes:	, , , , , , , , , , , , , , , , , , , ,	nding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the				

#### Exposure controls

### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

### Personal protection







range of exposure concentrations that are expected to protect worker health.





- Eye and face protection
- Safety glasses with side shields.
- Chemical goggles.
   Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants
- Skin protection
- See Hand protection below

 Version No: 1.3
 Page 6 of 12
 Issue Date: 08/24/2022

 Print Date: 08/24/2022
 Print Date: 08/24/2022

#### **APOC Foam System HFO A-side**

Hands/feet protection	NOTE:  The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.  Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.  Isocyanate resistant materials include Teflon, Viton, nitrile rubber and some PVA gloves.  Protective gloves and overalls should be worn as specified in the appropriate national standard.  Contaminated garments should be removed promptly and should not be re-used until they have been decontaminated.  When handling sealed and suitably insulated cylinders wear cloth or leather gloves.
Body protection	See Other protection below
Other protection	<ul> <li>Protective overalls, closely fitted at neck and wrist.</li> <li>Eye-wash unit.</li> <li>Ensure availability of lifeline in confined spaces.</li> </ul>

#### Respiratory protection

Full face respirator with supplied air.

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

#### **SECTION 9 Physical and chemical properties**

Information on basic physical	and chemical properties		
Appearance	Moisture sensitive.		
Physical state	Compressed Gas	Relative density (Water = 1)	1.2
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	208	Molecular weight (g/mol)	Not Available
Flash point (°C)	>199	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Partly miscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<25 When mixed as intended with Side B

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> <li>Presence of elevated temperatures.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7

Version No: **1.3** Page **7** of **12** Issue Date: **08/24/2022** 

#### **APOC Foam System HFO A-side**

Print Date: 08/24/2022

Hazardous decomposition products

See section 5

#### **SECTION 11 Toxicological information**

#### Information on toxicological effects

The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of the vapour is hazardous and may even be fatal

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

Inhalation of toxic gases may cause:

- Central Nervous System effects including depression, headache, confusion, dizziness, stupor, coma and seizures;
- respiratory: acute lung swellings, shortness of breath, wheezing, rapid breathing, other symptoms and respiratory arrest;
- Inhaled heart: collapse, irregular heartbeats and cardiac arrest;
  - gastrointestinal: irritation, ulcers, nausea and vomiting (may be bloody), and abdominal pain.

The vapour/mist may be highly irritating to the upper respiratory tract and lungs; the response may be severe enough to produce bronchitis and pulmonary oedema. Possible neurological symptoms arising from isocyanate exposure include headache, insomnia, euphoria, ataxia, anxiety neurosis, depression and paranoia. Gastrointestinal disturbances are characterised by nausea and vomiting.

Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects. Relatively small amounts absorbed from the lungs may prove fatal.

There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs.

#### Ingestion

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments

Accidental ingestion of the material may be seriously damaging to the health of the individual; animal experiments indicate that ingestion of less than 40 gram may be fatal.

#### Skin Contact

This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition

Skin contact with the material may damage the health of the individual; systemic effects may result following absorption.

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

#### Eye

Not considered to be a risk because of the extreme volatility of the gas.

This material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.

There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.

This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. This product contains a polymer with a functional group considered to be of high concern. Isothiocyanates may cause hypersensitivity of the skin and airways.

#### Chronic

The reactivity of an epoxide intermediate may be the reason for the cancer-causing properties of halogenated oxiranes. It is reported that

1,1-dichloroethyne, vinyl chloride, trichloroethylene, tetrachloroethylene and chloroprene all cause cancer.

Generally speaking, substances with one halogen substitution show higher potential to cause cancer compared to substances with two. Main route of exposure to the gas in the workplace is by inhalation.

Persons with a history of asthma or other respiratory problems or are known to be sensitised, should not be engaged in any work involving the handling of isocvanates.

The chemistry of reaction of isocyanates, as evidenced by MDI, in biological milieu is such that in the event of a true exposure of small MDI doses to the mouth, reactions will commence at once with biological macromolecules in the buccal region and will continue along the digestive tract prior to reaching the stomach. Reaction products will be a variety of polyureas and macromolecular conjugates with for example mucus, proteins and cell components.

Animal testing shows that polymeric MDI can damage the nasal cavities and lungs, causing inflammation.and increased cell growth.

Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia.

#### APOC Foam System HFO A-side

TOXICITY	IRRITATION
Not Available	Not Available

## 4,4'-diphenylmethane diisocyanate (MDI)

TOXICITY	IRRITATION
Dermal (rabbit) LD50: >6200 mg/kg <sup>[2]</sup>	Dermal Sensitiser *
Inhalation(Rat) LC50; 0.368 mg/L4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
Oral (Rat) LD50; >2000 mg/kg <sup>[1]</sup>	Skin (rabbit): 500 mg /24 hours
	Skin: adverse effect observed (irritating) <sup>[1]</sup>

# polymeric diphenylmethane diisocyanate

TOXICITY	IRRITATION
Dermal (rabbit) LD50: >9400 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg - mild
Inhalation(Rat) LC50; 0.49 mg/L4h <sup>[2]</sup>	

Version No: 1.3 Page 8 of 12 Issue Date: 08/24/2022 Print Date: 08/24/2022

#### **APOC Foam System HFO A-side**

Oral (Rat) LD50; 43000 mg/kg<sup>[2]</sup> TOXICITY IRRITATION 1,3,3,3-tetrafluoropropene Inhalation(Rat) LC50; >1157.752 ppm4h<sup>[2]</sup> Not Available TOXICITY IRRITATION nitrogen Not Available Not Available 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise Legend: specified data extracted from RTECS - Register of Toxic Effect of chemical Substances 4,4'-DIPHENYLMETHANE Inhalation (human) TCLo: 0.13 ppm/30 mins Eve (rabbit): 0.10 mg moderate DIISOCYANATE (MDI) POLYMERIC DIPHENYLMETHANE product DIISOCYANATE Inhalation (rat) NOEL (28 days): >1.5 mg/l \* \* Vendor HFO-1234ze is not likely to accumulate in the bodies of humans or animals HFO-1234ze is practically non-toxic. Short-term exposures at levels higher than 10% have not induced cardiac sensitization to adrenalin nor induced serious toxic effects. Rats and rabbits did not exhibit any serious toxic, developmental or reproductive effects even with exposures to high levels of HFO-1234ze. Based on a series of mutagenicity and genomics studies, the cancer risk for HFO-1234ze is low, no cardiac sensitisation was 1,3,3,3 observed in dogs with exposures up to 120,000 ppm; repeated dose toxicity in rats (13-wk) found mild effects on the heart (NOEL 5,000ppm); in **TETRAFLUOROPROPENE** vitro genotoxicity findings include negative Ames Test and negative human lymphocyte chromosome aberration test; in vivo genotoxicity findings in the mouse micronucleus test were negative (inhalation, mammalian bone-marrow cytogenic test with chromosomal analysis). Inhalation of perfluoroalkenes can cause lung injury, kidney damage, brain changes and death. Repeated exposures may alter blood pressure and the production of blood cells. The potential for causing cancer is the subject of speculation. NITROGEN No significant acute toxicological data identified in literature search. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent **APOC Foam System HFO** asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A-side & Allergic reactions involving the respiratory tract are usually due to interactions between IgE antibodies and allergens and occur rapidly. Allergic 4 4'-DIPHENYI METHANE potential of the allergen and period of exposure often determine the severity of symptoms. Some people may be genetically more prone than DIISOCYANATE (MDI) & others, and exposure to other irritants may aggravate symptoms. POLYMERIC Attention should be paid to atopic diathesis, characterised by increased susceptibility to nasal inflammation, asthma and eczema. DIPHENYLMETHANE Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T DIISOCYANATE lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure. The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. **APOC Foam System HFO** Disinfection byproducts (DBPs) are formed when disinfectants such as chlorine, chloramines and ozone react with organic and inorganic matter A-side & 1,3,3,3in water. Animal studies have shown that some DBPs cause cancer. To date, several hundred DBPs have been identified. **TETRAFLUOROPROPENE** Numerous haloalkanes and haloalkenes have been tested for cancer-causing and mutation-causing activities

4,4'-DIPHENYLMETHANE DIISOCYANATE (MDI) & POLYMERIC DIPHENYLMETHANE DIISOCYANATE Isocyanate vapours are irritating to the airways and can cause their inflammation, with wheezing, gasping, severe distress, even loss of consciousness and fluid in the lungs. Nervous system symptoms that may occur include headache, sleep disturbance, euphoria, inco-ordination, anxiety, depression and paranoia.

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis

Aromatic and aliphatic diisocyanates may cause airway toxicity and skin sensitization. Monomers and prepolymers exhibit similar respiratory effect. Of the several members of diisocyanates tested on experimental animals by inhalation and oral exposure, some caused cancer while others produced a harmless outcome.

The substance is classified by IARC as Group 3:

72h

NOT classifiable as to its carcinogenicity to humans.

Evidence of carcinogenicity may be inadequate or limited in animal testing

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	<b>✓</b>	STOT - Repeated Exposure	<b>~</b>
Mutagenicity	×	Aspiration Hazard	×

Legend:

Algae or other aquatic plants

★ - Data either not available or does not fill the criteria for classification

Data available to make classification

>1640ma/l

#### **SECTION 12 Ecological information**

FC50

#### Toxicity

APOC Foam System HFO	Endpoint Test Duration (hr)			Species	Va	alue	So	urce
A-side	Not Available	Not Available		Not Available	No	ot Available	No	t Available
4 41 dimb amulmosth and	En la dat	Total Boundary (L.)				Water		
4,4'-diphenylmethane	Endpoint	Test Duration (hr)	Species			Value		Source

2

Version No: 1.3 Page 9 of 12 Issue Date: 08/24/2022 Print Date: 08/24/2022

#### **APOC Foam System HFO A-side**

	BCF 672h		Fish		61-150		7			
	NOEC(ECx)	504h		Crustacea		>=10mg/l		2		
	LC50	96h		Fish			95.24-134.37m	95.24-134.37mg/l		Available
polymeric diphenylmethane	Endpoint		Test Duration (hr)		Species	Va	alue		Source	
diisocyanate	Not Available Not Available			Not Available Not Available		Not Available				
	Endpoint	Те	st Duration (hr)	Spec	cies		\	/alue		Source
	EC50	72	. ,	Algae or other aquatic plants		>	>170mg/l		2	
1,3,3,3-tetrafluoropropene	EC50	48	h	Crustacea		>	>160mg/l		2	
	EC50(ECx)	48	h	Crus	Crustacea		>	>160mg/l		2
nitrogon	Endpoint		Test Duration (hr)		Species	Va	alue		Source	
nitrogen	Not Available	Not Available		Not Available		No	Not Available		Not Available	

for polyisocyanates:

Polyisocyanates are not readily biodegradable. However, due to other elimination mechanisms (hydrolysis, adsorption), long retention times in water are not to be expected. The resulting polyurea is more or less inert and, due to its molecular size, not bioavailable. For Isocyanate Monomers:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA,

Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan)

Environmental Fate: Isocyanates, (di- and polyfunctional isocyanates), are commonly used to make various polymers, such as polyurethanes. Polyurethanes find significant application in the manufacture of rigid and flexible foams. They are also used in the production of adhesives, elastomers, and coatings. DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Legend:

Ingredient	Persistence: Water/Soil	Persistence: Air
4,4'-diphenylmethane diisocyanate (MDI)	LOW (Half-life = 1 days)	LOW (Half-life = 0.24 days)

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
4,4'-diphenylmethane diisocyanate (MDI)	LOW (BCF = 330)

#### Mobility in soil

Ingredient	Mobility
4,4'-diphenylmethane diisocyanate (MDI)	LOW (KOC = 376200)

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Evaporate residue at an approved site.

- Bioconcentration Data 8. Vendor Data

Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.

#### **SECTION 14 Transport information**

#### **Labels Required**



**Marine Pollutant** 

NO

#### Land transport (DOT)

UN number	3500
UN proper shipping name	Chemical under pressure, n.o.s. (Hydrofluoroolefin, Nitrogen)

 Version No: 1.3
 Page 10 of 12
 Issue Date: 08/24/2022

 Print Date: 08/24/2022
 Print Date: 08/24/2022

#### **APOC Foam System HFO A-side**

	Ι			
Tourse and bossed along (as)	Class	2.2		
Transport hazard class(es)	Subrisk	Not Applicab	le	
Packing group	Not Applicabl	Not Applicable		
Environmental hazard	Not Applicabl	Not Applicable		
	l		•	
Special precautions for user	Hazard Lab	pel 2.	2	
	Special pro	visions 36	52, T50, TP40	

#### Air transport (ICAO-IATA / DGR)

UN number	3500			
UN proper shipping name	Chemical under pressure	Chemical under pressure, n.o.s. * (Hydrofluoroolefin, Nitrogen)		
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	2.2  Not Applicable  2L		
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
	Special provisions  Cargo Only Packing In		A187 218	
Special precautions for user	Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions		150 kg 218	
	Passenger and Cargo Maximum Qty / Pack  Passenger and Cargo Limited Quantity Packing Instructions		75 kg Forbidden	
	Passenger and Cargo Limited Maximum Qty / Pack		Forbidden	

#### Sea transport (IMDG-Code / GGVSee)

UN number	3500		
UN proper shipping name	CHEMICAL UNDER PRESSURE, N.O.S. (Hydrofluoroolefin, Nitrogen)		
Transport hazard class(es)	IMDG Class     2.2       IMDG Subrisk     Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number F-C, S-V Special provisions 274 362 Limited Quantities 0		

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
4,4'-diphenylmethane diisocyanate (MDI)	Not Available
polymeric diphenylmethane diisocyanate	Not Available
1,3,3,3-tetrafluoropropene	Not Available
nitrogen	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
4,4'-diphenylmethane diisocyanate (MDI)	Not Available
polymeric diphenylmethane diisocyanate	Not Available
1,3,3,3-tetrafluoropropene	Not Available
nitrogen	Not Available

#### **SECTION 15 Regulatory information**

Version No: **1.3** Page **11** of **12** Issue Date: **08/24/2022** 

#### **APOC Foam System HFO A-side**

Print Date: 08/24/2022

#### 4,4'-diphenylmethane diisocyanate (MDI) is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - Massachusetts - Right To Know Listed Chemicals

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

#### polymeric diphenylmethane diisocyanate is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US DOE Temporary Emergency Exposure Limits (TEELs)

#### 1,3,3,3-tetrafluoropropene is found on the following regulatory lists

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### nitrogen is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

#### US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US TSCA New Chemical Exposure Limits (NCEL)

#### US EPCRA Section 313 Chemical List

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

### US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

US TSCA Chemical Substance Inventory - Interim List of Active Substances

## US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### **Federal Regulations**

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 hazard categories	
Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	Yes
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	Yes
Acute toxicity (any route of exposure)	Yes
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	Yes
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No

#### US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
4,4'-diphenylmethane diisocyanate (MDI)	5000	2270

#### State Regulations

#### US. California Proposition 65

Hazards Not Otherwise Classified

None Reported

#### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (4,4'-diphenylmethane diisocyanate (MDI); polymeric diphenylmethane diisocyanate; nitrogen)	
China - IECSC	Yes	

Nο

Version No: 1.3 Page 12 of 12 Issue Date: 08/24/2022

#### **APOC Foam System HFO A-side**

Print Date: 08/24/2022

National Inventory	Status
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	No (1,3,3,3-tetrafluoropropene)
Philippines - PICCS	No (1,3,3,3-tetrafluoropropene)
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

#### **SECTION 16 Other information**

Revision Date	08/24/2022
Initial Date	02/26/2021

#### CONTACT POINT

\*\*PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
0.3	08/24/2022	Classification, Physical Properties

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit $_{\circ}$ 

IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China

EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals

PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorlTe, from Chemwatch.



# APOC Foam System HFO B-side ICP Construction Inc.

Version No: 1.2

Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Issue Date: **08/25/2022** Print Date: **08/25/2022** S.GHS.USA.EN

#### **SECTION 1 Identification**

Product Identific	er
-------------------	----

Product name	APOC Foam System HFO B-side	
Synonyms	Not Available	
Proper shipping name	Chemical under pressure, n.o.s. (Hydrofluoroolefin, Nitrogen)	
Other means of identification	Not Available	

#### Recommended use of the chemical and restrictions on use

Relevant identified uses Low

Low Pressure Polyurethane Foam B-Component

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	ICP Construction Inc.	
Address	150 Dascomb Road Andover, MA 01810 United States	
Telephone	1-866-667-5119 1-978-623-9987	
Fax	Not Available	
Website	www.icpgroup.com	
Email	sds@icpgroup.com	

#### **Emergency phone number**

• • • •	
Association / Organisation	ChemTel
Emergency telephone numbers	1-800-255-3924
Other emergency telephone numbers	1-813-248-0585

#### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture

#### NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification

Serious Eye Damage/Eye Irritation Category 2A, Skin Corrosion/Irritation Category 2, Reproductive Toxicity Category 1B, Gases Under Pressure (Compressed Gas), Sensitisation (Skin) Category 1

#### Label elements

Hazard pictogram(s)







Signal word

Danger

#### Hazard statement(s)

H31

Causes serious eye irritation.

Version No: 1.2 Page 2 of 14 Issue Date: 08/25/2022 Print Date: 08/25/2022

#### **APOC Foam System HFO B-side**

H315	Causes skin irritation.
H360	May damage fertility or the unborn child.
H280	Contains gas under pressure; may explode if heated.
H317	May cause an allergic skin reaction.

#### Hazard(s) not otherwise classified

Not Applicable

#### Precautionary statement(s) Prevention

P202	Do not handle until all safety precautions have been read and understood.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P271	Use only outdoors or in a well-ventilated area.	
P261	Avoid breathing gas.	
P264	Wash hands and other skin areas exposed to material thoroughly after handling	

#### Precautionary statement(s) Response

P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P302+P352+P333+P313	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	

#### Precautionary statement(s) Storage

P405	Store locked up.	
P410+P403	Protect from sunlight. Store in a well-ventilated place.	

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Not Applicable

#### **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name
111-46-6	5-10	diethylene glycol
13674-84-5*	15-45	tris(2-chloroisopropyl)phosphate
1185-81-5	0.1-1	dibutyltin dilauryl mercaptide
107-21-1	0.1-1	ethylene glycol
29118-24-9	10-20	1.3.3.3-tetrafluoropropene
56-81-5	1-5	glycerol
7727-37-9.	<5	nitrogen

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

#### **SECTION 4 First-aid measures**

#### Description of first aid measures

- If product comes in contact with eyes remove the patient from gas source or contaminated area.
- ► Take the patient to the nearest eye wash, shower or other source of clean water.
- ▶ Open the eyelid(s) wide to allow the material to evaporate.
- F Gently rinse the affected eye(s) with clean, cool water for at least 15 minutes. Have the patient lie or sit down and tilt the head back. Hold the eyelid(s) open and pour water slowly over the eyeball(s) at the inner corners, letting the water run out of the outer corners.
- The patient may be in great pain and wish to keep the eyes closed. It is important that the material is rinsed from the eyes to prevent further damage.
- ▶ Ensure that the patient looks up, and side to side as the eye is rinsed in order to better reach all parts of the eye(s) **Eye Contact** 
  - Transport to hospital or doctor.
  - Feven when no pain persists and vision is good, a doctor should examine the eye as delayed damage may occur.
  - If the patient cannot tolerate light, protect the eyes with a clean, loosely tied bandage.
  - ► Ensure verbal communication and physical contact with the patient.

DO NOT allow the patient to rub the eyes

DO NOT allow the patient to tightly shut the eyes

DO NOT introduce oil or ointment into the eye(s) without medical advice

DO NOT use hot or tepid water.

 Version No: 1.2
 Page 3 of 14
 Issue Date: 08/25/2022

 ADDC Floors System LIFO Paids
 Print Date: 08/25/2022

#### **APOC Foam System HFO B-side**

If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available Skin Contact Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ► Transport to hospital, or doctor. Following exposure to gas, remove the patient from the gas source or contaminated area. NOTE: Personal Protective Equipment (PPE), including positive pressure self-contained breathing apparatus may be required to assure the safety of the rescuer. Prostheses such as false teeth, which may block the airway, should be removed, where possible, prior to initiating first aid procedures. If the patient is not breathing spontaneously, administer rescue breathing. If the patient does not have a pulse, administer CPR. Inhalation If medical oxygen and appropriately trained personnel are available, administer 100% oxygen. ▶ Summon an emergency ambulance. If an ambulance is not available, contact a physician, hospital, or Poison Control Centre for further ▶ Keep the patient warm, comfortable and at rest while awaiting medical care. MONITOR THE BREATHING AND PULSE, CONTINUOUSLY Administer rescue breathing (preferably with a demand-valve resuscitator, bag-valve mask-device, or pocket mask as trained) or CPR if Not considered a normal route of entry. Ingestion Avoid giving milk or oils. Avoid giving alcohol.

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons:

A: Emergency and Supportive Measures

- ▶ Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:
- ► There is no specific antidote

C: Decontamination

- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital: Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes) D: Enhanced elimination:
- ▶ There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal.

 $POISONING\ and\ DRUG\ OVERDOSE,\ Californian\ Poison\ Control\ System\ Ed.\ Kent\ R\ Olson;\ 3rd\ Edition$ 

- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- ▶ Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- ▶ Treatment based on judgment of the physician in response to reactions of the patient

To treat poisoning by the higher aliphatic alcohols (up to C7):

- Gastric lavage with copious amounts of water.
- It may be beneficial to instill 60 ml of mineral oil into the stomach.
- Oxygen and artificial respiration as needed.
- Electrolyte balance: it may be useful to start 500 ml. M/6 sodium bicarbonate intravenously but maintain a cautious and conservative attitude toward electrolyte replacement unless shock or severe acidosis threatens.
- ▶ To protect the liver, maintain carbohydrate intake by intravenous infusions of glucose.
- ▶ Haemodialysis if coma is deep and persistent. [GOSSELIN, SMITH HODGE: Clinical Toxicology of Commercial Products, Ed 5)

#### BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min
- ▶ Monitor and treat, where necessary, for shock
- Monitor and treat, where necessary, for pulmonary oedema.
- Anticipate and treat, where necessary, for seizures.
- DO NOT use emetics. Where ingestion is suspected rinse mouth and give up to 200 ml water (5 ml/kg recommended) for dilution where patient is able to swallow, has a strong gag reflex and does not drool.
- Give activated charcoal.

#### ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- If the patient is hypoglycaemic (decreased or loss of consciousness, tachycardia, pallor, dilated pupils, diaphoresis and/or dextrose strip or glucometer readings below 50 mg), give 50% dextrose.
- · Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

EMERGENCY DEPARTMENT

Version No: 1.2 Page 4 of 14 Issue Date: 08/25/2022

#### **APOC Foam System HFO B-side**

Print Date: 08/25/2022

Laboratory analysis of complete blood count, serum electrolytes, BUN, creatinine, glucose, urinalysis, baseline for serum aminotransferases (ALT and AST), calcium, phosphorus and magnesium, may assist in establishing a treatment regime. Other useful analyses include anion and osmolar gaps, arterial blood gases (ABGs), chest radiographs and electrocardiograph.

- Positive end-expiratory pressure (PEEP)-assisted ventilation may be required for acute parenchymal injury or adult respiratory distress syndrome.
- Acidosis may respond to hyperventilation and bicarbonate therapy.
- Haemodialysis might be considered in patients with severe intoxication.
- Consult a toxicologist as necessary. BRONSTEIN, A.C. and CURRANCE, P.L. EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

For C8 alcohols and above

Symptomatic and supportive therapy is advised in managing patients.

For gas exposures:

#### BASIC TREATMENT

- Establish a patent airway with suction where necessary.
- Watch for signs of respiratory insufficiency and assist ventilation as necessary.
- Administer oxygen by non-rebreather mask at 10 to 15 l/min.
- Monitor and treat, where necessary, for pulmonary oedema .
- Monitor and treat, where necessary, for shock.
- Anticipate seizures.

#### ADVANCED TREATMENT

- Consider orotracheal or nasotracheal intubation for airway control in unconscious patient or where respiratory arrest has occurred.
- Positive-pressure ventilation using a bag-valve mask might be of use.
- Monitor and treat, where necessary, for arrhythmias.
- Start an IV D5W TKO. If signs of hypovolaemia are present use lactated Ringers solution. Fluid overload might create complications.
- Drug therapy should be considered for pulmonary oedema.
- Hypotension with signs of hypovolaemia requires the cautious administration of fluids. Fluid overload might create complications.
- Treat seizures with diazepam.
- Proparacaine hydrochloride should be used to assist eye irrigation.

BRONSTEIN, A.C. and CURRANCE, P.L.

EMERGENCY CARE FOR HAZARDOUS MATERIALS EXPOSURE: 2nd Ed. 1994

#### **SECTION 5 Fire-fighting measures**

#### **Extinguishing media**

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).

#### Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

#### GENERAL Fire Fighting Alert Fire Brigade and tell them location and nature of hazard. Wear full body protective clothing with breathing apparatus Fight fire from a safe distance, with adequate cover. ▶ Containers may explode when heated - Ruptured cylinders may rocket May burn but does not ignite easily. Fire exposed cylinders may vent contents through pressure relief devices thereby increasing vapour concentration.. Fire may produce irritating, poisonous or corrosive gases. Decomposition may produce toxic fumes of: Fire/Explosion Hazard carbon monoxide (CO) carbon dioxide (CO2) hydrogen fluoride other pyrolysis products typical of burning organic material.

#### **SECTION 6 Accidental release measures**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

Methods and material for cont	ainment and cleaning up
Minor Spills	<ul> <li>Avoid breathing vapour and any contact with liquid or gas. Protective equipment including respirator should be used.</li> <li>DO NOT enter confined spaces where gas may have accumulated.</li> </ul>
Major Spills	Clear area of all unprotected personnel and move upwind. Alert Emergency Authority and advise them of the location and nature of hazard. Wear full body clothing with breathing apparatus.

Issue Date: 08/25/2022 Version No: 1.2 Page 5 of 14

#### **APOC Foam System HFO B-side**

Print Date: 08/25/2022

- Remove leaking cylinders to a safe place.
- Fit vent pipes. Release pressure under safe, controlled conditions
- Burn issuing gas at vent pipes.
- ▶ DO NOT exert excessive pressure on valve; DO NOT attempt to operate damaged valve.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

#### **SECTION 7 Handling and storage**

#### Precautions for safe handling

#### Safe handling

- Consider use in closed pressurised systems, fitted with temperature, pressure and safety relief valves which are vented for safe dispersal. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature
- The tubing network design connecting gas cylinders to the delivery system should include appropriate pressure indicators and vacuum or suction lines.
- Fully-welded types of pressure gauges, where the bourdon tube sensing element is welded to the gauge body, are recommended.
- ▶ DO NOT transfer gas from one cylinder to another.

#### Other information

- ▶ Cylinders should be stored in a purpose-built compound with good ventilation, preferably in the open.
- Such compounds should be sited and built in accordance with statutory requirements.
- ▶ The storage compound should be kept clear and access restricted to authorised personnel only.

#### Conditions for safe storage, including any incompatibilities

#### Suitable container

- ▶ Cylinder:
- Ensure the use of equipment rated for cylinder pressure.
- Ensure the use of compatible materials of construction
- Valve protection cap to be in place until cylinder is secured, connected.

### Storage incompatibility

- Figure 1 Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water.
- As a general rule, hydrofluorocarbons tend to be flammable unless they contain more fluorine atoms than hydrogen atoms.
- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
  - react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
  - ▶ should not be heated above 49 deg. C. when in contact with aluminium equipment
  - Avoid magnesium, aluminium and their alloys, brass and steel.
  - Compressed gases may contain a large amount of kinetic energy over and above that potentially available from the energy of reaction produced by the gas in chemical reaction with other substances

#### SECTION 8 Exposure controls / personal protection

#### **Control parameters**

#### Occupational Exposure Limits (OEL)

#### **INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Limits (PELs) Table Z-1	dibutyltin dilauryl mercaptide	Tin, organic compounds (as Sn)	0.1 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	dibutyltin dilauryl mercaptide	Tin (organic compounds, as Sn)	0.1 mg/m3	Not Available	Not Available	[skin] [*Note: The REL applies to all organic tin compounds except Cyhexatin.]
US NIOSH Recommended Exposure Limits (RELs)	ethylene glycol	Ethylene glycol	Not Available	Not Available	Not Available	See Appendix D
US OSHA Permissible Exposure Limits (PELs) Table Z-1	glycerol	Glycerin (mist)- Respirable fraction	5 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Limits (PELs) Table Z-1	glycerol	Glycerin (mist)- Total dust	15 mg/m3	Not Available	Not Available	Not Available
US NIOSH Recommended Exposure Limits (RELs)	glycerol	Glycerin (mist)	Not Available	Not Available	Not Available	See Appendix D

#### **Emergency Limits**

Ingredient	TEEL-1	TEEL-2	TEEL-3
diethylene glycol	6.9 ppm	140 ppm	860 ppm
ethylene glycol	30 ppm	150 ppm	900 ppm
1,3,3,3-tetrafluoropropene	1,400 ppm	Not Available	Not Available
glycerol	45 mg/m3	180 mg/m3	1,100 mg/m3
nitrogen	7.96E+05 ppm	8.32E+05 ppm	8.69E+05 ppm

Ingredient	Original IDLH	Revised IDLH
diethylene glycol	Not Available	Not Available
tris(2-chloroisopropyl)phosphate	Not Available	Not Available

Version No: 1.2 Page **6** of **14** Issue Date: 08/25/2022 Print Date: 08/25/2022

#### **APOC Foam System HFO B-side**

Ingredient	Original IDLH	Revised IDLH
dibutyltin dilauryl mercaptide	25 mg/m3	Not Available
ethylene glycol	Not Available	Not Available
1,3,3,3-tetrafluoropropene	Not Available	Not Available
glycerol	Not Available	Not Available
nitrogen	Not Available	Not Available

#### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
diethylene glycol	Е	≤ 0.1 ppm
tris(2-chloroisopropyl)phosphate	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into s adverse health outcomes associated with exposure. The output of this pro- range of exposure concentrations that are expected to protect worker hea	cess is an occupational exposure band (OEB), which corresponds to a

#### **Exposure controls**

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

#### Personal protection











#### Eye and face protection

- Safety glasses with side shields.
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants.

#### Skin protection

See Hand protection below

#### NOTE:

#### Hands/feet protection

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
- When handling sealed and suitably insulated cylinders wear cloth or leather gloves.

#### **Body protection**

See Other protection below

#### Other protection

- ▶ Protective overalls, closely fitted at neck and wrist.
- Eye-wash unit.
- Ensure availability of lifeline in confined spaces.

#### Respiratory protection

Full face respirator with supplied air.

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- La Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case. cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used
- Positive pressure, full face, air-supplied breathing apparatus should be used for work in enclosed spaces if a leak is suspected or the primary containment is to be opened (e.g. for a cylinder change)
- Air-supplied breathing apparatus is required where release of gas from primary containment is either suspected or demonstrated.

#### **SECTION 9 Physical and chemical properties**

#### Information on basic physical and chemical properties **Appearance** Not Available Compressed Gas Not Available Physical state Relative density (Water = 1) Partition coefficient n-octanol Not Available Not Available Odour / water Not Available Not Available Odour threshold Auto-ignition temperature (°C) Decomposition pH (as supplied) Not Available Not Available temperature (°C) Melting point / freezing point Not Available Viscosity (cSt) Not Available Initial boiling point and boiling Not Available Molecular weight (g/mol) Not Available range (°C)

Version No: **1.2** Page **7** of **14** Issue Date: **08/25/2022** 

#### **APOC Foam System HFO B-side**

Print Date: 08/25/2022

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	<25

#### **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

#### **SECTION 11 Toxicological information**

#### Information on toxicological effects

The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Exposure to fluorocarbons can produce non-specific flu-like symptoms such as chills, fever, weakness, muscle pain, headache, chest discomfort, sore throat and dry cough with rapid recovery. High concentrations can cause irregular heartbeats and a stepwise reduction in lung capacity. Inhalation of the vapour is hazardous and may even be fatal

#### Inhaled

The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing. Before starting consider control of exposure by mechanical ventilation.

Aliphatic alcohols with more than 3-carbons cause headache, dizziness, drowsiness, muscle weakness and delirium, central depression, coma, seizures and behavioural changes. Secondary respiratory depression and failure, as well as low blood pressure and irregular heart rhythms, may follow.

Inhalation of toxic gases may cause:

- ▶ Central Nervous System effects including depression, headache, confusion, dizziness, stupor, coma and seizures;
- respiratory: acute lung swellings, shortness of breath, wheezing, rapid breathing, other symptoms and respiratory arrest;
- heart: collapse, irregular heartbeats and cardiac arrest;
- gastrointestinal: irritation, ulcers, nausea and vomiting (may be bloody), and abdominal pain.

#### Ingestion

Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.

Overexposure to non-ring alcohols causes nervous system symptoms. These include headache, muscle weakness and inco-ordination, giddiness, confusion, delirium and coma.

Not normally a hazard due to physical form of product.

Considered an unlikely route of entry in commercial/industrial environments

### Skin Contact

Skin contact is not thought to produce harmful health effects (as classified under EC Directives using animal models). Systemic harm, however, has been identified following exposure of animals by at least one other route and the material may still produce health damage following entry through wounds, lesions or abrasions.

Fluorocarbons remove natural oils from the skin, causing irritation, dryness and sensitivity.

Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutant

Most liquid alcohols appear to act as primary skin irritants in humans. Significant percutaneous absorption occurs in rabbits but not apparently in man.

Open cuts, abraded or irritated skin should not be exposed to this material

Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

#### Eye

This material can cause eye irritation and damage in some persons.

Not considered to be a risk because of the extreme volatility of the gas.

### Chronic

Repeated or long-term occupational exposure is likely to produce cumulative health effects involving organs or biochemical systems.

Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population.

Ample evidence exists from experimentation that reduced human fertility is directly caused by exposure to the material.

The reactivity of an epoxide intermediate may be the reason for the cancer-causing properties of halogenated oxiranes. It is reported that 1,1-dichloroethyne, vinyl chloride, trichloroethylene, tetrachloroethylene and chloroprene all cause cancer.

Generally speaking, substances with one halogen substitution show higher potential to cause cancer compared to substances with two.

Version No: 1.2 Page 8 of 14

APOC Foam System HFO B-side

Issue Date: 08/25/2022 Print Date: 08/25/2022

Main route of exposure to the gas in the workplace is by inhalation.

There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment. Fluorocarbons can cause an increased risk of cancer, spontaneous abortion and birth defects.

APOC Foam System HFO	TOXICITY	IRRITATION
B-side	Not Available	Not Available
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 11890 mg/kg <sup>[2]</sup>	Eye (rabbit) 50 mg mild
	Inhalation(Rat) LC50; >4.6 mg/l4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
diethylene glycol	Oral (Rat) LD50; 12565 mg/kg <sup>[2]</sup>	Skin (human): 112 mg/3d-I mild
		Skin (rabbit): 500 mg mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: >5000 mg/kg* <sup>[2]</sup>	Eye (rabbit): non-irritating*
tris(2-	Inhalation(Rat) LC50; >4.6 mg/kl/4H*[2]	Skin (rabbit): mild (24 h):
chloroisopropyl)phosphate	Intravenous (Mouse) LD50: 56 mg/kg <sup>[2]</sup>	
	Oral (Rat) LD50; 1500 mg/kg <sup>[2]</sup>	
	Gran (real) EDSO, 1300 mg/kg- 1	
	TOXICITY	IRRITATION
dibutyltin dilauryl mercaptide	Dermal (rabbit) LD50: >1000<2000 mg/kg <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral (Rat) LD50; 136 mg/kg <sup>[2]</sup>	Skin: adverse effect observed (irritating) $^{[1]}$
	TOXICITY	IRRITATION
	dermal (mouse) LD50: >3500 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg/1h - mild
	Oral (Rat) LD50; >2000 mg/kg <sup>[2]</sup>	Eye (rabbit): 12 mg/m3/3D
		Eye (rabbit): 1440mg/6h-moderate
ethylene glycol		Eye (rabbit): 500 mg/24h - mild
		Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin (rabbit): 555 mg(open)-mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY	IRRITATION
1,3,3,3-tetrafluoropropene	Inhalation(Rat) LC50; >1157.752 ppm4h <sup>[2]</sup>	Not Available
	TOXICITY	IRRITATION
glycerol	dermal (guinea pig) LD50: 58500 mg/kg <sup>[1]</sup>	Not Available
•	Oral (Mouse) LD50; 4090 mg/kg <sup>[2]</sup>	
	TOXICITY	IRRITATION
nitrogen	Not Available	Not Available
Legend:	Value obtained from Europe ECHA Registered Substances - Acute to:	vicity 2 * Value obtained from manufacturer's SDS. Unless otherwise
	specified data extracted from RTECS - Register of Toxic Effect of chemic	
APOC Foam System HFO B-side	The following information refers to contact allergens as a group and may Contact allergies quickly manifest themselves as contact eczema, more eczema involves a cell-mediated (T lymphocytes) immune reaction of the	rarely as urticaria or Quincke's oedema. The pathogenesis of contact
DIETHYLENE GLYCOL	The material may cause skin irritation after prolonged or repeated exposivesicles, scaling and thickening of the skin.  Diglycolic acid is formed following the oxidation of accidentally ingested of fatal outcome.	ure and may produce on contact skin redness, swelling, the production of diethylene glycol in the body and can lead to severe complications with
tris(2- chloroisopropyl)phosphate	Non-chlorinated triphosphates have varying chemical, physical, toxicolog source of potential exposure (human and environmental) to triphosphate ingredient in rubber or plastic to the outer surface after curing. For tris(2-chloro-1-methylethyl)phosphate (TCPP)  The flame retardant product supplied in the EU, marketed as TCPP, is act in this reaction mixture are not separated or marketed. The individual cor Alkyl esters of phosphoric acid exhibit a low to moderate acute toxicity at gene damage or affect reproduction. However, 2-ethylhexanoic acid proc	plasticisers / flame retardants. Blooming is the movement of an stually a reaction mixture containing four isomers. The individual isomers mponents are never produced as such. In the model of the mode
DIBUTYLTIN DILAURYL MERCAPTIDE	* Arkema Canada MSDS for substance in 40% mineral oil ** Geleste MS	DS
ETHYLENE GLYCOL	[Estimated Lethal Dose (human) 100 ml; RTECS quoted by Orica] Subst For ethylene glycol: Ethylene glycol is quickly and extensively absorbed throughout the gastr	ance is reproductive effector in rats (birth defects). Mutagenic to rat cells.

Version No: 1.2 Page **9** of **14** Issue Date: 08/25/2022

through the airways; absorption through skin is apparently slow. Following absorption, it is distributed throughout the body.

#### **APOC Foam System HFO B-side**

Print Date: 08/25/2022

#### 1.3.3.3-**TETRAFLUOROPROPENE**

Inhalation (rat) NOEL (28 days): >1.5 mg/l \* \* Vendor HFO-1234ze is not likely to accumulate in the bodies of humans or animals HFO-1234ze is practically non-toxic. Short-term exposures at levels higher than 10% have not induced cardiac sensitization to adrenalin nor induced serious toxic effects. Rats and rabbits did not exhibit any serious toxic, developmental or reproductive effects even with exposures to high levels of HFO-1234ze. Based on a series of mutagenicity and genomics studies, the cancer risk for HFO-1234ze is low, no cardiac sensitisation was observed in dogs with exposures up to 120,000 ppm; repeated dose toxicity in rats (13-wk) found mild effects on the heart (NOEL 5,000ppm); in vitro genotoxicity findings include negative Ames Test and negative human lymphocyte chromosome aberration test; in vivo genotoxicity findings in the mouse micronucleus test were negative (inhalation, mammalian bone-marrow cytogenic test with chromosomal analysis).

#### GLYCEROL

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.

At very high concentrations, evidence predicts that glycerol may cause tremor, irritation of the skin, eyes, digestive tract and airway. Otherwise it is of low toxicity. There is no significant evidence to suggest that it causes cancer, genetic, reproductive or developmental toxicity

#### NITROGEN

No significant acute toxicological data identified in literature search

#### **APOC Foam System HFO** B-side & 1,3,3,3-**TETRAFLUOROPROPENE**

Inhalation of perfluoroalkenes can cause lung injury, kidney damage, brain changes and death. Repeated exposures may alter blood pressure and the production of blood cells. The potential for causing cancer is the subject of speculation.

Disinfection byproducts (DBPs) are formed when disinfectants such as chlorine, chloramines and ozone react with organic and inorganic matter in water. Animal studies have shown that some DBPs cause cancer. To date, several hundred DBPs have been identified. Numerous haloalkanes and haloalkenes have been tested for cancer-causing and mutation-causing activities.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	<b>✓</b>	Reproductivity	✓
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	<b>✓</b>	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

X - Data either not available or does not fill the criteria for classification

Data available to make classification

#### **SECTION 12 Ecological information**

#### Toxicity

APOC Foam System HFO B-side	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	84000mg/l	1
diethylene glycol	NOEC(ECx)	192h	Algae or other aquatic plants	800mg/l	1
	LC50	96h	Fish	>100mg/l	4
	EC50	96h	Algae or other aquatic plants	6500-13000mg	/1 2
	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1008h	Fish	0.8-2.8	7
	EC50	72h	Algae or other aquatic plants	82mg/l	Not Available
tris(2-	ErC50	72h	Algae or other aquatic plants	4mg/l	1
chloroisopropyl)phosphate	EC50	48h	Crustacea	65335mg/	1
	EC50(ECx)	96h	Algae or other aquatic plants	4mg/l	1
	LC50	96h	Fish	56.2mg/l	Not Available
	EC50	96h	Algae or other aquatic plants	4mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
Plant Mar Plant I market and la	EC50	72h	Algae or other aquatic plants	>=1.6mg	/1 2
dibutyltin dilauryl mercaptide	EC50	48h	Crustacea	0.023mg	/1 2
	EC50(ECx)	48h	Crustacea	0.023mg	/1 2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	Not Available	Algae or other aquatic plants	6500-7500mg/	1
ethylene glycol	EC50	48h	Crustacea	>100mg/l	2
	LC50	96h	Fish	>10000mg/l	1
	EC50	96h	Algae or other aquatic plants	6500-13000mg	/I 1
	Endpoint	Test Duration (hr)	Species	Value	Source
1,3,3,3-tetrafluoropropene	EC50	72h	Algae or other aquatic plants	>170mg	/1 2
	EC50	48h	Crustacea	>160mg	/1 2

Version No: 1.2 Page 10 of 14 Issue Date: 08/25/2022 Print Date: 08/25/2022

#### **APOC Foam System HFO B-side**

	EC50(ECx)	48h	Crustacea	>160mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
glycerol	EC0(ECx)	24h	Crustacea	>500mg/l	1
	LC50	96h	Fish	885mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
nitrogen	Not Available	Not Available	Not Available	Not Available	Not Available

In addition to carbon dioxide (CO2), methane (CH4) and nitrous oxide (N2O), the greenhouse gases mentioned in the Kyoto Protocol include synthetic substances that share the common feature of being highly persistent in the atmosphere and inhibit radiation from escaping out of the atmosphere. These synthetic substances include hydrocarbons that are partially fluorinated (HCFs) or totally fluorinated (PFCs) as well as sulfur hexafluoride (SF6). The greenhouse potential of these substances, expressed as multiples of that of CO2, are within the range of 140 to 11,700 for HFCs, from 6500 to 9,200 for PFCs and 23,900 for SF6. DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
diethylene glycol	LOW	LOW
tris(2-chloroisopropyl)phosphate	HIGH	HIGH
dibutyltin dilauryl mercaptide	HIGH	HIGH
ethylene glycol	LOW (Half-life = 24 days)	LOW (Half-life = 3.46 days)
glycerol	LOW	LOW

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
diethylene glycol	LOW (BCF = 180)
tris(2-chloroisopropyl)phosphate	LOW (BCF = 4.6)
dibutyltin dilauryl mercaptide	LOW (LogKOW = 16.42)
ethylene glycol	LOW (BCF = 200)
glycerol	LOW (LogKOW = -1.76)

#### Mobility in soil

Ingredient	Mobility
diethylene glycol	HIGH (KOC = 1)
tris(2-chloroisopropyl)phosphate	LOW (KOC = 1278)
dibutyltin dilauryl mercaptide	LOW (KOC = 6187000000)
ethylene glycol	HIGH (KOC = 1)
glycerol	HIGH (KOC = 1)

#### **SECTION 13 Disposal considerations**

#### Waste treatment methods

Product / Packaging disposal

- Evaporate residue at an approved site.
- Return empty containers to supplier. If containers are marked non-returnable establish means of disposal with manufacturer prior to purchase.

#### **SECTION 14 Transport information**

#### **Labels Required**



Marine Pollutant

#### Land transport (DOT)

UN number	3500
UN proper shipping name	Chemical under pressure, n.o.s. (Hydrofluoroolefin, Nitrogen)

Version No: 1.2 Page 11 of 14 Issue Date: 08/25/2022 Print Date: 08/25/2022

#### **APOC Foam System HFO B-side**

Transport hazard class(es)	Class 2.2 Subrisk Not A	pplicable	
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	Hazard Label Special provisions	2.2 s 362, T50, TP40	

#### Air transport (ICAO-IATA / DGR)

UN number	3500			
UN proper shipping name	Chemical under pressure	Chemical under pressure, n.o.s. * (Hydrofluoroolefin, Nitrogen)		
Transport hazard class(es)	ICAO/IATA Class 2.2 ICAO / IATA Subrisk Not Applicable ERG Code 2L			
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
	Special provisions  Cargo Only Packing Ir  Cargo Only Maximum		A187 218	
Special precautions for user	Passenger and Cargo	Packing Instructions	150 kg 218 75 kg	
	Passenger and Cargo	Passenger and Cargo Maximum Qty / Pack  Passenger and Cargo Limited Quantity Packing Instructions		
	Passenger and Cargo	Limited Maximum Qty / Pack	Forbidden	

#### Sea transport (IMDG-Code / GGVSee)

UN number	3500	
UN proper shipping name	CHEMICAL UNDER PR	RESSURE, N.O.S. (Hydrofluoroolefin, Nitrogen)
Transport hazard class(es)	IMDG Class 2.2 IMDG Subrisk No	2ot Applicable
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number Special provisions Limited Quantities	F-C, S-V 274 362 0

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
diethylene glycol	Not Available
tris(2-chloroisopropyl)phosphate	Not Available
dibutyltin dilauryl mercaptide	Not Available
ethylene glycol	Not Available
1,3,3,3-tetrafluoropropene	Not Available
glycerol	Not Available
nitrogen	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
diethylene glycol	Not Available
tris(2-chloroisopropyl)phosphate	Not Available
dibutyltin dilauryl mercaptide	Not Available
ethylene glycol	Not Available
1,3,3,3-tetrafluoropropene	Not Available
glycerol	Not Available
nitrogen	Not Available

Version No: **1.2** Page **12** of **14** Issue Date: **08/25/2022** 

#### **APOC Foam System HFO B-side**

Print Date: 08/25/2022

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### diethylene glycol is found on the following regulatory lists

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### tris(2-chloroisopropyl)phosphate is found on the following regulatory lists

US - California - Biomonitoring - Priority Chemicals

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

#### dibutyltin dilauryl mercaptide is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US NIOSH Recommended Exposure Limits (RELs)

US OSHA Permissible Exposure Limits (PELs) Table Z-1

#### ethylene glycol is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

US - California Hazardous Air Pollutants Identified as Toxic Air Contaminants

US - California Proposition 65 - Maximum Allowable Dose Levels (MADLs) for

Chemicals Causing Reproductive Toxicity

US - California Proposition 65 - Reproductive Toxicity

US - California Safe Drinking Water and Toxic Enforcement Act of 1986 - Proposition 65 List

US - Massachusetts - Right To Know Listed Chemicals

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

#### 1,3,3,3-tetrafluoropropene is found on the following regulatory lists

US AIHA Workplace Environmental Exposure Levels (WEELs)

US DOE Temporary Emergency Exposure Limits (TEELs)

#### US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

glycerol is found on the following regulatory lists
US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US NIOSH Recommended Exposure Limits (RELs)

#### nitrogen is found on the following regulatory lists

US - Massachusetts - Right To Know Listed Chemicals

US DOE Temporary Emergency Exposure Limits (TEELs)

US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US Clean Air Act - Hazardous Air Pollutants

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

US EPCRA Section 313 Chemical List

US NIOSH Recommended Exposure Limits (RELs)

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US OSHA Permissible Exposure Limits (PELs) Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### **Federal Regulations**

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	No
Gas under pressure	Yes
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No
Acute toxicity (any route of exposure)	No
Reproductive toxicity	Yes
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	Yes
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	No
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	

#### **APOC Foam System HFO B-side**

Print Date: 08/25/2022

#### US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

Name	Reportable Quantity in Pounds (lb)	Reportable Quantity in kg
ethylene glycol	5000	2270

#### **State Regulations**

#### US. California Proposition 65



MARNING: This product can expose you to chemicals including ethylene glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov

#### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (diethylene glycol; tris(2-chloroisopropyl)phosphate; dibutyltin dilauryl mercaptide; ethylene glycol; glycerol; nitrogen)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	No (1,3,3,3-tetrafluoropropene)	
Philippines - PICCS	No (1,3,3,3-tetrafluoropropene)	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (1,3,3,3-tetrafluoropropene)	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

#### **SECTION 16 Other information**

Revision Date	08/25/2022
Initial Date	01/15/2022

#### CONTACT POINT

#### **SDS Version Summary**

Version	Date of Update	Sections Updated
0.2	08/25/2022	Ingredients

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios.

#### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

DSL: Domestic Substances List

NDSL: Non-Domestic Substances List

IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances

ELINCS: European List of Notified Chemical Substances

NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

<sup>\*\*</sup>PLEASE NOTE THAT TITANIUM DIOXIDE IS NOT PRESENT IN CLEAR OR NEUTRAL BASES\*\*

Page **14** of **14** Version No: 1.2 Issue Date: 08/25/2022

#### APOC Foam System HFO B-side

Print Date: 08/25/2022

KECI: Korea Existing Chemicals Inventory

NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances

TSCA: Toxic Substances Control Act

TCSI: Taiwan Chemical Substance Inventory

INSQ: Inventario Nacional de Sustancias Químicas

NCI: National Chemical Inventory
FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.