FASCO AUSTRALIA IS HAPPY TO PROVIDE TECHNICAL ASSISTANCE TO OUR CUSTOMERS IN MANY AREAS. HOWEVER, SINCE FASCO AUSTRALIA IS NOT AWARE OF ALL DATA CONCERNING NOTE : THE USE AND APPLICATION OF THIS MOTOR, THE SUITABILITY OF THE MOTOR FOR THE APPLICATION MUST BE DETERMINED BY AND IS THE RESPONSIBILITY OF THE CUSTOMER MOTOR SPECIFICATION DO NOT SCALE PRINT VARIOUS CUSTOMER Ø 102 TO END SHIELD CUSTOMER PA 32.0 ±1 (BOTH ENDS) CAPACITOR QRNo. uf/V 10W POWEROUTPUT START NIL NIL SH/POLE RUN MOTOR TYPE Ø 7.924 7.912 POLE8 VOLT8 HERTZ PHASE -17.5 FLAT BOTH ENDS BOTH ENDS 240 SINGLE 4 50 TO TALLY ENCLOSED EN CLO SURE SPEED (RPM) AT WINDING 1300 FIXED RATED OUTPUT TYPE 1.0 X 45° CLOCKWISE - LEAD END ROTATION 6.73 FLAT (BOTH ENDS) BOTH ENDS IN SULATION E 120 AOM CLASS TH ER MAL AUTO RESET PROTECTIO RATED 0.38 AMPS AT RATED OUTPUT CURRENT 3 HOLES 3/16" BSW 4 HOLES 3/16" BSW APPLICATION FAN DRIVE EQUISPOCED ON 71.42 PCD SNAP OFF GROOVE EQUISPQCED ON 54.0 PCD (BOTH ENDS) BOTH ENDS TAPPED HOLES IN ENDSHIELDS MOUNTING (BOTH ENDS) (FOR CHANGING ROTATION) BEARING & 608ZZ WIDE RANGE, LONG LIFE LUBRICATION Sales & Sei SUPPLY LEAD **PVC GREY** MULTI STRAND 750 ⁺⁵⁰ (45±5 STRIPPED) LENGTH - 1.85 TERMINATION BOOTLACES SIN G LE MAX. CORE Q.C. HOUSING NIL EARTH VIA SUPPLY LEAD PROVISION BASIC BUILD SPECIFICATION EARTH PERFORMANCE SCREW SPECIFICATION SHAFT MILD STEEL MATERIAL ENDSHIELD SHAKEPROOF CONNECTION PAINT SPEC NIL NIL WASHER DIAGRAM SPECIAL REQUIREMENTS 1) ATTACH TO LEAD IS A PLASTIC BAG CONTAINING Q.C. EARTH POINT 4 - SCREWS 3/16" BSW x 8.0mm PAN POSI HD. 4 - SHAKEPROOF EXTERNAL WASHER 5m m I.D. IMENSIONS IN MINUNUESS OTHERWISE SPECIFIED MATL FRAME 2) RUST PREVENTATIVE IS APPLIED TO MILD STEEL GENERAL TOLERANCES LINEAR: X = 41.0 MOTOR-SHAFTS AFTER ASSEMBLY. FNSH XX = 40.25 3) 6-MOTORS IN HAPPY JACKS PRINTED BOX. 2000 - 40.1 STATUS X = 2 XX = 10.5 4P 10W MURFETTR 05/12/06 DRAWN 4) 1-ONLY INSTRUCTION SHEET 398-060-01 TO BE R SURFACE FINISHES MAX 1.0 MICRO METRES

CHECKED

RELEASED

8CALE

SYMBOLS PERA.S. 1100

This drawing remains the gogerty of Pasco Australia Pty. Ltd. No part or parts of this drawing may be regroduced without

PLACED IN EACH SIX PACK CARTON.

THE END SHIELD.

5) MAX. SCREW PENETRATION 6MM FROM FACE OF

BALCHANT

BALCHANT

01/11/07

01/11/07

AUSTRALIA

ABN 75 000 010 944

1/14 Monterey Road, Dandenong, Victoria

SHEET

A3

DWG.NO

50D501-80AT

REVISION

В