

	V	ЛОТО	OR S	P	ECI	FIC	CAT	101	V		
Q	Q.R. NO.		CUSTOMER PART				NO.	80	8555	NVA-A13	
	VOLTS	24	Ö	Hz	5	0	PH	1		DUTY	A.O.M.
MOTOR RATING	RPM.		13	50 /	3SP					2.5	AMPS
	NOM. OUTPUT				;	315	WAT	TS			
RC	OTATION		C	LO	CK V	VIS	E AT	DR	۷E	END	
CAI	PACITOR	START	-		μF/ V RUN				4	/440 μF/ V	
MO	TOR TYPE	CSR			11	ATION (CLAS	S		B130	
THERMAL	PROTECTION		1	ΑU	TO F	RES	ET O	VEF	RLC	AD	
DATA	A TEST NO.	W443-1725-			SL		Paint/ Olour		GREY #5082		

SPECIAL REQUIREMENTS:

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN MM.

TOLERANCES

THIS DRAWING REMAINS THE PROPERTY OF REGAL BELOIT AUSTRALIA AND MAY NOT BE USED, COPIED OR ISSUED WITHOUT WRITTEN PERMISSION FROM REGAL

DECIMALS

.X ± 1.0

.XX ± 0.1

BELOIT AUSTRALIA

- After the motor is complete, applied rust proof oil at shaft end.
- 2) The tensile strength of each lead wire at least 4 Kgs.
 3) The runout of the shaft end circumference 0.10 mm.

ANGULAR

± 30'

MOTOR WEIGHT

DRAWN

CHECKED

RELEASED

SCALE

6.28

N.T.S.


THANATCHA

EKAPHOP

WEERAPAN

			MODEL	5NVA-A13		
					DDMMYY	XXXX
VOLTS	240	R.P.M	. 1350/3SP	CLASS B130	Hz	50
WATTS	315	TYPE	CSR	μF/V R 4/440	Ph	1
AMPS	2.5	DUTY	AOM	PROT. AUTO)	

Marathon



FRAME

STATUS

SHEET

NAMEPLATE

kg. BCB 01/02/2023 01/02/2023 01/02/2023 01/02/2023 01/02/2023 03 9546 3833 MOTOR
315W 4P 3SP 240V S/S CW DE PSC
FASCO MODEL 808555NVA-A13

DWG. NO. REVISION B