

		ИОТС	R SF	PEC	CIFIC	CAT	IO	N			SPECIAL REQUIREME 1) After the motor is complete, as		
Q	Q.R. NO.		QR230046		CUSTOMER PART N			NO. 808557KTB-A11					
	VOLTS	240	0 H	-lz	50	PH		1	DUTY	A.O.M.	3) The runout of the shaft end cir		
MOTOR RATING	RPM.		900	/3SF	•				1.2	AMPS	4) Default : rotation clockwise :5) Motor to be packed in single		
	NOM. OUTPUT				150								
ROTATION		CLOCKWISE DRIVE END (REVERSIBLE)								UNLESS OTHERWISE SPECIFIED : DIMENSIONS ARE IN MM.			
CAPACITOR		START	RT μF/ ν			RUN	6/44			μF/ V			
MO	TOR TYPE	C	SR		INSUL	ATION (CLAS	SS		B130	.X ± 1.0 ± 30'		
THERMAL	THERMAL PROTECTION		A	UTO	RES	.XX ± 0.1 THIS DRAWING REMAINS THE PROPERTY OF REGAL							
DATA TEST NO.		W443-2911-SL PAINT/ COLOUR					GREY #5082				BELOIT AUSTRALIA AND MAY NOT BE USED, COPIED OR ISSUED WITHOUT WRITTEN PERMISSION FROM REGAL BELOIT AUSTRALIA		

PECIAL REQUIREMENTS:

After the motor is complete, applied rust proof oil at shaft end.

The tensile strength of each lead wire at least 4 Kgs.

MOTOR WEIGHT

DRAWN

CHECKED

RELEASED

SCALE

6.19

N.T.S.

14/08/2023

14/08/2023

14/08/2023

THANATCHA


EKAPHOP

WEERAPAN

- The runout of the shaft end circumference 0.08 mm.
- Default: rotation clockwise at drive end.

Motor to be packed in single carton.

			MODEL	. 81	M8557	7KTB-A11S		
						DDMMYY	XXXX	
DLTS	240	R.P	.M. 900/3SP	CLASS	B130	Hz	50	
ATTS	150	TYF	E CSR	μF/V R	6/440	Ph	1	
/IPS	1.2	DUT	Y AOM	PROT.	AUTO			



NAMEPLATE

BCB Sales & Service (Vic)

STATUS sales&bcbsales.com.au 03 9546 3833

MOTOR 150W 6P 3SP 240V S/S REV FASCO MODEL 808557KTB-A11S

SHEET DWG, NO.

FRAME

R

A3

8M8557KTB-A11S

REVISION Α