

		лотс	R SF	PEC	IFIC	CATI	ON			SPECIAL REQUIREN 1) After the motor is complete.		
Q.R. NO.		QR230048		CUSTOMER PART N			10. 80	855B(QVA-A25S			
MOTOR RATING	VOLTS	240	0	łz	50	PH	1	DUTY	A.O.M.	3) The runout of the shaft end		
	RPM.		13	370	70			4.4	AMPS	4) Capacitor supplied by Custo 5) Motor to be packed in single		
	NOM. OUTPUT]							
ROTATION		CLOCKWISE DRIVE END								UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MM.		
CAPACITOR		START	START		μF/ V	RUN	:	25/440 μF/ V		TOLERANCES DECIMALS ANGULAR		
MOTOR TYPE		CSR			INSULATION CLA				B130	.X ± 1.0 ± 30'		
THERMAL	THERMAL PROTECTION		Al	UTO	.XX ± 0.1 THIS DRAWING REMAINS THE PROPERTY OF REGAL BELOIT AUSTRALIA AND MAY NOT BE USED, COPIED OR ISSUED WITHOUT WRITTEN PERMISSION FROM REGAL BELOIT AUSTRALIA							
DATA TEST NO.		W////3_2U13_SI						Paint/ Olour	GREY #5082			

SPECIAL REQUIREMENTS:

- 1) After the motor is complete, applied rust proof oil at shaft end.
- The tensile strength of each lead wire at least 4 Kgs.

MOTOR WEIGHT

THANATCHA

EKAPHOP

WEERAPAN

N.T.S.

05/08/2023

05/08/2023

05/08/2023

DRAWN

SCALE

CHECKED


RELEASED

The runout of the shaft end circumference 0.10 mm.

- Capacitor supplied by Customer.
- Motor to be packed in single carton.

UNLESS OTHERWISE SPECIFIED:

			MODEL	. 8N	1855E	BQVA-A25S	
						DDMMY	YXXXX
VOLTS	240	R.P.I	И. 1370	CLASS	B130	Hz	50
WATTS	750	TYPE	CSR	μF/V R	25/440	Ph	1
AMPS	4.4	DUT	Y AOM	PROT.	AUTO		



NAMEPLATE

BCB Sales & Service (Vic) sales@bcbsales.com.au 03 9546 3833

FRAME **MOTOR** STATUS R FASCO MODEL 80855BQVA-A25S

DWG. NO.

SHEET

A3

REVISION 8M855BQVA-A25S Α

750W 4P 1SP 240V S/S CW DE