

ROTARY GRATE SEPARATOR

Process Line Motorized Hopper Magnet



- Unique solution for high volume flow of powdery granules, high viscosity flow of fluids and dry grains with micro impurities. The rotating movement of the magnetic cartridge aids in material flow and prevents caking.
- Depending on the size of raw materials, the annular configuration & number of magnet rods can be increased or decreased.
- The magnetic cartridge can be easily removed for cleaning.

Product Code: RGS

All dimensions in metric units

Model No.	Dimensions (mm)				Motor (KW)	No. of Rods	Weight (Kg)
	Inlet Dims	A	B	H			
RGS-R-150	150	205	208	450	0.25	7	30
RGS-R-200	200	255	258	500	0.25	9	38
RGS-R-250	250	305	308	550	0.25	11	50
RGS-R-300	300	355	358	600	0.37	13	62
RGS-R-350	350	405	408	650	0.37	15	78
RGS-S-2020	200 x 200	205	208	270	0.25	7	28
RGS-S-2525	250 x 250	255	258	320	0.25	9	35
RGS-S-3030	300 x 300	305	308	370	0.25	11	47
RGS-S-3535	350 x 350	355	358	420	0.37	13	58

Due to continuous upgradation in design there could be changes in specification. Other sizes on request. Before ordering, contact Supreme Magnets or your nearest dealer to confirm the suitability of this model for your application.



IMPURITY SEPARATION

