

18 Inch (Reverse Rim)		Super Low Disk	Low Disk
		5-114.3	5-100, 5-112, 5-114.3
Diameter	Width	Offset Range	
18	7.5J	48 ~ 31	39 ~ 22
18	8.0J	54 ~ 25	45 ~ 16
18	8.5J	56 ~ 18	51 ~ 9
18	9.0J	56 ~ 19	54 ~ 10
18	9.5J	56 ~ 18	54 ~ 9
18	10.0J	56 ~ 24	52 ~ 11

! Not TPMS Compatible (Adapter is required for TPMS support).

19 Inch (Normal Rim)		Super Low Disk	Low Disk
		5-114.3	5-100, 5-112, 5-114.3
Diameter	Width	Offset Range	
19	8.0J	31 ~ 20	22 ~ 11
19	8.5J	37 ~ 13	28 ~ 4
19	9.0J	43 ~ 19	34 ~ 10
19	9.5J	50 ~ 14	41 ~ 5
19	10.0J	53 ~ 20	47 ~ 11
19	10.5J	53 ~ 19	52 ~ 10
19	11.0J	53 ~ 20	52 ~ 11

! Not TPMS Compatible (Adapter is required for TPMS support).

19 Inch (Reverse Rim)		Super Low Disk	Low Disk	High Disk
		5-114.3	5-100, 5-112, 5-114.3, 5-120	5-114.3
Diameter	Width	Offset Range		
19	7.5J	48 ~ 39	39 ~ 30	27 ~ 18
19	8.0J	54 ~ 33	45 ~ 24	33 ~ 12
19	8.5J	56 ~ 26	51 ~ 17	39 ~ 5
19	9.0J	56 ~ 19	54 ~ 10	46 ~ 2
19	9.5J	56 ~ 18	54 ~ 9	46 ~ 3
19	10.0J	56 ~ 24	54 ~ 15	46 ~ 3
19	10.5J	56 ~ 21	54 ~ 12	46 ~ 0

20 Inch (Normal Rim)		Super Low Disk	Low Disk	High Disk
		5-114.3	5-100, 5-112, 5-114.3, 5-120	5-114.3
Diameter	Width	Offset Range		
20	8.5J	36 ~ 21	27 ~ 12	15 ~ 0
20	9.0J	42 ~ 14	33 ~ 5	21 ~ -7
20	9.5J	49 ~ 9	40 ~ -1	28 ~ -13
20	10.0J	53 ~ 2	46 ~ -7	34 ~ -19
20	10.5J	53 ~ 8	52 ~ -1	40 ~ -13
20	11.0J	53 ~ 9	52 ~ -1	43 ~ -13

! Not TPMS Compatible (Adapter is required for TPMS support).

20 Inch (Reverse Rim)		Super Low Disk	Low Disk	High Disk
		5-114.3	5-112, 5-114.3, 5-120	5-112, 5-114.3, 5-120
Diameter	Width	Offset Range		
20	8.0J	54 ~ 33	45 ~ 24	33 ~ 12
20	8.5J	42 ~ 14	51 ~ 17	39 ~ 5
20	9.0J	49 ~ 9	54 ~ 10	46 ~ -2
20	9.5J	53 ~ 2	54 ~ 9	46 ~ -3
20	10.0J	53 ~ 8	54 ~ 15	46 ~ 3
20	10.5J	53 ~ 9	54 ~ 12	46 ~ 0

21 Inch (Normal Rim)		Super Low Disk	Low Disk	High Disk
		5-114.3	5-112, 5-114.3, 5-120	5-112, 5-114.3, 5-120
Diameter	Width	Offset Range		
21	9.0J	48 ~ 20	39 ~ 11	27 ~ 1
21	9.5J	54 ~ 13	45 ~ 4	33 ~ -8
21	10.0J	55 ~ 13	51 ~ 4	39 ~ -8
21	10.5J	55 ~ 20	51 ~ 11	46 ~ -1
21	11.0J	55 ~ 20	51 ~ 11	47 ~ -1

! Not TPMS Compatible (Adapter is required for TPMS support).

COLOR OPTION:

18" - Matte Gunmetallic / Black Polish

19" - Matte Gunmetallic / Black Polish

20" Normal Rim - Matte Gunmetallic / Black Polish

20" Reverse and 21" -Matte Gunmetallic / Black Polish / Brushed

RIM COLOR OPTION:

Standard finish is Anodized Polished

With additional cost. Gloss Black (Painted) is available



* Hub bore size: 5-100 = 65mm / 5-112 = 66.5mm / 5-114.3 = 73mm / 5x120 = 72.5mm

* You must specify that you would like to have TPMS support on your 19, 20 or 21 inch 910M upon ordering.

If it is not specified, we will build the wheel without TPMS support.

* If the wheel cannot be made TPMS compatible from the Weds factory. Optional TPMS adapter can be used and is sold separately

* Unlisted vehicle bolt pattern might be available. Please contact us for details.

* Any questions regarding disk type. Please contact us for support.

* All specifications are subject to change without prior notice.