



### □ **G1696** Emergency Shower, Free Standing, Stainless Steel Construction

**Application:** Free standing emergency shower. Ideal for use in areas where highly corrosive materials are handled, as well as in laboratory and clean room applications.

**Shower Head:** 10" diameter stainless steel with 20 GPM flow control.

**Valve:** 1" IPS stainless steel stay-open ball valve. Valve has stainless steel ball and PTFE seals. Furnished with stainless steel actuating arm and 29" stainless steel pull rod.


**Pipe and Fittings:** Schedule 40 stainless steel. Furnished with orange polyethylene covers on vertical piping for high visibility and corrosion resistance.

**Supply:** 1 1/4" NPT female top or side inlet.

**Sign:** ANSI-compliant identification sign.


#### Available Options

- **AP275-200** Electric flashing light and alarm horn unit for mounting on wall or vertical pipe. Light illuminates and horn sounds when shower is activated. Furnished complete with flow switch and mounting hardware.
- **AP250-015** Modesty curtain for horizontal shower installation.
- **G3800LF** Thermostatic mixing valve precisely blends hot and cold water to deliver warm (tepid) water as required by ANSI Z358.1-2014. Refer to "Tempering Valves" section for complete technical and product selection information.





### □ G1696 Emergency Shower, Free Standing, Stainless Steel Construction



THIS SPACE FOR ARCHITECT/ENGINEER APPROVAL

Sign Included



Due to continuing product improvement, the information contained in this document is subject to change without notice. All dimensions are ± 1/4" (6mm). rev. 1117

