

Product Specifications

MODEL
TG24-3WW & TG24-3WB
TG24-3PW & TG24-3PB

CATEGORY
Circulation

DESCRIPTION
Tuff & Gusty™ brand 24" circulation fan with OSHA guards and 3-speed motor with pull chain switch designed for agriculture, horticulture and industrial use.

TG24-3WW and TG24-3PW shown; also available in black



FEATURES

- Totally enclosed, maintenance-free ball bearing, permanently lubricated, permanent split capacitor motor with three-speed pull chain.
- Durable powder-coated steel fan guard meets OSHA requirements.
- Ten foot, 115 volt grounded cord attached. Includes mount as shown.
- UL 507 listed; suitable for outdoor use in wet locations when installed on a GFCI protected circuit.

DIMENSIONS

	Fan Alone	Fan w/Wall Mount	Fan w/Pedestal Mount
Height & Width	26"		
Guard Depth	5-1/2"		
Total Depth	15"		

PERFORMANCE

CCFM	4769 (high)	4397 (medium)	3688 (low)
Test Number	Schaefer 0396	Schaefer 0397	Schaefer 0398

MOTOR

HVW-24M	280 watts - 3 speeds	Type = TE	120 Volts	2.65 Amps
---------	----------------------	-----------	-----------	-----------

SHIPPING

TG24-3WW	42 lbs	28" x 8" x 41"	UPS = Yes	Pallet Quantity = 10
TG24-3WB	42 lbs	28" x 8" x 41"	UPS = Yes	Pallet Quantity = 10
TG24-3PW				
TG24-3PB				



800-779-3267

sales@schaeferfan.com • www.schaeferfan.com

Test data, performance, energy consumption and other specifications are based on results in a controlled environment. Actual results will vary. Product specifications subject to change. ©2012 Schaefer Ventilation Equipment 5-11-12