

SPECIFIED

SOLUTIONS
Commercial Floors & Walls

Estate Hickory
Engineered



EH0093CH



EH7018CH



EH0093CH

Style Number	EH486	
Construction	Engineered	
Species	Hickory	
Nominal Overall Thickness	9/16"	
Nominal Width	7.48"	
Finish	UV Aluminum Oxide	
Gloss Level	10%	
Surface Texture	Wirebrushed	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Profile	Tongue And Groove	
Weight per Carton	56.22 lbs	
SQFT per Carton	31.09 sq ft	
SQFT per Pallet	1243.6 sq ft	
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	50 Years	
Commercial Warranty	5 Year Commercial	
All measurements are nominal.	Cartons may include random lengths.	3-mm Wear Layer

Hickory is one of the most durable wood flooring choices available. It requires minimal maintenance and is one of the more water-resistant wood flooring options. Registering 1820 on the Janka scale, it is scratch resistant and durable.

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH12
Flush Reducer



SORH2
*Overlap Reducer



SSH12
Flush Stairnose



SOSH2
*Overlap Stairnose



SCH12
Threshold / Carpet



TMH78
T-Molding



QTR96
Quarter Round

SPECIFIED

SOLUTIONS

Commercial Floors & Walls