

SPECIFIED

SOLUTIONS
Commercial Floors & Walls

Estate Oak
Engineered



EO146CW



EO508CW



EO514CW



EO1010CW



EO1070CW



EO1075CW



EO986CW



EO533CW



EO2047CW



EO5031CW

Style Number	EO485
Construction	Engineered
Species	White Oak
Nominal Overall Thickness	9/16"
Finish	UV Aluminum Oxide
Gloss Level	7%
Surface Texture	Wirebrushed
Edge Description	Micro Bevel
End Description	Micro Bevel
Installation Methods	Nail, Staple, Glue, Floating
Installation Grade	Above, On, Below
Variation	High
GREENGUARD® Certified	Yes
Radiant Heat Approved	Yes
Warranty	Lifetime Structural Warranty

All measurements are nominal.

Cartons may include random lengths.

3-mm Wear Layer

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH12
Flush
Reducer



SORH2
*Overlap
Reducer



SSH12
Flush
Stairnose




SOSH2
*Overlap
Stairnose



SCH12
Threshold /
Carpet
Reducer



TMH78
T-Molding



QTR96
Quarter
Round