

SPECIFIED

SOLUTIONS
Commercial Floors & Walls

Foundation Oak
Engineered



FO1080CO



FO1038CO



FO5056CO



FO1083CO



FO1038CO

Style Number	FO676	
Construction	Engineered	
Species	White Oak	
Nominal Overall Thickness	3/8"	
Nominal Width	5"	
Finish	UV Aluminum Oxide	
Gloss Level	7%	
Surface Texture	Wirebrushed	
Edge Description	Micro Bevel	
End Description	Micro Bevel	
Weight per Carton	36.61 lbs	16.6 kg
SQFT per Carton	29.53 sq ft	2.74 sq m
SQFT per Pallet	1181.2 sq ft	109.73 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Warranty	Lifetime Structural Warranty	
All measurements are nominal.	Cartons may include random lengths.	2-mm Wear Layer

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH38
Flush
Reducer



SORH8
*Overlap
Reducer



SSH38
Flush
Stairnose



SOSH8
*Overlap
Stairnose



SCH38
Threshold /
Carpet
Reducer



TMH78
T-Molding



QTR96
Quarter
Round