

SPECIFIED

SOLUTIONS
Commercial Floors & Walls

Haute Oak
Engineered



HO1045



HO2034



HO5056



HO1045

Style Number	HO689		
Construction	Engineered		
Species	White Oak		
Nominal Overall Thickness	1/2"		
Nominal Width	7.5"		
Finish	UV Aluminum Oxide		
Gloss Level	7%		
Surface Texture	Wirebrushed		
Edge Description	Micro Bevel		
End Description	Micro Bevel		
Weight per Carton	51.7 lbs		
SQFT per Carton	31.08 sq ft		
SQFT per Pallet	1398.6 sq ft		
Installation Methods	Nail, Staple, Glue, Floating		
Installation Grade	Above, On, Below		
Variation	High		
GREENGUARD® Certified	Yes		
Cradle-to-Cradle Certified	Yes		
Radiant Heat Approved	Yes		
Warranty	Lifetime Structural Warranty		
All measurements are nominal.	Cartons may include random lengths.	2-mm Wear Layer	

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SRH12
Flush
Reducer



SORH2
*Overlap
Reducer



SSH12
Flush
Stairnose



SOSH2
*Overlap
Stairnose



SCH12
Threshold /
Carpet
Reducer



TMH78
T-Molding



QTR96
Quarter
Round