

Click Wood

Engineered Wood with Waterproof Core

Click-Lock Installation

Attached Cushion for Noise Reduction



Click Wood

Engineered Wood with Waterproof Core

Click-Lock Installation

Attached Cushion for Noise Reduction

Colors



SS-01052-BH Hickory



SS-01054-AW Walnut




SS-01057-BO Oak



SS-01058-CO Oak



SS-01084-FO Oak



SS-02039-RW Walnut



SS-02040-WO Oak




SS-02042-NH Hickory



SS-02056-HO Oak




SS-05065-SO Oak



SS-07053-RW Walnut

- Scuff-Resistant Finish
- Waterproof Core
- Sealed for additional protection from water & spills
- Click-lock install
- Attached pad for sound reduction

SPECIFIED | **SOLUTIONS**
Commercial Floors & Walls



Click Wood

Engineered Wood with Waterproof Core

Click-Lock Installation

Attached Cushion for Noise Reduction

Construction	Engineered
Species	Oak, Hickory, Walnut
Nominal Overall Thickness	5/16"
Nominal Width	7.5"
Finish	Waterproof
Gloss Level	7%
Surface Texture	Wirebrushed
Edge Description	Bevel
End Description	Bevel
Weight per Carton	55.5 lbs
SQFT per Carton	22.45 sq ft
SQFT per Pallet	1347 sq ft
Installation Methods	Floating / Glue-Down
Installation Grade	Above, On, Below
Variation	High
Ortho-Phthalates Free	Yes
Radiant Heat Approved	Yes


All measurements are nominal.

Cartons may include random lengths.


Click Wood is engineered wood plank flooring with unique features: *Scuff-Resistant Finish

*Waterproof Core *Sealed for additional protection from water & spills *Click-lock install *Attached pad for sound reduction


Trim Pieces length: 94"



FHTRS
Threshold*



FHTMD
T-Molding*



FHRDC
Multi-Purpose Reducer*



FHQTR
Quarter Round



FHFST
Flush Stairnose*

SPECIFIED | **SOLUTIONS**
Commercial Floors & Walls

www.SpecifiedSolutionsInc.com
info@specifiedsolutionsinc.com
(864) 414-3675

